

TE Internal Number: 1617119-6

Not EU RoHS or ELV Compliant

- 1MA TO-5 Relay Series
- Input Voltage = 26.5 VDC
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Contact Current Rating = 1 A
- Non Polarized, Monostable Coil Magnetic System

[View all Features](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

- None Available

- [RELAY](#) (PDF, English)

- None Available

- None Available

- None Available

- None Available

- Product Line Information

- Tooling

[List all Documents](#)

- Termination Type = Long Leads

- Input Voltage (VDC) = 26.5
- Contact Current Rating (A) = 1
- Coil Polarity Protection Diode = Without
- Transistor Driver = Without
- Coil Resistance (Ω) = 2000
- MOSFET Driver = Without
- Coil Power Measurement = Milliwatts
- Coil Power, Nominal (mW) = 351
- Actuating System = DC
- Shock = 75 G's, 6ms
- Vibration = 30G's, 10 to 3000Hz

- Series = 1MA TO-5 Relay

- Mounting Options = PC Board
- Enclosure Type = Hermetically Sealed
- Approved Standards = M39016 Qualified, L Level

- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Coil Magnetic System = Non Polarized, Monostable
- Coil Suppression Diode = Without

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M39016/7-023L
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Not suitable for lead free processing

- Temperature Range (°C) = -65 - +125

- Brand = CII