


Ultrafast Dual Diode

60 A, 200 V

FFA60UP20DN



1. Anode 2. Cathode 3. Anode

Description

The FFA60UP20DN is an ultrafast diode with low forward voltage drop and rugged UIS capability. This device is intended for use as freewheeling and clamping diodes in a variety of switching power supplies and other power switching applications. It is specially suited for use in switching power supplies and industrial applications as Welder and UPS application.

Features

- Ultrafast Recovery, $T_{rr} < 32$ ns (@ $I_F = 30$ A)
- Max. Forward Voltage, $V_F = 1.15$ V (@ $T_C = 25^\circ\text{C}$)
- Reverse Voltage: $V_{RRM} = 200$ V
- Avalanche Energy Rated
- These Devices are Pb-Free and are RoHS Compliant

Applications

- Power Switching Circuits
- Output Rectifiers
- Free-Wheeling Diodes
- SMPS
- Welder
- UPS

ABSOLUTE MAXIMUM RATINGS


(per diode) $T_C = 25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Value	Unit
DC Blocking Voltage	V_R	200	V
Peak Repetitive Reverse Voltage	V_{RRM}	200	V
Working Peak Reverse Voltage	V_{RWM}	200	V
Average Rectified Forward Current (@ $T_C = 100^\circ\text{C}$)	$I_{F(AV)}$	30	A
Non-repetitive Peak Surge Current 60 Hz Single Half-Sine Wave	I_{FSM}	300	A
Operating Junction and Storage Temperature	T_J, T_{STG}	-65 to +175	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Maximum Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.4	°C/W

1. Anode 2. Cathode 3. Anode
TO-3P-3LD / EIAJ SC-65, ISOLATED
CASE 340BZ

MARKING DIAGRAM



\$Y = Logo
&Z = Assembly Plant Code
&3 = Date Code
&K = Lot Run Traceability Code
F60UP20DN = Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

ELECTRICAL CHARACTERISTICS

(per diode) $T_C = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_F (Note 1)	Maximum Instantaneous Forward Voltage	$I_F = 30 \text{ A}, T_C = 25^\circ\text{C}$ $I_F = 30 \text{ A}, T_C = 100^\circ\text{C}$	—	—	1.15 1.0	V
I_R (Note 1)	Maximum Instantaneous Reverse Current	$V_R = 200 \text{ V}, T_C = 25^\circ\text{C}$ $V_R = 200 \text{ V}, T_C = 100^\circ\text{C}$	—	—	10 100	μA
t_{rr}	Reverse Recovery Time	$I_F = 30 \text{ A}, dI_F/dt = 200 \text{ A}/\mu\text{s}, V_R = 130 \text{ V}$	—	32	—	ns
I_{rr}	Reverse Recovery Current		—	2.4	—	A
Q_{rr}	Reverse Recovery Charge		—	38.4	—	nC
t_{rr}	Maximum Reverse Recovery Time	$I_F = 1 \text{ A}, dI_F/dt = 100 \text{ A}/\mu\text{s}$	—	—	40	ns
W_{AVL}	Avalanche Energy	$L = 40 \text{ mH}$	2	—	—	mJ

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. Pulse Test: Pulse Width = 300 μs , Duty Cycle = 2%

TEST CIRCUIT AND WAVEFORMS




Figure 1. Diode Reverse Recovery Test Circuit & Waveform










Figure 2. Unclamped Inductive Switching Test Circuit & Waveform

ORDERING INFORMATION


Part Number	Top Mark	Package	Shipping
FFA60UP20DNTU	F60UP20DN	TO-3P-3LD (Pb-Free)	30 Units / Tube

TYPICAL CHARACTERISTICS



TO-3P-3LD / EIAJ SC-65, ISOLATED
CASE 340BZ
ISSUE O

DATE 31 OCT 2016



DOCUMENT NUMBER:	98AON13862G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO-3P-3LD / EIAJ SC-65, ISOLATED	PAGE 1 OF 1

onsemi and Onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **ONSEMI**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales

