



Pushing Performance
Since 1945

Circular Connector w. Harax M12 L 4 F



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 21 03 212 2305 |
| Specification | Circular Connector w. Harax M12 L 4 F |
| HARTING eCatalogue | https://harting.com/21032122305 |

Identification

| | |
|----------------|-------------------------|
| Category | Connectors |
| Series | Circular connectors M12 |
| Identification | M12-L |
| Element | Cable connector |
| Specification | Straight |

Version

| | |
|--------------------|------------------------------|
| Termination method | HARAX® connection technology |
| Gender | Female |
| Shielding | Unshielded |
| Number of contacts | 4 |
| Coding | A-coding |
| Locking type | Screw locking |

Technical characteristics

| | |
|-------------------------------|-------------------|
| Conductor cross-section | 0.34 ... 0.75 mm² |
| Conductor cross-section [AWG] | AWG 22 ... AWG 18 |
| Wire outer diameter | ≤2.6 mm |
| Rated current | 4 A |
| Rated voltage | 50 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| Overvoltage category | III |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---|-----------------------------|
| Insulation resistance | $>10^8 \Omega$ |
| Contact resistance | $\leq 10 \text{ m}\Omega$ |
| Tightening torque | 0.6 Nm |
| Wrench size (knurled screw / knurled nut) | 17 |
| Limiting temperature | -40 ... +85 °C |
| Mating cycles | ≥ 100 |
| Degree of protection acc. to IEC 60529 | IP65 / IP67 mated condition |
| Cable diameter | 6 ... 8 mm |
| Isolation group | I ($600 \leq \text{CTI}$) |

Material properties

| | |
|--------------------------------------|--|
| Material (insert) | Polyamide (PA) |
| Material (contacts) | Brass |
| Surface (contacts) | Au over Ni Mating side |
| Material (hood/housing) | Polyamide (PA) Zinc die-cast |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 0d7d3693-d625-47ab-934a-d241bf72c86e |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| | |
|----------------|-----------------|
| Specifications | IEC 61076-2-101 |
|----------------|-----------------|



Pushing Performance
Since 1945

Specifications and approvals

| | |
|----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E102079 |
| | CSA-C22.2 No. 182.3 ECBT8.E102079 |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 38 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140137301 |
| eCl@ss | 27440116 Circular connector (for field assembly) |
| ETIM | EC002635 |
| UNSPSC 24.0 | 39121413 |