







Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.

NOTE	
Purchased assembly includes box, lid and 4 cover screws.	
Box and lid are made from Diecast Aluminum Alloy.	
Silicone Gasket supplied with liquid resistant enclosure.	

PART NUMBERS		
1590K Enclosure		
Natural Finish Enclosure	1590K	
Black Textured Enclosure	1590KBK	
1590K Liquid Resistant Enclosure (Silicon	e Gasket)	
Natural Finish Enclosure	1590W K	
Black Textured Enclosure	1590W KBK	
ACCESSORIES		
Recommended Torque: 75 ozf.in / 55 cN.m		
Liquid Resistant Cover Screws		
Stainless Steel Cover Screws (Pkg 100)		
[6-32 x 1/2" With O-Ring]	1590W M S 100	
Black Stainless Steel Cover Screws (Pkg 100)	1590W M S 100B K	
[6-32 x 1/2" With O-Ring]	1390W W 3 100BK	
Standard Cover Screws		
Plated Cover Screws (Pkg 100)	1590MS100	
[6-32 x 1/2"]	10001110100	
Black Cover Screws (Pkg 100)	1590MS100BK	
[6-32 x 1/2"]		
HAMMONI	$\overline{}$	
🖊 📕 🦊 MANUFACTI		
4 = 0.017		
■ <b>I I</b> 1590K		

Dimensions: mm [inches]

www.hammondmfg.com

2