

# **SKINDICHT® MR-M**

SKINDICHT® MR-M, reducer, enables the use of cable gland with smaller connection threads than the existing threaded holes





Space requirement



Reliability



Connector with standard housing unit

### **Benefits**

Corrects the size difference between the connection thread of a cable gland and the threaded hole in an enclosure. Provides flexibility in the selection of a cable gland, as the selection is independent to the threaded hole of the enclosure. Article numbers ending in "LF" are lead-free product alternatives with the same product properties. "Lead-free" articles do not contain lead, which is currently still allowed to make up to four percent in copper alloys. It could be banned in the future according to the RoHS Directive.

## **Application range**

For use with a metric cable gland whose connection thread is smaller than the existing threaded hole. Withstands high chemical and mechanical stress. Suitable for outdoor use.

## **Product Make-up**

Metric connection thread acc. to DIN EN 60423 Basis for technical information DIN IEC 62444

### **Technical Data**

Classification ETIM 5: ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6: ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

On request: Also available with pre-installed O-ring

Material: Nickel-plated brass

Temperature range: -60 °C to +200 °C

Last Update (14.04.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16





# **SKINDICHT® MR-M**

## Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (14.04.2022)
©2022 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16

# SKINDICHT® MR-M

Thread, male M1  16 x 1.5  20 x 1.5  20 x 1.5  25 x 1.5  25 x 1.5	Thread, female M2  12 x 1.5  12 x 1.5  16 x 1.5  16 x 1.5	100 100 100 50
20 x 1.5 20 x 1.5 25 x 1.5	12 x 1.5 16 x 1.5 16 x 1.5	100
20 x 1.5 20 x 1.5 25 x 1.5	12 x 1.5 16 x 1.5 16 x 1.5	100
20 x 1.5 25 x 1.5	16 x 1.5 16 x 1.5	100
25 x 1.5	16 x 1.5	
		50
25 x 1.5		1
	20 x 1.5	50
32 x 1.5	20 x 1.5	50
32 x 1.5	25 x 1.5	50
40 x 1.5	25 x 1.5	25
40 x 1.5	32 x 1.5	25
50 x 1.5	32 x 1.5	25
50 x 1.5	40 x 1.5	10
63 x 1.5	40 x 1.5	10
63 x 1.5	50 x 1.5	10
72 x 2	63 x 1.5	1
SKINDICHT® MR-M, blank brass		
80 x 2	75 x 1.5	1
16 x 1.5	12 x 1.5	100
20 x 1.5	12 x 1.5	100
20 x 1.5	16 x 1.5	100
	32 x 1.5 40 x 1.5 40 x 1.5 50 x 1.5 50 x 1.5 63 x 1.5 63 x 1.5 72 x 2 80 x 2 16 x 1.5 20 x 1.5	32 x 1.5       25 x 1.5         40 x 1.5       25 x 1.5         40 x 1.5       32 x 1.5         50 x 1.5       32 x 1.5         50 x 1.5       40 x 1.5         63 x 1.5       40 x 1.5         63 x 1.5       50 x 1.5         72 x 2       63 x 1.5         80 x 2       75 x 1.5         16 x 1.5       12 x 1.5         20 x 1.5       12 x 1.5