# D2.5/8.ADO



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products + Low Voltage Products and Systems + Connection Devices + Terminal Blocks + Solution Series

#### **General Information**

Extended Product Type: D2.5/8.ADO

Product ID: 1SNA199089R2500 EAN: 3472591990898

Catalog Description: D2.5/8.ADO IDC Terminal Blocks - Feed-through ADO - ADO - Black

Long Description: - With the ABB ADO System®, experience the fastest and most reliable co

nnection on the market, - Designed for control applications exposed to sev ere constrains (vibrations, shocks, corrosion etc.), - Up to 2 wires per conn

ection.

## Ordering

Color: Black

Minimum Order Quantity: 50 piece

Customs Tariff Number: 85369010

## Popular Downloads

Data Sheet, Technical Information: 1SNC160001C0207-CH-C ADO system

Instructions and Manuals: 1SNC160001C0207-CH-C ADO system

#### **Dimensions**

Product Net Width: 8 mm

Product Net Height: 45 mm

Product Net Depth / Length: 41 mm

Product Net Weight: 9 g

#### **Technical**

Rated Cross-Section: 2.5 mm<sup>2</sup>

Spacing: 8 mm

Connection Type: ADO System

Function: Feed-through

Number of Levels: 1

Rated Current (I<sub>n</sub>): Main Circuit 24 A

Rated Short-time Withstand for 1 s 300 A

Current (I<sub>cw</sub>):

Rated Voltage (U<sub>r</sub>): 1000 V

Rated Impulse Withstand Voltage 8000 V

 $(U_{imp})$ :

Downloaded from Arrow.com.

Dielectric Test Voltage:	3500 V	
Pollution Degree:	3	
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20	
Insulation Material:	Polyamide	
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715	

## Technical UL/CSA

Maximum	Operating	Voltage

Main Circuit 600 V

UL/CSA:

Connecting Capacity UL/CSA: Stranded 14 AWG

Flammability According to UL94: V0

#### Environmental

**RoHS Status:** 

Ambient Air Temperature:	Operation -55 +110 °C	
	Storage -55 +110 °C	

Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Certificates and Declarations (Document Number)

cUL Certificate:	1SND163001A0202
Declaration of Conformity - CE:	1SND225025U1000
EAC Certificate:	1SND162001A1100
Environmental Information:	1SND220024E1003
Instructions and Manuals:	1SNC160001C0207-CH-C ADO system
RMRS Certificate:	1SND163000A1101
RoHS Information:	1SND230472F0201

## Classifications

Object Classification Code:	X
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
ETIM 6:	EC000897 - Feed-through terminal block

## **Container Information**

50 piece
81 mm
220 mm
47 mm
0.45 kg
3472591990898

Package Level 2 Units:	750 piece
Package Level 2 Width:	300 mm
Package Level 2 Depth / Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 2 Gross Weight:	7.1 kg
Package Level 3 Units:	36000 piece
Product Packing Type:	Box

