

Part Number: 2119960100

Product Description: 5.8-8.5 GHz Ultra Wideband (UWB) Flexible Antenna, 7.60mm Width, 16.40mm Length, 100.00mm Cable Length, Compatible with U.FL/I-PEX MHF

Connectors
Status: Active

Series Number : 211996 Product Category : Antennas

#### **Documents & Resources**

#### **Drawings**

Drawing 2119960100\_sd.pdf
Packaging Design Drawing 2119960100-001.pdf

# **3D Models and Design Files**3D Model 2119960100\_stp.zip

#### **Specifications**

Application Specification 2119960100-001.pdf Product Specification 2119960100-000.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

## **Part Details**

#### General

Status	Active
Category	Antennas
Series	211996
Description	5.8-8.5 GHz Ultra Wideband (UWB) Flexible Antenna, 7.60mm Width, 16.40mm Length, 100.00mm Cable Length, Compatible with U.FL/I-PEX MHF Connectors
Component Type	Flexible Antenna with Cable
Function	Signal
Product Family	Ultra-Wideband (UWB) PCB Antenna with Balanced Transmission
Product Name	5.8-8.5GHz UWB Flexible
Protocol	UWB
Туре	Internal, UWB Antenna
UPC	193264067824

## **Electrical**

Band#1 F_End (MHz)	6000
Band#1 F_Start (MHz)	5800
Band#2 F_End (MHz)	8500
Band#2 F_Start (MHz)	6000
Electrical Connectivity	Cable
Peak Gain (dBi)	5.5 @ 5.8-6 GHz, 6.4 @ 6-8.5 GHz
Return Loss - S11 (dB)	< -10, < -5
Total Efficiency	>70% @ 6-8.5 GHz, >75% @ 5.8-6 GHz

# Physical

Cable Length	100.00mm
--------------	----------

Length	16.40mm
Mounting Style	Adhesive
Net Weight	0.555/g
Packaging Type	PET Film
Polarization	Linear
Radiation Pattern	Omnidirectional
Thickness	0.16mm
Width	7.60mm

This document was generated on May 06, 2024