

Glass Passivated Single Phase Bridge Rectifiers

Reverse Voltage 200 to 1000V

Forward Current 8.0 Amp

Features

- Glass passivated die construction
- Ideal for printed circuit boards
- Plastic material used carries UL flammability recognition 94V-0
- High surge current capability
- High temperature soldering guaranteed: 265°C /10 seconds, 0.375" (9.5mm) lead length, 5lbs. (2.3kg) tension

Mechanical Data

Case: Molded plastic case

Terminals: Plated leads solderable per MIL-STD-750, Method 2026

Polarity: Marked on Body

Mounting Position: Any

Module Type

TYPE	V _{RRM}	V _{RSM}
GBU8D	200V	300V
GBU8G	400V	500V
GBU8J	600V	700V
GBU8K	800V	900V
GBU8M	1000V	1100V

Maximum Ratings and Thermal Characteristics (TA = 25°C unless otherwise noted)

Symbol	Conditions	Values	Units
I _{F(AV)}	Maximum average forward output rectified current T _c = 100°C	8.0 ⁽¹⁾	A
I _{FSM}	Peak forward surge current single half sine-wave superimposed on rated load (JEDEC Method)	200	A
i ² t	Rating for fusing (t < 8.3ms)	166	A ² s
Visol	a.c. 50HZ; r.m.s.; 1min	2500	V
R _{θJA} R _{θJC}	Maximum thermal resistance per leg	22 ⁽²⁾ 4.2 ⁽³⁾	°C/W
T _j , T _{STG}	Operating Junction and storage temperature range	-55 to +150	°C
Weight	Approximate Weight	4.0	g

Electrical Characteristics (TA = 25°C unless otherwise noted)

Symbol	Conditions	Values	Units
V _F	Maximum Instantaneous Forward Voltage per leg I _{FM} = 8.0A	1.1	V
I _R	Maximum DC reverse current at rated DC blocking voltage per leg T _A = 25°C T _A = 125°C	5.0 500	μA

Notes: (1) Heat sink, T_c mounting-4x4x0.15cm thick copper plate

(2) Junction to ambient without heatsink

(3) Junction to case with heatsink

(4) Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with M3 screw

Performance Curves




Fig.1 Forward Current Derating Curve




Fig.2 Typical Forward Characteristics, per element




Fig.3 Max Non-Repetitive Forward Surge Current




Fig.4 Typical Junction Capacitance per element





Fig.5 Typical Reverse Characteristics

Package Outline Information

CASE: GBU



Dimensions in inches (mm)