

DELPHI Connection Systems

Catalog

Customer Service

Comparison List (0)

Samples Request

Find by Feature

Browse by Category

Browse by Application

Share

12015880

Search

Enter part number or keyword

Search Results (1)

Search

Options

1 Result(s): [All] - 12015880


☐ Compare

12015880 - Series 56 Female Unsealed
☐ Tin Plating Tang Terminal, Cable Range
3.00 - 3.00 mm2

☐ Compare

Series 56 Female Unsealed Tin Plating Tang Terminal, Cable
Range 3.00 - 3.00 mm2

Part # 12015880



Question about this product?

Attributes		Documents (2)	
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	 12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Part # :	12015880		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	 Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2		

Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Series 56 Female Unsealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	✔ Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Status :	Active
Status :	Active
Status :	Active
Status :	✔ Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	✔ 56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0
Terminal Family :	56.0

Terminal Family :	56.0
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	✓ SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Series :	SERIES
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	✓ Female
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	Female
Gender :	Female
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	✓ Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	✓ 2

Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Weight [g] :	2
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	✔ Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	✔ 3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	✔ 3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65

Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	 3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	 3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00

Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.



[Suppliers](#) | [Terms of Use](#) | [Privacy](#) | [Mexico Privacy Statement](#) | [Cookie Policy](#) | [Sitemap](#) | [European Safe Harbor](#) | [California Supply Chains Act](#)

© Delphi Automotive LLP. All rights reserved.