**Part Number :** 350230013
**Product Description :** 2.00mm Pitch, Board-In Crimp Housing, Right-Angle and Vertical, 13 Circuits, Natural
**Series Number :** 35023
**Status :** Active
**Product Category :** Connector Housings



## Documents & Resources

### Drawings

350230013_sd.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

### Specifications

PK-35023-001-001.pdf

PS-35023-001-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC

Downloaded from Arrow.com.

- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Connector Housings |
| Series | 35023 |
| Description | 2.00mm Pitch, Board-In Crimp Housing, Right-Angle and Vertical, 13 Circuits, Natural |
| Application | Signal, Wire-to-Board |
| Product Name | Board-in |
| UPC | 800753340480 |

### Agency

| | |
|---|---|
| CSA | LR19980 |
| UL | E29179 |

### Physical

| | |
|---|---|
| Circuits (maximum) | 13 |
| Color - Resin | Natural |
| Flammability | 94V-0 |
| Gender | N/A |
| Glow-Wire Capable | No |
| Material - Resin | Nylon |
| Net Weight | 0.260/g |

Downloaded from Arrow.com.

| | |
|---|---|
| Number of Rows | 1 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 2.00mm |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |

### Solder Process Data

| | |
|---|---|
| Lead-Free Process Capability | N/A |

## Mates With / Use With

### Use with Part(s)

| Description | Part Number |
|---|---|
| 2.00/2.50mm Board-in Terminal, Pre-Tin Plating, Wire Insulation Diameter 1.50mm max. | 350449102 |
| 2.00mm Pitch, Board-in Male Crimp Terminal, Right-Angle, Brass Tin (Sn) Plating, 30-24 AWG, Reel | 350211201 |
| 2.00mm Pitch, Board-in Male Crimp Terminal, Right-Angle, Pre-Plated, 30-24 AWG, Reel | 350211301 |
| 2.00mm Pitch, Board-in Male Crimp Terminal, Right-Angle, Post-Tin Plated, 30-24 AWG, Reel | 350211360 |



Downloaded from Arrow.com.