

COAXIAL CONNECTOR, MMBX, 50 Ohm, Straight PCB plug (male)
81_MMBX-S50-0-1/111_N

Properties

- Smallest board-to-board distance
- Very high frequencies
- Excellent return loss values
- Blind mateable
- Reliable and secure connection



Product configuration		
Interface type	Gender	Standard
MMBX	plug	HUBER+SUHNER-MMBX

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO Plating
Outer conductor	Bronze / Brass	SUCOPRO Plating
Body	Bronze / Brass	SUCOPRO Plating
Insulator	PFA / LCP	

Electrical data	
Impedance	50 Ω
Interface frequency	12.4 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 2 GHz	30 dB	1.07
2 GHz ... 6 GHz	23 dB	1.15

Mechanical data	
Weight	0.0005 kg
Mating cycles	100
Board mounting type	surface mount
Number of printlegs	4
Height above PCB HA	5.75 mm
Height of stand off HS	0.6 mm

COAXIAL CONNECTOR, MMBX, 50 Ohm, Straight PCB plug (male)

81_MMBX-S50-0-1/111_N

Engagement / Disengagement force			
	Engagement		Disengagement
Interface force max	15 N		15 N
Environmental data			
Operation temperature		-55 °C ... 155 °C	
Material compliance			
Item number	Directive / Regulation	Rating	Exemptions / Details
23001782	RoHS 2011/65/EU and (EU) 2015/863	Compliant with exemption	6c
	REACH 1907/2006 Article 33 SVHC	Contains one or more SVHC >0,1%	CAS: 7439-92-1 Lead
23001781	RoHS 2011/65/EU and (EU) 2015/863	Compliant with exemption	6c
	REACH 1907/2006 Article 33 SVHC	Contains one or more SVHC >0,1%	CAS: 7439-92-1 Lead
23001780	RoHS 2011/65/EU and (EU) 2015/863	Compliant with exemption	6c
	REACH 1907/2006 Article 33 SVHC	Contains one or more SVHC >0,1%	CAS: 7439-92-1 Lead
Ordering Information Table			
Item number	Item description		Packaging type
23001782	81_MMBX-S50-0-1/111_NE		Single
23001781	81_MMBX-S50-0-1/111_NH		Bulk 100 pcs
23001780	81_MMBX-S50-0-1/111_NM		Tape and Reel
Additional Information			
Remarks		PCB connector with stand-offs	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1367 / Date of publication: 12.07.2025 / uncontrolled copy