

# SACC-CIP-M8FS-3P SMD SH R32 - Contact carrier



1412257

<https://www.phoenixcontact.com/us/products/1412257>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact carrier, 3-position, Socket, straight, M8, A-coding, SMD reflow, this item is expected to be lead-free from Q1 2027 in accordance with RoHS II without exception 6c (Pb < 0.1%), a lead-free alternative is possible on request in advance

## Your advantages

- Reduced mounting costs thanks to two-piece device connector
- Packaging available for automated pick and place assembly
- All common pin assignments and codings available
- Easy device integration thanks to mechanical port screw connections with threaded attachment, press-in contour or direct integration in the front plate
- Optional shield connection and seal for the device when not plugged in

## Commercial data

Item number	1412257
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	AB22
Product key	ABQHCH
GTIN	4046356988995
Weight per piece (including packing)	4.91 g
Weight per piece (excluding packing)	2.061 g
Customs tariff number	85366990
Country of origin	DE

# SACC-CIP-M8FS-3P SMD SH R32 - Contact carrier



1412257

<https://www.phoenixcontact.com/us/products/1412257>

## Technical data

### Product properties

Product type	Contact insert
Application	Signal
Number of positions	3
Seal present	yes
Shielded	yes
Coding	A
Thread type	M8

### Insulation characteristics

Overvoltage category	III
----------------------	-----

### Electrical properties

Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage $U_N$	48 V AC
	60 V DC
Nominal current $I_N$	4 A

### Connection data

Connection method	SMD reflow
-------------------	------------

### Signaling

Status display	no
Status display present	no

### Material specifications

Material Insulating body	PA
Material Contact	CuZn
Material Contact surface	Au
Material Seal	FKM
Flammability rating according to UL 94	V0

### Connector

#### Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M8
Coding	A

### Mechanical properties

# SACC-CIP-M8FS-3P SMD SH R32 - Contact carrier



1412257

<https://www.phoenixcontact.com/us/products/1412257>

## Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection	IP67 (correctly plugged in and locked)
Ambient temperature (operation) (male connector/female connector)	-25 °C ... 105 °C (Plug / socket)
	-40 °C ... 105 °C (without mechanical actuation)

## Standards and regulations

Standard designation	M8 circular connector
Standards/specifications	according to IEC 61076-2-104

## Packaging specifications

Type of packaging	Belt
-------------------	------

# SACC-CIP-M8FS-3P SMD SH R32 - Contact carrier




1412257

<https://www.phoenixcontact.com/us/products/1412257>

## Drawings

Schematic diagram



Pin assignment M8 socket, 3-pos., view female side

# SACC-CIP-M8FS-3P SMD SH R32 - Contact carrier




1412257

<https://www.phoenixcontact.com/us/products/1412257>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1412257>

<div> <b>cULus Recognized</b> Approval ID: E221474-20160506</div>				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine				
	60 V	4 A	-	-

# SACC-CIP-M8FS-3P SMD SH R32 - Contact carrier



1412257

<https://www.phoenixcontact.com/us/products/1412257>

## Classifications

### ECLASS

ECLASS-13.0	27440223
ECLASS-15.0	27440223

### ETIM

ETIM 9.0	EC003568
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

## Environmental product compliance

## EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

## China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

## EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	a83930d2-5823-4b05-a366-db3927eac09b