Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

APC IT Power Distribution Module 3 Pole 5 Wire 30A L21-30 560cm



PDM3530L2130-560

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phases	
Main Output Voltage	120 V	
Provided equipment	Installation guide	

Physical

Colour	Black
Height	12.7 cm
Width	44.5 cm
Depth	40.6 cm
net weight	4.82 kg

Input

Network frequency	60 Hz	
Permissible voltage	200240 V	
Max line current	30 A	

Output

Max current draw	30 A
Number of power socket outlets	1 NEMA L21-30

Conformance

Product certifications UL listed

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.7 cm
Package 1 Width	40.6 cm

Jul 1, 2024

Package 1 Length	44.5 cm
Package 1 Weight	5.36 kg

Contractual warranty

Warranty 1 year repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Take-back Transparency

Resource performance



Take-Back Program Available

Well-being performance



Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information