



**Part Number :** [459841422](#)

**Product Description :** EXTreme LPHPower  
Receptacle Header, Right-Angle, 10 Power Contacts, 16  
Signal Contacts, Select Gold (Au) Plating, for 2.36mm  
Thick PC Board, with Guide Posts and Press-fit Plastic  
Pegs

**Series Number :** 45984

**Status :** Active

**Product Category :** Board-to-Board Connectors



## Documents & Resources

### Drawings

[459841422 sd.pdf](#)

### 3D Models and Design Files

[STEP AP242](#)

[SOLIDWORKS](#)

[Creo](#)

[Symbol and Footprint \(Multi-Format\)](#)

[SYM-45984-1421-001.zip](#)

### Specifications

[PS-45984-001-001.pdf](#)

## Product Environment Compliance

### Compliance

|                    |  |
|--------------------|--|
| GADSL/IMDS         | Not Relevant                                       |
| China RoHS         | per SJ/T 11365-2006                                |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                     |
| REACH SVHC         | Not Contained per D(2025)4165-DC<br>(25 June 2025) |
| EU RoHS            | Compliant per EU 2015/863                          |

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

### Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### Substances of Interest

- PFAS

### EU RoHS Certificate of Compliance

### Additional Product Compliance Information

---

## Part Details

### General

|                |  |
|----------------|--|
| Status         | Active   |
| Category       | Board-to-Board Connectors  |
| Series         | 45984  |
| Description    | EXTreme LPHPower Receptacle Header, Right-Angle, 10 Power Contacts, 16 Signal Contacts, Select Gold (Au) Plating, for 2.36mm Thick PC Board, with Guide Posts and Press-fit Plastic Pegs |
| Application    | Board-to-Board, Power, Signal  |
| Component Type | PCB Receptacle   |
| Product Name   | EXTreme LPHPower   |
| UPC            | 822350773065   |

### Agency

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

### Electrical

|                               |       |
|-------------------------------|-------|
| Current - Maximum per Contact | 20.0A |
| Grounding to PCB              | No    |

|                   |   |
|-------------------|---|
| Voltage - Maximum | 250V AC (RMS)/DC (Power), 30V DC (Signal) |
|-------------------|---|

## Physical

|                                |                                |
|--------------------------------|--------------------------------|
| Circuits (Loaded)              | 26                             |
| Circuits (maximum)             | 26                             |
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 250                            |
| Flammability                   | 94V-0                          |
| Glow-Wire Capable              | No                             |
| Guide to Mating Part           | Yes                            |
| Keying to Mating Part          | None                           |
| Lock to Mating Part            | None                           |
| Material - Metal               | High Performance Alloy (HPA)   |
| Material - Plating Mating      | Gold                           |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 14.100/g                       |
| Number of Rows                 | 2                              |
| Orientation                    | Right Angle                    |
| Packaging Type                 | Tray                           |
| PCB Locator                    | Yes                            |
| PCB Retention                  | Yes                            |
| PCB Thickness - Recommended    | 2.36mm                         |
| PC Tail Length                 | 3.60mm                         |
| Pitch - Mating Interface       | 12.00mm, 1.27mm                |
| Pitch - Termination Interface  | 2.00mm, 2.50mm, 1.27mm         |
| Plating min - Mating           | 0.762µm                        |
| Plating min - Termination      | 3.810µm                        |
| Polarized to Mating Part       | Yes                            |
| Polarized to PCB               | Yes                            |
| (p)ower-(s)ignal Configuration | 10p - 16s                      |
| Stackable                      | No                             |
| Temperature Range - Operating  | -40° to +105°C                 |
| Termination Interface Style    | Through Hole                   |

**Solder Process Data**

|                              |      |
|------------------------------|------|
| Max-Duration                 | 20   |
| Lead-Free Process Capability | WAVE |
| Max-Cycle                    | 3    |
| Max-Temp                     | 260  |

---

**Mates With / Use With**

**Mates with Part(s)**

|                                    |                  |
|------------------------------------|------------------|
| Description                        | Part Number      |
| EXTreme LPHPower Right-Angle Plugs | <u>45985</u>     |
| Mates With                         | 1.57mm Card Edge |

---

This document was generated on Sep 25, 2025