IXYS

Depletion Mode MOSFET

IXTA6N50D2
IXTP6N50D2
IXTH6N50D2

V_{DSX} = 500V
$I_{D(on)}$ ≥ 6A
$R_{DS(on)}$ ≤ 550mΩ

N-Channel



TO-263 AA (IXTA)



TO-220AB (IXTP)



TO-247 (IXTH)



G = Gate D = Drain
S = Source Tab = Drain

Symbol	Test Conditions	Maximum Ratings	
V_{DSX}	T_J = 25°C to 150°C	500	V
V_{GSX}	Continuous	±20	V
V_{GSM}	Transient	±30	V
P_D	T_C = 25°C	300	W
T_J		- 55 ... +150	°C
T_{JM}		150	°C
T_{stg}		- 55 ... +150	°C
T_L	1.6mm (0.062 in.) from Case for 10s	300	°C
T_{SOLD}	Plastic Body for 10s	260	°C
M_d	Mounting Torque (TO-220 & TO-247)	1.13 / 10	Nm/lb.in.
Weight	TO-263	2.5	g
	TO-220	3.0	g
	TO-247	6.0	g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{DSX}	V_{GS} = - 5V, I_D = 250μA	500			V
$V_{GS(off)}$	V_{DS} = 25V, I_D = 250μA	- 2.5		- 4.5	V
I_{GSX}	V_{GS} = ±20V, V_{DS} = 0V			±100	nA
$I_{DSX(off)}$	V_{DS} = V_{DSX}, V_{GS} = - 5V			5	μA
	T_J = 125°C			50	μA
$R_{DS(on)}$	V_{GS} = 0V, I_D = 3A, Note 1			550	mΩ
$I_{D(on)}$	V_{GS} = 0V, V_{DS} = 25V, Note 1	6			A

Features

- Normally ON Mode
- International Standard Packages
- Molding Epoxies Meet UL 94 V-0 Flammability Classification

Advantages

- Easy to Mount
- Space Savings
- High Power Density

Applications

- Audio Amplifiers
- Start-up Circuits
- Protection Circuits
- Ramp Generators
- Current Regulators
- Active Loads

© 2017 IXYS CORPORATION, All Rights Reserved

Downloaded from Arrow.com.

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	V_{DS} = 30V, I_D = 3A, Note 1	2.8	4.5		S
C_{iss}	V_{GS} = -10V, V_{DS} = 25V, f = 1MHz		2800		pF
C_{oss}			255		pF
C_{rss}			64		pF
$t_{d(on)}$	**Resistive Switching Times** V_{GS} = ±5V, V_{DS} = 250V, I_D = 3A R_G = 2.4Ω (External)		28		ns
t_r			72		ns
$t_{d(off)}$			82		ns
t_f			43		ns
$Q_{g(on)}$	V_{GS} = ±5V, V_{DS} = 250V, I_D = 3A		96		nC
Q_{gs}			11		nC
Q_{gd}			48		nC
R_{thJC}				0.41	°C/W
R_{thCS}	TO-220		0.50		°C/W
	TO-247		0.21		°C/W

Safe-Operating-Area Specification

Symbol	Test Conditions	Characteristic Values Min.	Typ.	Max.	
SOA	V_{DS} = 400V, I_D = 0.45A, T_C = 75°C, Tp = 5s	180			W

Source-Drain Diode

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
V_{SD}	I_F = 6A, V_{GS} = -10V, Note 1		0.8	1.3	V
t_{rr}	I_F = 3A, -di/dt = 100A/µs V_R = 100V, V_{GS} = -10V		350		ns
I_{RM}			16		A
Q_{RM}			2.8		µC

Note 1. Pulse test, t ≤ 300µs, duty cycle, d ≤ 2%.

TO-220 Outline



Pins: 1 - Gate 2 - Drain
3 - Source

SYM	INCHES MIN	MAX	MILLIMETERS MIN	MAX
A	.170	.190	4.32	4.83
b	.025	.040	0.64	1.02
b1	.045	.065	1.15	1.65
c	.014	.022	0.35	0.56
D	.580	.630	14.73	16.00
E	.390	.420	9.91	10.66
e	.100 BSC		2.54 BSC	
F	.045	.055	1.14	1.40
H1	.230	.270	5.85	6.85
J1	.090	.110	2.29	2.79
k	0	.015	0	0.38
L	.500	.550	12.70	13.97
L1	.110	.230	2.79	5.84
ØP	.139	.161	3.53	4.08
Q	.100	.125	2.54	3.18

TO-247 Outline



1 = Gate
2 = Drain
3 = Source

SYM	INCHES MIN	MAX	MILLIMETERS MIN	MAX
A	.185	.209	4.7	5.3
A_1	.087	.102	2.2	2.54
A_2	.059	.098	2.2	2.6
b	.040	.055	1.0	1.4
b_1	.065	.084	1.65	2.13
b_2	.113	.123	2.87	3.12
C	.016	.031	.4	.8
D	.819	.845	20.80	21.46
E	.610	.640	15.75	16.26
e	.215 BSC		5.45 BSC	
L	.780	.800	19.81	20.32
L1		.177		4.50
ØP	.140	.144	3.55	3.65
Q	.212	.244	5.4	6.2
R	.170	.216	4.32	5.49
S	.242 BSC		6.15 BSC	

TO-263 Outline



1. Gate
2. Drain
3. Source
4. Drain

Dim.	Millimeter Min.	Max.	Inches Min.	Max.
A	4.06	4.83	.160	.190
b	0.51	0.99	.020	.039
b2	1.14	1.40	.045	.055
c	0.40	0.74	.016	.029
c2	1.14	1.40	.045	.055
D	8.64	9.65	.340	.380
D1	8.00	8.89	.280	.320
E	9.65	10.41	.380	.405
E1	6.22	8.13	.270	.320
e	2.54	BSC	.100	BSC
L	14.61	15.88	.575	.625
L1	2.29	2.79	.090	.110
L2	1.02	1.40	.040	.055
L3	1.27	1.78	.050	.070

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,850,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

Downloaded from Arrow.com.

Fig. 1. Output Characteristics @ T_J = 25°C



Fig. 2. Extended Output Characteristics @ T_J = 25°C



Fig. 3. Output Characteristics @ T_J = 125°C



Fig. 4. Drain Current @ T_J = 25°C



Fig. 5. Drain Current @ T_J = 100°C



Fig. 6. Dynamic Output Resistance vs. Gate Voltage



© 2017 IXYS CORPORATION, All Rights Reserved

Downloaded from Arrow.com.

Fig. 7. Normalized $R_{DS(on)}$ vs. Junction Temperature



Fig. 8. $R_{DS(on)}$ Normalized to I_D = 3A Value vs. Drain Current



Fig. 9. Input Admittance



Fig. 10. Transconductance



Fig. 11. Breakdown and Threshold Voltages vs. Junction Temperature



Fig. 12. Forward Voltage Drop of Intrinsic Diode



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Downloaded from Arrow.com.

Fig. 13. Capacitance



Fig. 14. Gate Charge



Fig. 15. Forward-Bias Safe Operating Area @ T_C = 25°C



Fig. 16. Forward-Bias Safe Operating Area @ T_C = 75°C



Fig. 17. Maximum Transient Thermal Impedance



© 2017 IXYS CORPORATION, All Rights Reserved

Downloaded from Arrow.com.

IXYS
A Littelfuse Technology

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

Downloaded from Arrow.com.