LCA110

350V, 120 mA 1-Form-A SSR

Key Attributes

Characteristic	Rating	Unit
Blocking Voltage	350	V_P
Load Current	120	mA_{RMS}/mA_{DC}
On-resistance (max.)	35	Ω
LED Current to Operate	2	mA



Pin Configuration



Switching Characteristics of Normally Open Device



Description

The LCA110 is a normally open (1-Form-A) Solid State Relay which uses optically coupled MOSFET technology to provide 3750V_{RMS} of input to output isolation.

Its optically coupled outputs, which use OptoMOS architecture, are controlled by a highly efficient infrared LED.

The LCA110 can be used to replace mechanical relays, and offers the superior reliability associated with semiconductor devices.

Features

- 3750V_{RMS} Input/Output Isolation
- Small 6-Pin Package
- Low Drive Power Requirements
- High Reliability
- No EMI/RFI Generation
- Immune to Radiated EM Fields

Applications

- Instrumentation
- Multiplexers
- Data Acquisition
- Electronic Switching
- I/O Subsystems
- Meters (Watt-Hour, Water, Gas)
- Medical Equipment—Patient/Equipment Isolation
- Security
- Industrial Controls

Approvals

- UL 1577 Recognized Component: File E76270
- CSA Certified Component: Certificate # 1175739
- TUV EN 62368-1: Certificate # B 082667 0008

Ordering Information

Part Number	Description
LCA110	6-PIN DIP (50/Tube)
LCA110S	6-Pin Surface Mount (50/Tube)
LCA110STR	6-Pin Surface Mount (1,000/Reel)

©Littelfuse, Inc.
Specifications are subject to change without notice
SC 11/18/2025
LCA110_R15

Downloaded from Arrow.com.

Specifications

Absolute Maximum Ratings

Parameter	Ratings	Units
Blocking Voltage	350	V_P
Reverse Input Voltage	5	V
Input Control Current	50	mA
Peak (10 ms)	1	A
Input Power Dissipation [1]	150	mW
Total Power Dissipation [2]	800	
Isolation Voltage, Input to Output	3750	V_{RMS}
Operational Temperature, Ambient	–40 to +85	°C
Storage Temperature	–40 to +125	

[1] *Derate linearly 1.33 mW/°C*
[2] *Derate output power linearly 6.67 mW/°C*

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.

Typical values are characteristic of the device at +25 °C, and are the result of engineering evaluations. They are provided for information purposes only, and are not part of the manufacturing testing requirements.

Electrical Characteristics @ 25 °C

Parameter	Conditions	Symbol	Value			Units
			Minimum	Typical	Maximum	
Output Characteristics						
Blocking voltage	$I_L = 1\,\mu A$	V_{DRM}	350	—	—	V_P
Load current:						
Continuous, AC/DC Configuration	—	I_L	—	—	120	mA_{RMS}/mA_{DC}
Continuous, DC Configuration	—	I_L	—	—	200	mA_{DC}
Peak	t = 10 ms	I_{LPK}	—	—	±350	mA_P
On-resistance [1]						
AC/DC Configuration	$I_L = 120\,mA$	R_{ON}	—	23	35	Ω
DC Configuration	$I_L = 200\,mA$	R_{ON}	—	7	10	Ω
Off-state leakage current	$V_L = 350\,V_P$	I_{LEAK}	—	—	1	µA
Switching speeds:						
Turn-on	$I_F = 5\,mA$, $V_L = 10\,V$	t_{on}	—	—	3	ms
Turn-off	$I_F = 5\,mA$, $V_L = 10\,V$	t_{off}	—	—	3	ms
Output capacitance	$I_F = 0\,mA$, $V_L = 50\,V$, f = 1 MHz	C_{OUT}	—	25	—	pF
Input Characteristics						
Input control current to activate	$I_L = 120\,mA$	I_F	—	—	2	mA
Input control current to deactivate	—	I_F	0.1	—	—	mA
Input voltage drop to deactivate	—	V_F	0.8	—	—	V
Input voltage drop	$I_F = 5\,mA$	V_F	0.9	1.36	1.5	V
Reverse input current	$V_R = 5\,V$	I_R	—	—	10	µA
Common Characteristics						
Capacitance, input to output	$V_{IO} = 0\,V$, f = 1 MHz	C_{IO}	—	3	—	pF

[1] *Measurement taken within 1 second of on-time.*

©Littelfuse, Inc.
Specifications are subject to change without notice
SC 11/18/2025
LCA110_R15

Downloaded from Arrow.com.

Load Configuration Methods

The diagrams below show load connection methods based on selected application circuit option.



Figure 1. AC/DC, Bidirectional Load Configuration



Figure 2. DC, Unidirectional Load Configuration

©Littelfuse, Inc.
Specifications are subject to change without notice
SC 11/18/2025
LCA110_R15

Downloaded from Arrow.com.

Characteristic Curves

Typical LED Forward Voltage Drop ($N = 50$, $I_F = 5$ mA)



Typical Turn-On Time ($N = 50$, $I_F = 2$ mA, $I_L = 120$ mA_{DC})



Typical Turn-Off Time ($N = 50$, $I_F = 2$ mA, $I_L = 120$ mA_{DC})



Typical I_F for Switch Operation ($N = 50$, $I_L = 120$ mA_{DC})



Typical I_F for Switch Dropout ($N = 50$, $I_L = 120$ mA_{DC})



Typical On-Resistance Distribution ($N = 50$, $I_L = 120$ mA_{DC})



Typical Blocking Voltage Distribution ($N = 50$)



Typical LED Forward Voltage Drop vs. Temperature



Typical Turn-On Time vs. LED Forward Current ($I_L = 120$ mA_{DC})



Typical Turn-Off Time vs. LED Forward Current ($I_L = 120$ mA_{DC})



*Unless otherwise noted, data presented in these graphs is typical of device operation at T_A = 25°C.

©Littelfuse, Inc.
Specifications are subject to change without notice
SC 11/18/2025
LCA110_R15

Downloaded from Arrow.com.

Characteristic Curves

Typical Turn-On Time vs. Temperature (I_L = 70 mA_{DC})



Typical Turn-Off Time vs. Temperature (I_F = 5 mA, I_L = 70 mA_{DC})



Typical Steady State On-Resistance vs. Temperature (I_L = 120 mA_{DC})



Typical I_F for Switch Operation vs. Temperature (I_L = 70 mA_{DC})



Typical I_F for Switch Dropout vs. Temperature (I_L = 70 mA_{DC})



Typical Load Current vs. Load Voltage (N = 50, I_F = 2 mA)



Maximum Load Current vs. Temperature



Typical Blocking Voltage vs. Temperature



Typical Leakage vs. Temperature Measured Across Pins 4 & 6



Energy Rating Curve



*Unless otherwise noted, data presented in these graphs is typical of device operation at T_A = 25°C.

©Littelfuse, Inc.
Specifications are subject to change without notice

Downloaded from Arrow.com.

Manufacturing Information

Moisture Sensitivity

All plastic encapsulated semiconductor packages are susceptible to moisture ingression. Littelfuse classifies its plastic encapsulated devices for moisture sensitivity according to the latest version of the joint industry standard, **IPC/JEDEC J-STD-020**, in force at the time of product evaluation. We test all of our products to the maximum conditions set forth in the standard, and guarantee proper operation of our devices when handled according to the limitations and information in that standard as well as to any limitations set forth in the information or standards referenced below.

Failure to adhere to the warnings or limitations as established by the listed specifications could result in reduced product performance, reduction of operable life, and/or reduction of overall reliability.

This product carries a **Moisture Sensitivity Level (MSL)** classification as shown below, and should be handled according to the requirements of the latest version of the joint industry standard **IPC/JEDEC J-STD-033**.

Device	Moisture Sensitivity Level (MSL) Classification
LCA110S	MSL 1

ESD Sensitivity

This product is ESD Sensitive, and should be handled according to the industry standard **JESD-625**.

Soldering Profile

Provided in the table below is the **IPC/JEDEC J-STD-020** Classification Temperature (T_C) and the maximum dwell time (T_C – 5 °C). The Classification Temperature sets the Maximum Body Temperature allowed for these devices during reflow soldering processes.

Device	Classification Temperature (T_C)	Dwell Time (T_P)	Max Reflow Cycles
LCA110S	250 °C	30 seconds	3

For through-hole devices, the maximum pin temperature and maximum dwell time through all solder waves is provided in the table below. Dwell time is the interval beginning when the pins are initially immersed into the solder wave until they exit the solder wave. For multiple waves, the dwell time is from entering the first wave until exiting the last wave. During this time, pin temperatures must not exceed the maximum temperature given in the table below. Body temperature of the device must not exceed the limit shown in the table below at any time during the soldering process.

Device	Maximum Pin Temperature	Maximum Body Temperature	Maximum Dwell Time	Wave Cycles
LCA110S	260 °C	250 °C	10 seconds*	1

**Total cumulative duration of all waves.*

Board Wash

Littelfuse recommends the use of no-clean flux formulations. Board washing to reduce, or remove flux residue following the solder reflow process is acceptable, provided proper precautions are taken to prevent damage to the device. These precautions include, but are not limited to: Using a low pressure wash and providing a follow-up bake cycle sufficient to remove any moisture trapped within the device, due to the washing process. Due to the variability of the wash parameters used to clean the board, determination of the bake temperature and duration necessary to remove the moisture trapped within the package is the responsibility of the user (assembler). Cleaning, or drying methods that employ ultrasonic energy may damage the device and should not be used. Additionally, the device must not be exposed to halide flux or solvents.

©Littelfuse, Inc.
Specifications are subject to change without notice
SC 11/18/2025
LCA110_R15

Downloaded from Arrow.com.

Mechanical Dimensions

LCA110





PCB Hole Pattern



Controlling dimension: inches

Dimensions
mm
(inches)

LCA110S





PCB Land Pattern



Controlling dimension: inches

Dimensions
mm
(inches)

©Littelfuse, Inc.
Specifications are subject to change without notice
SC 11/18/2025
LCA110_R15

Downloaded from Arrow.com.

LCA110STR Tape and Reel Packaging



NOTES:
1. All dimensions carry tolerances of EIA Standard 481-2
2. The tape complies with all “Notes” for constant dimensions listed on page 5 of EIA-481-2

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at **https://www.littelfuse.com/disclaimer-electronics**

©Littelfuse, Inc.
Specifications are subject to change without notice
SC 11/18/2025
LCA110_R15

Downloaded from Arrow.com.