

https://www.phoenixcontact.com/us/products/0201663



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insulating sleeve, color: white



Your advantages

- Two-piece test plug for individual plug color combinations
- The test plugs are inserted in the function shaft of the terminal blocks from the CLIPLINE complete system or in the test pick-offs provided

Commercial data

Item number	0201663
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE19
Product key	BE1Z3X
GTIN	4017918098773
Weight per piece (including packing)	0.494 g
Weight per piece (excluding packing)	0.276 g
Customs tariff number	85472000
Country of origin	PL



https://www.phoenixcontact.com/us/products/0201663



Technical data

Product properties

Product type	Insulating sleeve			
Connection data				
Connection method	Spring-cage connection			
Dimensions				
Width	4.6 mm			
11-2-16				
Height	27.5 mm			

Material specifications

Color	white (RAL 9010)
Material	PA
Flammability rating according to UL 94	V2
Insulating material	PA
Static insulating material application in cold	-40 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (operation)	20 % 90 %
Permissible humidity (storage/transport)	30 % 70 %



0201663

https://www.phoenixcontact.com/us/products/0201663

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-13.0	27141192			
	ECLASS-15.0	27141192			
ETIM					
	ETIM 9.0	EC004592			
UNSPSC					

39121400



https://www.phoenixcontact.com/us/products/0201663



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com