

https://www.phoenixcontact.com/us/products/2901642



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Patch panel, one RJ45 jack to 8 spring-force connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers

Product description

Ethernet patch panels enable quick and easy connection between the field cabling and control cabinet cabling. The passive termination panels are a convenient alternative to the on-site assembly of RJ45 connectors.

Your advantages

- · Safe shield connection to ground potential
- · Mounting on a DIN rail
- CAT5e
- 10/100/1000 Mbps
- · Optional shield connection via jumpers
- · Shipbuilding approval in accordance with DNV GL
- PoE-capable in accordance with IEEE 802.3bt, type 4

Commercial data

Item number	2901642
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	DN07
Product key	DNC331
Catalog page	Page 363 (C-6-2019)
GTIN	4046356623384
Weight per piece (including packing)	56.073 g
Weight per piece (excluding packing)	56.073 g
Customs tariff number	85366990
Country of origin	US



https://www.phoenixcontact.com/us/products/2901642



Technical data

Notes

Utilization restriction

CCCex note U	Use in potentially explosive areas is not permitted in China.
--------------	---

Product properties

Product type	Patch panel
MTBF	6702 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))
	2962 Years (Telcordia standard, 40°C temperature, 34.25% operating cycle (5 days a week, 12 hours a day))

Connection data

Connection method	Spring-cage connection

Interfaces

Data: Ethernet interface, 10/100/1000Base-T(X) in accordance with IEEE 802.3

Serial transmission speed	10/100/1000 Mbps
Connection method	Spring-cage connection
No. of channels	1
Pin assignment	1:1
Transmission length	100 m (including patch cables)
Single conductor/terminal point, rigid	0.2 mm² 1.5 mm²
Single-wire/terminal point, flexible	0.2 mm² 1 mm²
Single-wire/terminal point, rigid AWG max.	16
Single-wire/terminal point, rigid AWG min.	24

Data: Ethernet interface, 10/100/1000Base-T(X) in accordance with IEEE 802.3

Connection method	RJ45 CAT5e
No. of channels	1

Dimensions

Dimensional drawing	59,8
Width	29 mm
Height	90 mm
Depth	53 mm



https://www.phoenixcontact.com/us/products/2901642



Material specifications

Color (Housing)	green (RAL 6021)
Material Housing	PVC / PA

Cable/line

External cable diameter ()	6 mm 10 mm
Cable impedance	100 Ω

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≤ 2500		

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C 70 °C
Ambient temperature (storage/transport)	-25 °C 85 °C
Ambient temperature (assembly)	-10 °C 70 °C
Permissible humidity (operation)	25 % 95 % (non-condensing)

Approvals

1	$\overline{}$	Λ	\sim
	ᆮ	н	L

Identification	EAC
ATEX	
Identification	
Certificate	PxCIF14ATEX2901642U
Note	Please follow the special installation instructions in the documentation!
JKEX	
Identification	
Certificate	PxCIMA21UKEX2901642U
Corrosive gas test	
Identification	ISA-S71.04-1985 G3 Harsh Group A
Shipbuilding	
Identification	DNV GL
DNV GL data	
Temperature	В
Humidity	A
Vibration	A
EMC	В



2901642

https://www.phoenixcontact.com/us/products/2901642

	Enclosure	Required protection according to the Rules shall be provided upon installation on board	
Mounting			
	Mounting type	DIN rail mounting	




https://www.phoenixcontact.com/us/products/2901642




Drawings

Circuit diagram



Circuit diagram




2901642


https://www.phoenixcontact.com/us/products/2901642



Circuit diagram



Schematic diagram




Shield connection direct to PE



https://www.phoenixcontact.com/us/products/2901642




Schematic diagram



Shield connection to PE via RC element

Circuit diagram







https://www.phoenixcontact.com/us/products/2901642



Dimensional drawing





Dimensional drawing



2901642

https://www.phoenixcontact.com/us/products/2901642

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2901642



EAC

Approval ID: RU D-DE.GB09.B.00312



DNV GL

Approval ID: TAA00001KR



2901642

https://www.phoenixcontact.com/us/products/2901642

Classifications

ECLASS

	ECLASS-11.0	19170112		
	ECLASS-12.0	19170112		
	ECLASS-13.0	19170112		
ETIM				
	ETIM 9.0	EC002697		

UNSPSC



https://www.phoenixcontact.com/us/products/2901642



Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"



https://www.phoenixcontact.com/us/products/2901642



Accessories

FL CRIMPTOOL - Assembly tool

2744869

https://www.phoenixcontact.com/us/products/2744869

Crimping pliers, for assembling the RJ45 plugs FL PLUG RJ45..., for assembly on site



SZF 0-0,4X2,5 - Screwdriver

1204504

https://www.phoenixcontact.com/us/products/1204504



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: $0.4 \times 2.5 \times 75$ mm, 2-component grip, with non-slip grip



https://www.phoenixcontact.com/us/products/2901642



FL ISOLATOR 100-RJ/RJ - Network isolator

2313931

https://www.phoenixcontact.com/us/products/2313931



Passive network isolator for electrical isolation in Ethernet networks. This protects Ethernet devices from potential differences of up to 4 kV. Can be used for transmission speeds of up to 100 Mbps. Possible to connect two RJ45 plugs.

FL ISOLATOR 1000-RJ/RJ - Network isolator

2313915

https://www.phoenixcontact.com/us/products/2313915



Passive network isolator for electrical isolation in Ethernet networks. This protects Ethernet devices from potential differences of up to 4 kV. Can be used for transmission speeds of up to 1 Gbps. Possible to connect two RJ45 plugs.



https://www.phoenixcontact.com/us/products/2901642



FL ISOLATOR 100-M12 - Network isolator

2902985

https://www.phoenixcontact.com/us/products/2902985



Passive network isolator for electrical isolation in Ethernet networks. For the protection of Ethernet devices against potential differences of up to 4 kV. Can be used for transmission speeds of up to 100 Mbps. Ethernet connection via two M12 sockets (D-coded).

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/us/products/2832250



Patch cable, CAT5, assembled, 0.3 m



https://www.phoenixcontact.com/us/products/2901642



FL CAT5 PATCH 0,5 - Patch cable

2832263

https://www.phoenixcontact.com/us/products/2832263



Patch cable, CAT5, assembled, 0.5 m

FL CAT5 PATCH 1,0 - Patch cable

2832276

https://www.phoenixcontact.com/us/products/2832276



Patch cable, CAT5, assembled, 1 m



https://www.phoenixcontact.com/us/products/2901642



FL CAT5 PATCH 1,5 - Patch cable

2832221

https://www.phoenixcontact.com/us/products/2832221



Patch cable, CAT5, assembled, 1.5 m

FL CAT5 PATCH 2,0 - Patch cable

2832289

https://www.phoenixcontact.com/us/products/2832289



Patch cable, CAT5, assembled, 2 m



https://www.phoenixcontact.com/us/products/2901642



FL CAT5 PATCH 3,0 - Patch cable

2832292

https://www.phoenixcontact.com/us/products/2832292



Patch cable, CAT5, assembled, 3 m

NBC-R4AC-R4AC-IE8A/.../... - Patch cable

1411854

https://www.phoenixcontact.com/us/products/1411854



Patch cable, degree of protection: IP20, number of positions: 8, 10 Gbps, ${\rm CAT6}_{\rm A}$, cable outlet: straight, Ethernet



https://www.phoenixcontact.com/us/products/2901642



NBC-R4AC/10G-R4AC/10G-94F/2,0 - Patch cable

1408360

https://www.phoenixcontact.com/us/products/1408360



Patch cable, CAT6 $_{\rm A}$, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 2.0 $_{\rm m}$

NBC-R4AC/10G-R4AC/10G-94F/3,0 - Patch cable

1408365

https://www.phoenixcontact.com/us/products/1408365



Patch cable, CAT6 $_{\rm A}$, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 3.0 m



https://www.phoenixcontact.com/us/products/2901642



NBC-R4AC/1,0-93B/R4AC - Patch cable

1408968

https://www.phoenixcontact.com/us/products/1408968



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

NBC-R4AC/2,0-93B/R4AC - Patch cable

1408969

https://www.phoenixcontact.com/us/products/1408969



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET



https://www.phoenixcontact.com/us/products/2901642



VS-08-RJ45-10G/Q - RJ45 connector

1419001

https://www.phoenixcontact.com/us/products/1419001



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: black, Ethernet

VS-PN-RJ45-5-Q/IP20 - RJ45 connector

1658435

https://www.phoenixcontact.com/us/products/1658435



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 4, 100 Mbps, CAT5, material: Plastic, connection method: Insulation displacement connection, cable outlet: straight, color: traffic grey A RAL 7042, PROFINET



https://www.phoenixcontact.com/us/products/2901642



VS-CABLE-STRIP-VARIO - Stripping tool

1657407

https://www.phoenixcontact.com/us/products/1657407

Stripping tool, for the multi-level stripping of shielded cables



VS-08-RJ45-5-Q/IP20 - RJ45 connector

1656725

https://www.phoenixcontact.com/us/products/1656725



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: traffic grey A RAL 7042, Ethernet



https://www.phoenixcontact.com/us/products/2901642



VS-08-RJ45-5-Q/IP20 BK - RJ45 connector

1658008

https://www.phoenixcontact.com/us/products/1658008



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: black, Ethernet

FL-PP-RJ45-SC - Patch panel

2901643

https://www.phoenixcontact.com/us/products/2901643



Patch panel, one RJ45 jack to 8 screw connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers



https://www.phoenixcontact.com/us/products/2901642



FL-PP-RJ45-LSA - Patch panel

2901645

https://www.phoenixcontact.com/us/products/2901645



Patch panel, one RJ45 jack to 8 LSA connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via bridges

FL-PP-RJ45/RJ45 - Patch panel

2901646

https://www.phoenixcontact.com/us/products/2901646



Patch panel, two RJ45 jacks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com