

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of NXRT15XV502FA5B050 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXRT15XV502FA5B050

NXRT15XV502FA5B050










Appearance & Shape







Features

- 1. NXR series can accurately detect temperature with NCP15 series on the head of parts.
- 2. The insulation coat with polyulethane on the surface of lead wire : 100VDC.
- 3. You can choose NTC characteristics from NCP15 series.
- 4. The resistance drift is small in the reliability test.
- 5. The production capacity is bigger and NXR is produced in almost all automation line.
- 6. Adopt to Sb regulation
- 7. UL/cULcertified product. (UL1434, File No. E137188)



Applications

Limited Usage	Consumer Grade
---------------	----------------



Packaging Information

F	Packaging		Standard Packing Quantity
E	3	Bulk(Bag)	500

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NXRT15XV502FA5B050 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXRT15XV502FA5B050

NXRT15XV502FA5B050



Specifications

Resistance (25°C)	5kΩ	
, ,	OKZ	
Resistance Value Tolerance	±1%	
(at 25°C)		
B-Constant (25/50°C)	3936K	
B-Constant (25/50°C)	±1%	
Tolerance	170	
B-Constant(25/80°C)	3971K	
(Reference Value)	007 110	
B-Constant(25/85°C)	3977K	
(Reference Value)	007711	
B-Constant(25/100°C)	3989K	
(Reference Value)		
Maximum Operating Current	0.22mA	
(25°C)		
Rated Electric Power (25°C)	13.0mW	
Typical Dissipation Constant	2.6mW/°C	
(25°C)		
Operating Temperature	-40°C to 125°C	
Range	10 € 15 120 €	
Thermal Time Constant	4s	
Lead Shape	Insulation type	
Size Code (in mm)	050 = 50mm	
Size Code (in inch)	050 = 50mm	
Shape	Lead	
Mass	0.149g	
MSL	N	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of NXRT15XV502FA5B050 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NXRT15XV502FA5B050

NXRT15XV502FA5B050



Product Data





Resistance-Temperature Characteristics

Temperature Tolenrance VS. Temp.

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

