MLG0603P2N9CTD25

Product Status	Production		
Applications	Automotive Grade		
Feature	AEC-Q200AEC-Q200 MultilayerMultilayer Non-Mag CoreNon-Magnetic Core (Dielectric Ceramic) High QHigh Q		
Series Type	MLG-P		
Brand	TDK		
Environmental Compliance	ROHS REACH Halogen Free Lead Free		



	Size
Length(L)	0.60mm ±0.03mm
Width(W)	0.30mm ±0.03mm
Thickness Height	0.30mm ±0.03mm
Recommended Land Pattern (A)	0.25mm Nom.
Recommended Land Pattern (B)	0.30mm Nom.
Recommended Land Pattern (C)	0.30mm Nom.

Electrical Characteristics		
Inductance	2.9nH ±0.2nH at 500MHz	
Rated Current	500mA	
DC Resistance [Typ.]	100mΩ	
DC Resistance [Max.]	200mΩ	
Self Resonant Frequency [Min.]	7.5GHz	
Self Resonant Frequency [Typ.]	9.2GHz	
Q [Min.]	14 at 500MHz	
Q [Typ.]	17 at 500MHz	

	Other
Operating Temp. Range	-55 to 125°C
Soldering Method	Reflow
AEC-Q200	YES
Packing	Punched (Paper)Taping [180mm Reel, Tape width 8mm]
Package Quantity	15000pcs
Weight	0.0002g

Downloaded from Arrow.com.




[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.


 $^{! \ \}mbox{All specifications}$ are subject to change without notice.


MLG0603P2N9CTD25

Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)










[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

MLG0603P2N9CTD25

Associated Images





[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{All specifications}$ are subject to change without notice.