

Industries

Solutions

Services

Software

Products

Partners

Support

About Us



-Search-Entire Site

Search Results

Evaluate

- FAQ's

Design a Solution

- Part Drawings
- PDF-Opti-Core 96 ...

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Product On-Line Catalog > Search Results >



Your search criteria matched only one product, shown below

FONRX96Y



- Allows installation using loose tube cable methods within buildings and outdoor environments for transitional aerial and duct applications, and in entrance facilities that require riser (OFNR) or plenum (OFNP) rated cable
- Eliminates the need for building entrance transition point
- All-dielectric cable construction requires no grounding or bonding
- UV resistant cable sheathing meets the light absorption requirement defined by Telcordia GR-20, Issue 2 to withstand harsh outdoor environmental demands
- Dry water-blocking technology allows rapid cable preparation and termination for lower. termination costs and time (no messy gel required)
- Available in 6 and 12-fiber counts in "central loose tube" design, and in 24, 36, 48, 72, 96, and 144-fiber counts in a "stranded loose tube" design
- Multimode (OM4,OM3, OM2, and OM1) and singlemode (OS1/OS2) fiber available
- Sheath markings provide positive identification, quality traceability, and length verification.
- 250µm buffer coating protects fibers during handling and allows for ease of stripping
- Opti-Core® 10Gig™ Fiber Optic Cable is designed to support network transmission speeds up to 10 Gb/s for link lengths up to 300 meters for OM3 and up to 550 meters for OM4 with an 850nm source per IEEE 802.3ae 10 GbE standard; backward compatible for use with all 50/125µm system requirements

These products are available for sale in the Americas regions only. Contact Customer Service for minimum order quantities, availability, and additional product configurations. Options include fiber counts, jacket colors, hybrid constructions (multiple fiber types within a single cable), flame ratings, subunit counts, armoring, premium optical performance grades and ribbonized constructions.

Part Number	FONRX96Y
 RoHS Compliancy Status 	Compliant
Note	FONRX96Y replaces FONRX96
Part Description	96-fiber 10Gig™ 50/125µm (OM3) multimode riser rated indoor/outdoor stranded cable.
Product Type	Indoor/Outdoor All-Dielectric Cable
Color	Black
Fiber Compatibility	10GbE 50/125µm
Fiber Type	Multimode
CE Compliant	No
■ Fiber Count	96
Flammability Rating	Riser (OFCR)
Pricing Description	96-Fiber (OM3) Multimode Cable, Riser Indoor/Outdoor Stranded Cable
Min. Order UOM	FT
Min. Order Qty.	3280
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.