

Surface Mount Fuse, PTC, 1812 footprint, 4.6 x 3.2 mm, 60 VDC



6.0 - 60.0VDC · 0.1 - 2.6A

See below:

[Approvals and Compliances](#)

Description

- 100% compatible with the PFMD type
Directly solderable on printed circuit boards

Applications

- Hard disk drives
- PC motherboards
- PC peripherals
- PCMCIA cards
- USB port protection

Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data

V max	6.0 - 60.0VDC
I max	10 - 100A
I hold	0.1 - 2.6A
Attachment	PCB,SMT
Allowable Operation Temperature	-40 °C to 85 °C
Material: Terminals	Electroless Nickel under Immersion Gold
Weight	0.025 g
Storage Conditions	0 °C to 40 °C, max. 70% r.h.
Product Marking	I hold, Data Code

Soldering Methods	Reflow Soldering Profile
Solderability	245 °C / 3 sec
Resistance to Soldering Heat	260 °C / 10 sec
Moisture Sensitivity Level	MSL 1, J-STD-020
Passing Aging	+85 °C, 1000 Hours -> +/- 5% Typical Resistance Change
Humidity Aging	+85 °C, 85% r.h., 1000 Hours -> +/- 5% Typical Resistance Change
Thermal Shock	+85 °C to -40 °C, 20 Times -> +/- 10% Typical Resistance Change
Vibration	MIL-STD-883C, Method 2007.1, Test Condition A
Resistance to Solvents	MIL-STD-202, Method 215

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: PFMF

Approval Logo	Certificates	Certification Body	Description
	TUEV Approvals	TUEV	Technischer Überwachungsverein
	UL Approvals	UL	UL File Number: E172175

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	62319-1-1	Polymeric thermistors. Part 1-1: Current limiting application
	Designed according to	UL 1434	Thermistor-type devices
	Designed according to	CSA 22.2 No. 0 TIL No. CA-3A	General requirements - Canadian electrical code, part II

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements



Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimension [mm]

4.6 mm



Soldering pads

Part marking



Part Identification Examples:

PFMF.020 = 02
PFMF.075 = 75
PFMF.150 = 15
PFMF.200 = 20


Biweekly Date Code:

Week 1 and 2 = A
Week 51 and 52 = Z

Year Code:

6 = 2016

Time-Current-Curves



Dimensions

A min [mm]	A max [mm]	B min [mm]	B max [mm]	C min [mm]	C max [mm]	D min [mm]	Order Number	
4.37	4.73	3.07	3.41	0.7	1.1	0.3	PFMF.010.2	■
4.37	4.73	3.07	3.41	0.7	1.1	0.3	PFMF.014.2	■
4.37	4.73	3.07	3.41	0.7	1.1	0.3	PFMF.020.2	■
4.37	4.73	3.07	3.41	0.7	1.1	0.3	PFMF.030.2	■
4.37	4.73	3.07	3.41	0.55	0.85	0.3	PFMF.050.2	■
4.37	4.73	3.07	3.41	0.55	0.85	0.3	PFMF.075.2	■
4.37	4.73	3.07	3.41	0.55	0.85	0.3	PFMF.075.24.2	
4.37	4.73	3.07	3.41	0.45	0.85	0.3	PFMF.110.2	
4.37	4.73	3.07	3.41	0.45	0.85	0.3	PFMF.110.16.2	
4.37	4.73	3.07	3.41	0.55	0.85	0.3	PFMF.125.2	
4.37	4.73	3.07	3.41	0.55	0.85	0.3	PFMF.150.2	
4.37	4.73	3.07	3.41	0.55	0.85	0.3	PFMF.160.2	
4.37	4.73	3.07	3.41	0.55	0.85	0.3	PFMF.200.2	
4.37	4.83	3.07	3.41	0.7	1.6	0.3	PFMF.250.16.2	
4.37	4.73	3.07	3.41	0.48	0.85	0.3	PFMF.260.2	

■ Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Thermal Derating Chart Ihold [A]

Order Number	-40 °C	-20 °C	0 °C	23 °C	40 °C	50 °C	60 °C	70 °C	85 °C	Order Number
PFMF.010.2	0.16	0.14	0.12	0.1	0.08	0.07	0.06	0.05	0.03	PFMF.010.2
PFMF.014.2	0.23	0.19	0.17	0.14	0.12	0.1	0.09	0.08	0.06	PFMF.014.2
PFMF.020.2	0.29	0.26	0.23	0.2	0.17	0.15	0.14	0.12	0.1	PFMF.020.2
PFMF.030.2	0.44	0.39	0.35	0.3	0.26	0.23	0.21	0.18	0.15	PFMF.030.2
PFMF.050.2	0.77	0.68	0.59	0.5	0.44	0.4	0.37	0.33	0.29	PFMF.050.2
PFMF.075.2	1.15	1.01	0.88	0.75	0.65	0.6	0.55	0.49	0.43	PFMF.075.2
PFMF.075.24.2	1.15	1.01	0.88	0.75	0.65	0.6	0.55	0.49	0.43	PFMF.075.24.2

Order Number	-40 °C	-20 °C	0 °C	23 °C	40 °C	50 °C	60 °C	70 °C	85 °C	Order Number
PFMF.110.2	1.59	1.43	1.26	1.1	0.95	0.87	0.8	0.71	0.6	PFMF.110.2
PFMF.110.16.2	1.59	1.43	1.26	1.1	0.95	0.87	0.8	0.71	0.6	PFMF.110.16.2
PFMF.125.2	1.8	1.63	1.43	1.25	1.08	0.99	0.91	0.81	0.68	PFMF.125.2
PFMF.150.2	2.17	1.95	1.72	1.5	1.3	1.18	1.09	0.97	0.82	PFMF.150.2
PFMF.160.2	2.3	2.2	1.9	1.6	1.45	1.3	1.15	1.03	0.91	PFMF.160.2
PFMF.200.2	3.08	2.71	2.35	2	1.8	1.6	1.5	1.4	1.25	PFMF.200.2
PFMF.250.16.2	3.9	3.42	2.96	2.5	2.24	1.98	1.85	1.29	0.94	PFMF.250.16.2
PFMF.260.2	4	3.52	3.06	2.6	2.34	2.08	1.95	1.39	1.04	PFMF.260.2

Most Popular:

Availability for all products can be searched real-time:<https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Electrical Characteristics at 23 °C

V max [VDC]	I max [A]	I hold [A]	I trip [A]	R initial min [Ω]	R 1hour max [Ω]	Max Time to trip [A]	Max Time to Trip [s]	Tripped Power Dissipation [W]	Order Number	
60.0	40	0.1	0.3	0.7	15	0.5	1.5	0.80	PFMF.010.2	
60.0	40	0.14	0.34	0.4	6.5	1.5	0.15	0.80	PFMF.014.2	
30.0	80	0.2	0.4	0.4	6	6	0.06	0.80	PFMF.020.2	
30.0	10	0.3	0.6	0.3	3	8	0.1	0.80	PFMF.030.2	
15.0	100	0.5	1	0.15	1	8	0.15	0.80	PFMF.050.2	
13.2	100	0.75	1.5	0.11	0.45	8	0.2	0.80	PFMF.075.2	
24.0	40	0.75	1.5	0.11	0.45	8	0.2	0.80	PFMF.075.24.2	
6.0	100	1.1	2.2	0.04	0.21	8	0.3	0.80	PFMF.110.2	
16.0	100	1.1	2.2	0.04	0.21	8	0.3	0.80	PFMF.110.16.2	
6.0	100	1.25	2.5	0.035	0.14	8	0.4	0.80	PFMF.125.2	
6.0	100	1.5	3	0.03	0.12	8	0.5	0.80	PFMF.150.2	
8.0	100	1.6	2.8	0.035	0.099	8	2	0.80	PFMF.160.2	
8.0	40	2	4	0.02	0.08	8	3	0.80	PFMF.200.2	
16.0	100	2.5	5	0.015	0.1	8	5	1.20	PFMF.250.16.2	
6.0	100	2.6	5.2	0.015	0.08	8	5	0.80	PFMF.260.2	

Most Popular:

Availability for all products can be searched real-time:<https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging Unit acc. IEC 60286-3 Type 2a	PFMF.010.2 - 1500 pcs. in tape [W: 12mm and P1: 8mm] on reel [A: 18cm] PFMF.030.2
	PFMF.050.2 + 2000 pcs. in tape [W: 12mm and P1: 8mm] on reel [A: 18cm] PFMF.260.2