

**Part Number :** 1502010007

**Product Description :** Ditto Hermaphroditic Crimp Housing, Positive Lock, 7 Circuit, Glow-Wire Capable, Natural

**Series Number :** 150201

**Status :** Obsolete

**Product Category :** Connector Housings



## Documents & Resources

[1502010007.stp.zip](#)

### Specifications

[1501700000-AS-000.pdf](#)

[TS-150170-0000-001.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	ⓘ per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

### Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

- chemSHERPA (xml)

### Substances of Interest

- PFAS

### EU RoHS Certificate of Compliance

### Additional Product Compliance Information

## Part Details

### General

Status	Obsolete
Category	Connector Housings
Series	150201
Description	Ditto Hermaphroditic Crimp Housing, Positive Lock, 7 Circuit, Glow-Wire Capable, Natural
Application	Power, Wire-to-Wire
Product Name	Ditto
UPC	889056215787

### Agency

UL	E29179
----	--------

### Physical

Circuits (maximum)	7
Color - Resin	Natural (White)
Flammability	94V-2
Gender	Hermaphroditic
Glow-Wire Capable	Yes
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	1.904/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	3.00mm

Pitch - Termination Interface	3.00mm
Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +105°C, -40° to +80°C, See Product Specification

---

## Mates With / Use With

### Mates with Part(s)

Description	Part Number
Ditto Hermaphroditic Crimp Housings	<u>150201</u>

### Use with Part(s)

Description	Part Number
Ditto Hermaphroditic Crimp Terminal, Tin Brass, Preplated Tin, 22-20 AWG	<u>1502000001</u>
Ditto Hermaphroditic Crimp Terminal, Tin Brass, Preplated Tin, 26-24 AWG	<u>1502000002</u>
Ditto Terminal Position Assurance (TPA), 3.00mm Pitch, 7 Circuits, Glow-Wire Capable, Black	<u>1502130007</u>

---

This document was generated on Sep 13, 2025