Product data sheet

Specifications

Rack ATS, 16A, 230V, (2)IEC 309 in, (1)IEC 309 out



AP7722A

Discontinued on: Jun 30, 2021

End-of-service on: Jun 28, 2023

Discontinued

Main

Main Input Voltage	200 V 208 V 230 V
Output voltage	230 V
Input Connection Type	IEC 60309 16 A 2P + E
Number of rack unit	1U
Number of cables	2
Cable length	0.91 m
Provided equipment	Rack mounting brackets User manual
Network frequency	50/60 Hz
permissible voltage	200…240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3840 VA
Max current draw	16 A
Number of power socket outlets	1 IEC 60309 16 A 2P + E
Power cable length	0.9 m

Complementary

Colour	Black
Height	44 mm
Width	432 mm
Depth	236 mm
Product weight	4.21 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Downloaded from Arrow.com.

Product certifications	C-Tick CE GOST TÜV VCCI class A
Standards	EN 55022 class A EN 55024
Ambient air temperature for operation	-5…45 °C
Relative humidity	0…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25…65 °C
Storage Relative Humidity	0…95 %
Storage altitude	0…15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	34.9 cm
Package 1 Length	60 cm
Package 1 Weight	5.95 kg

Contractual warranty

Warranty (in months)	24

Downloaded from Arrow.com.

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Downloaded from Arrow.com.