



Bridgelux® Vesta® Series Tunable White Gen 2 18mm Array, 90 CRI and Thrive™

Product Data Sheet DS353

Downloaded from Arrow.com.


Product Feature Map

Bridgelux arrays are fully engineered devices that provide consistent thermal and optical performance on an engineered mechanical platform. The arrays incorporate several features to simplify design integration and assembly. Please visit www.bridgelux.com for more information on the Vesta Series family of products.



Product Nomenclature

The part number designation for Bridgelux Vesta Series arrays is explained as follows:



Downloaded from Arrow.com.

Product Selection Guide

The following product configurations are available:

Table 1: Selection Guide, Measurement Data

Part Number	Nominal CCT [1] T_c=85°C (K)	Typical CRI [2] T_c=85°C	Nominal Drive Current per channel (mA)	Typical V_f [3] T_c=25°C (V)	Typical Power T_c=25°C (W)	Typical Pulsed Flux [3, 4, 5] T_c=25°C (lm)	Typical Efficacy [5] T_c=25°C (lm/W)	Minimum Pulsed Flux [8] T_c=25°C (lm)	Typical DC Flux [7, 8] T_c=85°C (lm)
BXRV-TR-2750G-40A0-A-23	2700	93	900	35.2	31.7	3650	115	3285	3212
	5000	92	900	35.8	32.2	4150	129	3735	3611
BXRV-TR-2765G-40A0-A-23	2700	93	900	35.2	31.7	3650	115	3285	3212
	6500	92	900	35.8	32.2	4150	129	3735	3611
BXRV-TR-2750S-40A0-A-23	2700	98, Thrive	900	35.2	31.7	3103	98	2792	2730
	5000	98, Thrive	900	35.8	32.2	3528	109	3175	3104
BXRV-TR-2765S-40A0-A-23	2700	98, Thrive	900	35.2	31.7	3103	98	2792	2730
	6500	98, Thrive	900	35.8	32.2	3528	109	3175	3104
BXRV-TR-1840G-40A0-A-2X	1800	92	900	35.2	31.7	2630	83	2367	2314
	4000	92	900	35.8	32.2	4000	124	3600	3480
BXRV-TR-1840S-40A0-A-2X	1800	92	900	35.2	31.7	2236	71	2012	1967
	4000	98, Thrive	900	35.8	32.2	3400	106	3060	2958
BXRV-TR-1830G-40A0-A-2X	1800	92	900	35.2	31.7	2600	82	2340	2288
	3000	92	900	35.8	32.2	3720	115	3348	3236

Notes for Table 1:

1. Nominal CCT as defined by ANSI C78.377-2017.
2. For CRI 92-93 products, the minimum CRI value is 90 and the minimum R9 value is 50. For CRI 98 Thrive products, the minimum CRI value is 95, Bridgelux maintains a ±3 tolerance on all CRI and R9 values.
3. Products tested under pulsed condition (10ms pulse width) at nominal drive current where T_j (junction temperature) = T_c (case temperature) = 25°C.
4. Typical performance values are provided as a reference only and are not a guarantee of performance.
5. Bridgelux maintains a ±7% tolerance on flux measurements.
6. Typical stabilized DC performance values are provided as reference only and are not a guarantee of performance.
7. Typical performance is estimated based on operation under DC (direct current) with LED array mounted onto a heat sink with thermal interface material and the case temperature maintained at 85°C. Based on Bridgelux test setup, values may vary depending on the thermal design of the luminaire and/or the exposed environment to which the product is subjected.
8. Minimum flux values at pulsed nominal drive current are guaranteed by 100% test.

Downloaded from Arrow.com.

European Product Registry for Energy Labeling

The European Product Registry for Energy Labeling (EPREL) is defined in the EU Regulation 2017/1369 to provide information about a product's energy efficiency to consumers. Together with Energy Labeling Regulation ELR (EU) 2019/2015, which was amended by regulation (EU) 2021/340 for energy labelling of light sources, manufacturers are required to declare an energy class based on key technical specifications from each of their product and register it in an open data base managed by EPREL. It is now a legal requirement for a vendor of light sources to upload information about their products into the EPREL database before placing these products on the market in the EU.

Table 2 provides a list of part numbers that are in compliance with EPREL regulations and are currently listed in the EPREL database.

At Bridgelux, we are fully committed to supplying products that are compliant with pertinent laws, rules, and obligation imposed by relevant government bodies including the ELR regulation. Customers can use these products with full confidence for any projects that fall under the EPREL requirement.

Table 2: Table of products registered in the European Product Registry for Energy Labeling (EPREL)

Part Number	CCT (K)	CRI	Current [3] (mA)	Voltage [3] (V)	Useful Flux [2] $Ø_{useful}$ Tc=85°C (lm)	Power (W)	Efficacy (lm/W)	Energy Efficiency Class [4] A G X	Registration No	URL [1]
BXRV-TR-2750G-40A0-A-23	5000	90	940	33.4	3726	31	118	E	876237	https://eprel.ec.europa.eu/qr/876237
BXRV-TR-2765G-40A0-A-23	6500	90	940	33.4	3726	31	118	E	879086	https://eprel.ec.europa.eu/qr/879086
BXRV-TR-2750S-40A0-A-23	5000	97	280	30.6	1031	9	120	E	876387	https://eprel.ec.europa.eu/qr/876387
BXRV-TR-2750S-40A0-A-23	6500	97	280	30.6	1031	9	120	E	854648	https://eprel.ec.europa.eu/qr/854648
BXRV-TR-1840G-40A0-A-2X	4000	90	550	31.8	2189	18	125	E	876345	https://eprel.ec.europa.eu/qr/876345
BXRV-TR-1840S-40A0-A-2X	4000	97	220	30.2	784	7	117	F	879083	https://eprel.ec.europa.eu/qr/879083
BXRV-TR-1830G-40A0-A-23	3000	90	320	30.8	941	10	96	F	2767306	https://eprel.ec.europa.eu/qr/2767306

Notes for Table 2:

1. The performance data in this table is a subset of the data that was submitted to EPREL for obtaining the energy class listed here. For accessing a complete set of technical documentation of Bridgelux registered products in the EPREL database, please visit one of the hyperlinks listed above.
2. For a definition of useful luminous flux ($Ø_{useful}$), please see the ELR regulations at https://tinyurl.com/4b6zvt4m.
3. For information on performance values at alternative drive conditions. please refer to the Product Selection Guide, Absolute Maximum Rating Table and Performance Curves in this data sheet.
4. EPREL requires a symbol for displaying the energy classification of a product in marketing literature. This symbol consists of a letter stating a product's

Downloaded from Arrow.com.

CRI and TM30 Characteristics for Vesta Arrays with Thrive


Table 3: Typical Color Rendering Index and TM-30 Values at T_c=85˚C

Nominal CCT[1]	R_f	R_g	Ra	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
2700K	96	99	98	96	98	97	94	96	95	98	98	97	95	91	92	96	97	97
4000K	95	99	98	99	99	99	98	98	98	97	98	98	98	99	92	98	99	98
5000K	96	99	98	98	98	98	95	98	96	97	97	95	96	97	91	97	98	96
6500K	96	99	98	98	98	99	97	98	98	99	98	95	96	98	93	98	99	96

Note for Table 3:

1. Applicable for part numbers BXRV-TR-xxxxS-10A0-B-23 with the Thrive spectrum
2. Bridgelux maintains a tolerance of ± 3 on Color Rendering Index R1-R15 measurements and TM-30 measurements.

Figure 1: 2700K Thrive TM-30 Graphs









Figure 2: 4000K Thrive TM-30 Graphs





Downloaded from Arrow.com.

Figure 3: 5000K Thrive TM-30 Graphs








Figure 4: 6500K Thrive TM-30 Graphs





Downloaded from Arrow.com.

Average Spectral Difference

Spectral Matching to Natural Light

The lighting market is in the early stages of adoption of human-centric lighting (HCL). HCL encompasses the effects of lighting on the physical and emotional health and well-being of people. Throughout evolution, the human visual system has evolved under the natural light of sun and fire. These light sources have standardized industry spectral power definitions that describe the state of natural light. However, conventional metrics such as CCT, CRI, and TM-30 fail to adequately quantify the naturalness, or closeness of these light sources to the standardized natural spectra. Due to a lack of an industry standard metric to quantitatively measure the naturalness of a light source, Bridgelux has pioneered a new metric that takes the guesswork out of comparing LED light sources to natural light.


Average Spectral Difference, or ASD, is calculated by measuring the absolute difference between two spectra at discrete wavelengths. These values are averaged across a wavelength range derived from the photopic response curve, or V(); a luminous efficiency function describing the average spectral sensitivity of human perception of brightness. The range of 425nm to 690nm was selected to remove the tails of the V() gaussian distribution below 1% of the peak value at 555nm, covering 99.9% of the area under the photopic response curve. Natural light is defined following the approach of IES TM-30; black body curves for light sources of ≤4000K and the CIE standard illuminant D for light sources of ≥ 5000K.

Natural light has an ASD of 0%; lower ASD values indicate a closer match to natural light. Thrive is engineered to provide the closest match to natural light available using proprietary chip, phosphor and packaging technology, resulting in an ASD between 8% to 11% for all CCTs used in Vesta products. By comparison, standard 80, 90, and 98 CRI light sources have ASD values that are 100% to 300% larger than Thrive. To learn more about the ASD metric, please review the Bridgelux whitepaper: Average Spectral Difference, a new method to make objective comparisons of naturalness between light sources; or contact your Bridgelux sales representative.

Table 4: Typical ASD Values at T_c=85˚C

Nominal CCT	ASD
2700K	11%
4000K	7%
5000K	9%
6500K	8%

Figure 5: SPD Comparison



Downloaded from Arrow.com.

Electrical Characteristics

Table 5: Electrical Characteristics

Part Number	CCT (K)	Nominal Drive Current (mA)	Forward Voltage Pulsed, T_c = 25°C [1, 2, 3, 7]			Typical Temperature Coefficient of Forward Voltage [4] $\Delta V_f / \Delta T_c$ (mV/°C)	Typical Thermal Resistance Junction to Case [5] (°C/W)	Driver Selection Voltages [6]	
			Minimum (V)	Typical (V)	Maximum (V)			V_f Min. Hot T_c = 105°C (V)	V_f Max. Cold T_c = -40°C (V)
BXRV-TR-xxxxX-40A0-A-2X	1800, 2700	900	33.1	35.2	37.3	-11.5	0.35	32.2	38.1
	3000, 4000 5000, 6500	900	33.7	35.8	37.9	-11.6		32.7	38.7

Notes for Table 5:

1. Parts are tested in pulsed conditions, T_c = 25°C. Pulse width is 10ms.
2. Voltage minimum and maximum are provided for reference only and are not a guarantee of performance.
3. Bridgelux maintains a tester tolerance of ± 0.10V on forward voltage measurements.
4. Typical temperature coefficient of forward voltage tolerance is ± 0.1mV for nominal current.
5. Thermal resistance value was calculated using total electrical input power; optical power was not subtracted from input power. The thermal interface material used during testing is not included in the thermal resistance value.
6. V_f min hot and max cold values are provided as reference only and are not guaranteed by test. These values are provided to aid in driver design and selection over the operating range of the product.
7. This product has been designed and manufactured per IEC 62031:2018. This product has passed dielectric withstand voltage testing at 500 V. The working voltage designated for the insulation is 60V DC. The maximum allowable voltage across the array must be determined in the end product application.

Downloaded from Arrow.com.

Absolute Maximum Ratings

Table 6: Maximum Ratings

Parameter	Maximum Rating
LED Junction Temperature (T_j)	125˚C
Storage Temperature	-40˚C to +105˚C
Operating Case Temperature [1] (T_c)	105˚C
Soldering Temperature [2]	350˚C or lower for a maximum of 6 seconds
Maximum Combined Drive Current [3, 4]	1400mA
Maximum Peak Pulsed Drive Current [5]	1680mA for 1800K/2700K, 1440mA for 3000K/4000K5000K/6500K
Maximum Total Power	49W

Notes for Table 6:

1. For IEC 62717 requirement, please contact Bridgelux Sales Support.
2. See Bridgelux Application Note AN101 "Handling and Assembly of LED Arrays" for more information.
3. The maximum drive current is defined as the maximum combined drive current in the 1800K/2700K and the 3000K/4000K/5000K/6500K channels. For example, if 1400mA is applied to the 1800K/2700K channel, then no current may be applied to the 3000K/4000K/5000K/6500K channel. If 400mA is applied to the 1800K/2700K channel, then a maximum of 1000mA may be applied to the 3000K/4000K/5000K/6500K channel.
4. Lumen maintenance and lifetime predictions are valid for drive current and case temperature conditions used for LM-80 testing as included in the applicable LM-80 test report. Contact your Bridgelux sales representatives for the LM-80 report.
5. Bridgelux recommends a maximum duty cycle of 10% and pulse width of 20ms when operating LED arrays at the maximum peak pulsed current specified. Maximum peak pulsed currents indicate values where the LED array can be driven without catastrophic failures.

Downloaded from Arrow.com.

Performance Curves

Figure 6: Forward Voltage vs. Forward Current, T_c=25°C




Figure 7: Relative Flux vs. Drive Current, T_c=25°C




Figure 8: Relative Flux vs. Case Temperature




Figure 9: Relative Voltage vs. Case Temperature




Figure 10: CCT vs. Relative Current, T_c= 85°C





Figure 11: CCT vs. Relative Current, T_c= 85°C



Downloaded from Arrow.com.

Performance Curves

Figure 12: CCT vs. Relative Current, Tc=85˚C




Figure 13: CCT vs. Relative Current, Tc=85˚C




Figure 14: CCT Tuning Range, T_c= 85˚C




Figure 15: CCT Tuning Range, Tc=85˚C




Figure 16: CCT Tuning Range, T_c= 85˚C





Figure 17: CCT Tuning Range, Tc=85˚C



Downloaded from Arrow.com.

Performance Curves

Figure 18: Relative Flux vs. Relative Current




Figure 19: Relative Flux vs. Relative Current





Figure 20: Relative Flux vs. Relative Current



Downloaded from Arrow.com.

Typical Radiation Pattern


Figure 21: Typical Spatial Radiation Pattern



Notes for Figure 21:

1. Typical viewing angle is 130°.
2. The viewing angle is defined as the off axis angle from the centerline where Iv is ½ of the peak value.


Figure 22: Typical Polar Radiation Pattern



Downloaded from Arrow.com.

Typical Color Spectrum


Figure 23: 2700K - 6500K with Thrive



Note for Figure 23:

1. Color spectra measured at nominal current and T_c = 85°C.


Figure 24: 2700K - 5000K with Thrive



Note for Figure 24:

1. Color spectra measured at nominal current and T_c = 85°C.


Figure 25: 2700K - 5000K with 90 CRI



Note for Figure 25:

1. Color spectra measured at nominal current and T_c = 25°C.


Figure 26: 2700K - 6500K with 90 CRI



Note for Figure 26:

1. Color spectra measured at nominal current and T_c = 25°C.


Figure 27: 1800K - 4000K with 90 CRI



Note for Figure 27:

1. Color spectra measured at nominal current and T_c = 25°C.

Figure 28: 1800K - 3000K with 90 CRI




Note for Figure 28:

1. Color spectra measured at nominal current and T_c = 25°C.

Downloaded from Arrow.com.

Typical Color Spectrum

Figure 29: 1800K - 4000K with Thrive




Note for Figure 29:

1. Color spectra measured at nominal current and T_c = 85°C.

Downloaded from Arrow.com.

Mechanical Dimensions

Figure 30: Mechanical Drawing Specifications



Notes for Figure 30:

1. Solder pads are labeled "+" to denote positive polarity and "-" to denote negative polarity. Solder pads have a gold surface finish.
2. Drawings are not to scale.
3. Drawing dimensions are in millimeters.
4. Unless otherwise specified, tolerances are ± 0.10mm.
5. The optical center of the LED array is nominally defined by the mechanical center of the array.
6. Bridgelux maintains a flatness of 0.1 mm across the mounting surface of the array. Refer to Application Notes for product handling, mounting and heat sink recommendations.

Downloaded from Arrow.com.

Color Binning Information

Figure 31: Graph of Bins in xy Color Space, Tc=85°C





Table 7: McAdam ellipse CCT color bin definitions for product operating at T_c = 85°C

CCT	Center Point	Bin Size	Axis a	Axis b	Rotation Angle
2700K	x=0.4578 y= 0.4101	3 SDCM	0.00810	0.00420	53.70°
5000K	x=0.3447 y=0.3553	3 SDCM	0.00822	0.00354	59.62°
6500K	x=0.3123 y=0.3282	3 SDCM	0.00690	0.00285	58.57°
1800K	x=0.5496 y=0.4081	5SDCM	0.01164	0.00655	40.00°
4000K	x=0.3818 y=0.3797	3SDCM	0.00939	0.00402	53.72°
1800K	x=0.5496 y=0.4081	3SDCM	0.00699	0.00393	40.00°
3000K	x=0.4338 y=0.4030	3SDCM	0.00834	0.00408	53.22°

Notes for Table 7:

1. The x,y center points are the center points of the respective ANSI bins in the CIE 1931 xy Color Space
2. Products are binned at Tc=85°C
3. Bridgelux maintains a tolerance of +/-0.007 on x and y color coordinates in the CIE 1931 Color Space


Figure 32: Definition of the McAdam ellipse



Downloaded from Arrow.com.

Packaging and Labeling


Figure 33: Packaging Specifications



Tube label



Bag label



Box label



Notes for Figure 33:

1. Each tube holds 20 Vesta Series Tunable White 18mm arrays.
2. Four tubes are sealed in an anti-static bag. Up to five such bags are placed in a box and shipped. Depending on quantities ordered, a bigger shipping box, containing four boxes will be used to ship products.
3. Each bag and box is to be labeled as shown above.
4. Dimensions for each tube are 510.0 mm (L) x 26.3 mm (W) x 9.5 mm (H). Dimensions for the anti-static bag are 100.0 mm (W) x 625.0 mm (L) x 0.1 mm (T) and that of the inner box are 58.7 mm (L) x 13.3 mm (W) x 7.9 mm (H).

Figure 34: Product Labeling

Bridgelux arrays have laser markings on the back side of the substrate to help with product identification. In addition to the product identification markings, Bridgelux arrays also contain markings for internal Bridgelux manufacturing use only. The image below shows which markings are for customer use and which ones are for Bridgelux internal use only. The Bridgelux internal manufacturing markings are subject to change without notice, however these will not impact the form, function or performance of the array.



Downloaded from Arrow.com.

Design Resources

Application Notes

Vesta Series Tunable White arrays are intended for use in dry, indoor applications. Bridgelux has developed a comprehensive set of application notes and design resources to assist customers in successfully designing with the Vesta Series product family of LED array products. For a list of resources under development, visit www.bridgelux.com.

Optical Source Models

Optical source models and ray set files are available for all Bridgelux products. For a list of available formats, visit www.bridgelux.com.

3D CAD Models

Three dimensional CAD models depicting the product outline of all Bridgelux Vesta Series LED arrays are available in both IGS and STEP formats. Please contact your Bridgelux sales representative for assistance.

LM80

Please contact your Bridgelux sales representative for more information.

Precautions

CAUTION: CHEMICAL EXPOSURE HAZARD

Exposure to some chemicals commonly used in luminaire manufacturing and assembly can cause damage to the LED array. Please consult Bridgelux Application Note for additional information.

CAUTION: EYE SAFETY

Eye safety classification for the use of Bridgelux Vesta Series is in accordance with IEC/TR62778 specification 'IEC 62471 for the assessment of blue light hazard to light source and luminaires'. Vesta Series Tunable White arrays are classified as Risk Group 1 when operated at or below the maximum drive current. Please use appropriate precautions. It is important that employees working with LEDs are trained to use them safely.

CAUTION: RISK OF BURN

Do not touch the Vesta Series LED array during operation. Allow the array to cool for a sufficient period of time before handling. The Vesta Series LED array may reach elevated temperatures such that could burn skin when touched.

CAUTION

CONTACT WITH LIGHT EMITTING SURFACE (LES)

Avoid any contact with the LES. Do not touch the LES of the LED array or apply stress to the LES (yellow phosphor resin area). Contact may cause damage to the LED array.

Optics and reflectors must not be mounted in contact with the LES (yellow phosphor resin area). Optical devices may be mounted on the top surface of the Vesta Series LED array. Use the mechanical features of the LED array housing, edges and/or mounting holes to locate and secure optical devices as needed.

Disclaimers

STANDARD TEST CONDITIONS

Unless otherwise stated, array testing is performed at the nominal drive current.

MINOR PRODUCT CHANGE POLICY

The rigorous qualification testing on products offered by Bridgelux provides performance assurance. Slight cosmetic changes that do not affect form, fit, or function may occur as Bridgelux continues product optimization.

Downloaded from Arrow.com.

About Bridgelux: Bridging Light and Life™

At Bridgelux, we help companies, industries and people experience the power and possibility of light. Since 2002, we've designed LED solutions that are high performing, energy efficient, cost effective and easy to integrate. Our focus is on light's impact on human behavior, delivering products that create better environments, experiences and returns—both experiential and financial. And our patented technology drives new platforms for commercial and industrial luminaires.

For more information about the company, please visit
bridgelux.com
twitter.com/Bridgelux
facebook.com/Bridgelux
youtube.com/user/Bridgelux
linkedin.com/company/bridgelux
WeChat ID: BridgeluxInChina

46410 Fremont Blvd
Fremont, CA 94538 USA
Tel (925) 583-8400
www.bridgelux.com

© 2026 Bridgelux, Inc. All rights reserved . Product specifications are subject to change without notice. Bridgelux, the Bridgelux stylized logo design and Vesta are registered trademarks of Bridgelux, Inc. All other trademarks are the property of their respective owners.

Downloaded from Arrow.com.