# molex

Part Number: 2196711124

Product Description: Pre-Crimped Lead Mini-Fit Sigma Female-to-Pigtail, Tin (Sn) Plating, 300.00mm Length, 16 AWG, Black

Series Number: 219671

Status: Active

**Product Category:** Power and Signal Cable

**Assemblies** 



#### **Documents & Resources**

# **Drawings**

2196711124\_sd.pdf

# **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2024)7663-DC<br>(21 Jan 2025) |
| EU RoHS            | Compliant per EU 2015/863                         |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### **EU RoHS Certificate of Compliance**

# **Part Details**

# General

| Status                 | Active  |
|------------------------|---|
| Category               | Power and Signal Cable Assemblies   |
| Series                 | 219671  |
| Description            | Pre-Crimped Lead Mini-Fit Sigma<br>Female-to-Pigtail, Tin (Sn) Plating,<br>300.00mm Length, 16 AWG, Black |
| Application            | Power, Wire-to-Board, Wire-to-Wire  |
| Assembly Configuration | Pre-crimped Lead Only   |
| Connector to Connector | Mini-Fit Sigma-to-Pigtail   |
| Product Name           | Mini-Fit Sigma  |
| UPC                    | 195842811119  |

# **Electrical**

| Current - Maximum per Contact | 11.5A      |
|-------------------------------|------------|
| Voltage - Maximum             | 600V AC/DC |

# Physical

| Cable Length                   | 300.00mm             |
|--------------------------------|----------------------|
| Circuits (Loaded)              | 1                    |
| Circuits (maximum)             | 1                    |
| Color - Resin                  | Black                |
| Gender                         | Female-Pigtail       |
| Material - Metal               | Brass                |
| Material - Plating Mating      | Tin                  |
| Material - Plating Termination | Tin                  |
| Net Weight                     | 4.731/g              |
| Number of Rows                 | 1                    |
| Packaging Type                 | Bag                  |
| Plating min - Mating           | 2.500µm              |
| Single Ended                   | Yes                  |
| Termination Interface Style    | Crimp or Compression |
| Wire/Cable Type                | UL 11028             |
| Wire Size (AWG)                | 16                   |

# Use with Part(s)

| Description  | Part Number   |
|--|---------------|
| Mini-Fit TPA2 and Mini-Fit Sigma<br>Dual Row Receptacle Housings   | <u>172708</u> |
| Mini-Fit TPA2 and Mini-Fit Sigma<br>Single Row Receptacle Housings | 200453        |

This document was generated on Apr 26, 2025