

DUAL HOT SWAP POWER CONTROLLERS WITH INDEPENDENT CIRCUIT BREAKER

Check for Samples: [TPS2320](#), [TPS2321](#)

FEATURES

- Dual-Channel High-Side MOSFET Drivers
- IN1: 3 V to 13 V; IN2: 3 V to 5.5 V
- Output dV/dt Control Limits Inrush Current
- Independent Circuit-Breaker With Programmable Overcurrent Threshold and Transient Timer
- CMOS- and TTL-Compatible Enable Input
- Low, 5-µA Standby Supply Current (Max)
- Available in 16-Pin SOIC and TSSOP Package
- –40°C to 85°C Ambient Temperature Range
- Electrostatic Discharge Protection


APPLICATIONS

- Hot-Swap/Plug/Dock Power Management
- Hot-Plug PCI, Device Bay
- Electronic Circuit Breaker

DESCRIPTION

The TPS2320 and TPS2321 are dual-channel hot-swap controllers that use external N-channel MOSFETs as high-side switches in power applications. Features of these devices, such as overcurrent protection (OCP), inrush-current control, and the ability to discriminate between load transients and faults, are critical requirements for hot-swap applications.

The TPS2320/21 devices incorporate undervoltage lockout (UVLO) to ensure the device is off at startup. Each internal charge pump, capable of driving multiple MOSFETs, provides enough gate-drive voltage to fully enhance the N-channel MOSFETs. The charge pumps control both the rise times and fall times (dv/dt) of the MOSFETs, reducing power transients during power up/down. The circuit-breaker functionality combines the ability to sense overcurrent conditions with a timer function; this allows designs such as DSPs, that may have high peak currents during power-state transitions, to disregard transients for a programmable period.



NOTE: Terminal 14 is active-high on TPS2321.

typical application




Table 1. AVAILABLE OPTIONS

| T _A | HOT-SWAP CONTROLLER DESCRIPTION | PIN COUNT | PACKAGES | |
|----------------|--|-----------|-------------------------|-------------------------|
| | | | ENABLE | ENABLE |
| –40°C to 85°C | Dual-channel with independent OCP and adjustable PG | 20 | TPS2300IPW | TPS2301IPW |
| | Dual-channel with interdependent OCP and adjustable PG | 20 | TPS2310IPW | TPS2311IPW |
| | Dual-channel with independent OCP | 16 | TPS2320ID TPS2320IPW | TPS2321ID TPS2321IPW |
| | Single-channel with OCP and adjustable PG | 14 | TPS2330ID TPS2330IPW | TPS2331ID TPS2331IPW |



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of the Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2000–2013, Texas Instruments Incorporated

FUNCTIONAL BLOCK DIAGRAM




Table 2. Terminal Functions

| TERMINAL NAME | NO. | I/O | DESCRIPTION |
|------------------|-----|-----|--|
| AGND | 6 | I | Analog ground, connects to DGND as close as possible |
| DGND | 3 | I | Digital ground |
| DISCH1 | 16 | O | Discharge transistor 1 |
| DISCH2 | 15 | O | Discharge transistor 2 |
| ENABLE/ENABLE | 14 | I | Active low (TPS2320) or active high enable (TPS2321) |
| FAULT | 13 | O | Overcurrent fault, open-drain output |
| GATE1 | 1 | O | Connects to gate of channel 1 high-side MOSFET |
| GATE2 | 2 | O | Connects to gate of channel 2 high-side MOSFET |
| IN1 | 9 | I | Input voltage for channel 1 |
| IN2 | 10 | I | Input voltage for channel 2 |
| ISENSE1 | 8 | I | Current-sense input channel 1 |
| ISENSE2 | 7 | I | Current-sense input channel 2 |
| ISET1 | 12 | I | Adjusts circuit-breaker threshold with resistor connected to IN1 |
| ISET2 | 11 | I | Adjusts circuit-breaker threshold with resistor connected to IN2 |
| TIMER | 4 | O | Adjusts circuit-breaker deglitch time |
| VREG | 5 | O | Connects to bypass capacitor, for stable operation |

DETAILED DESCRIPTION

DISCH1, DISCH2 – DISCH1 and DISCH2 should be connected to the sources of the external N-channel MOSFET transistors connected to GATE1 and GATE2, respectively. These pins discharge the loads when the MOSFET transistors are disabled. They also serve as reference-voltage connections for internal gate voltage-clamp circuitry.

ENABLE or $\overline{\text{ENABLE}}$ – $\overline{\text{ENABLE}}$ for TPS2320 is active low. ENABLE for TPS2321 is active high. When the controller is enabled, both GATE1 and GATE2 voltages will power up to turn on the external MOSFETs. When the ENABLE pin is pulled high for TPS2320 or the ENABLE pin is pulled low for TPS2321 for more than 50 μs , the gate of the MOSFET is discharged at a controlled rate by a current source, and a transistor is enabled to discharge the output bulk capacitance. In addition, the device turns on the internal regulator PREREG (see VREG) when enabled and shuts down PREREG when disabled so that total supply current is much less than 5 μA .

FAULT – FAULT is an open-drain overcurrent flag output. When an overcurrent condition in either channel is sustained long enough to charge TIMER to 0.5 V, the overcurrent channel latches off and pulls FAULT low. The other channel will run normally if not in overcurrent. In order to turn the channel back on, either the enable pin has to be toggled or the input power has to be cycled.

GATE1, GATE2 – GATE1 and GATE2 connect to the gates of external N-channel MOSFET transistors. When the device is enabled, internal charge-pump circuitry pulls these pins up by sourcing approximately 15 μA to each. The turnon slew rates depend upon the capacitance present at the GATE1 and GATE2 terminals. If desired, the turnon slew rates can be further reduced by connecting capacitors between these pins and ground. These capacitors also reduce inrush current and protect the device from false overcurrent triggering during power up. The charge-pump circuitry will generate gate-to-source voltages of 9 V-12 V across the external MOSFET transistors.

IN1, IN2 – IN1 and IN2 should be connected to the power sources driving the external N-channel MOSFET transistors connected to GATE1 and GATE2, respectively. The TPS2320/TPS2321 draws its operating current from IN1, and both channels will remain disabled until the IN1 power supply has been established. The IN1 channel has been constructed to support 3-V, 5-V, or 12-V operation, while the IN2 channel has been constructed to support 3-V or 5-V operation

ISENSE1, ISENSE2, ISET1, ISET2 – ISENSE1 and ISENSE2, in combination with ISET1 and ISET2, implement overcurrent sensing for GATE1 and GATE2. ISET1 and ISET2 set the magnitude of the current that generates an overcurrent fault, through external resistors connected to ISET1 and ISET2. An internal current source draws 50 μA from ISET1 and ISET2. With a sense resistor from IN1 to ISENSE1 or from IN2 to ISENSE2, which is also connected to the drains of external MOSFETs, the voltage on the sense resistor reflects the load current. An overcurrent condition is assumed to exist if ISENSE1 is pulled below ISET1 or if ISENSE2 is pulled below ISET2. To ensure proper circuit breaker operation, $V_{I(\text{ISENSE1})}$ and $V_{I(\text{ISET1})}$ should never exceed $V_{I(\text{IN1})}$. Similarly, $V_{I(\text{ISENSE2})}$ and $V_{I(\text{ISET2})}$ should never exceed $V_{I(\text{IN2})}$.

TIMER – A capacitor on TIMER sets the time during which the power switch can be in overcurrent before turning off. When the overcurrent protection circuits sense an excessive current, a current source is enabled which charges the capacitor on TIMER. Once the voltage on TIMER reaches approximately 0.5 V, the circuit-breaker latch is set and the power switch is latched off. Power must be recycled or the ENABLE pin must be toggled to restart the controller. In high-power or high-temperature applications, a minimum 50-pF capacitor is strongly recommended from TIMER to ground, to prevent any false triggering.

VREG – VREG is the output of an internal low-dropout voltage regulator, where IN1 is the input. The regulator is used to generate a regulated voltage source, less than 5.5 V, for the device. A 0.1- μF ceramic capacitor should be connected between VREG and ground to aid in noise rejection. In this configuration, upon disabling the device, the internal low-dropout regulator will also be disabled, which removes power from the internal circuitry and allows the device to be placed in low-quiescent-current mode. In applications where IN1 is less than 5.5 V, VREG and IN1 may be connected together. However, under these conditions, disabling the device will not place the device in low-quiescent-current mode, because the internal low-dropout voltage regulator is being bypassed, thereby keeping internal circuitry operational. If VREG and IN1 are connected together, a 0.1- μF ceramic capacitor between VREG and ground is not needed if IN1 already has a bypass capacitor of 1 μF to 10 μF .

ABSOLUTE MAXIMUM RATINGS

over operating free-air temperature range (unless otherwise noted) ⁽¹⁾ ⁽²⁾

| | | VALUE | UNIT |
|--|---|------------|------|
| Input voltage range | $V_{I(IN1)}$, $V_{I(ISENSE1)}$, $V_{I(ISET1)}$, $V_{I(ENABLE)}$ | –0.3 to 15 | V |
| | $V_{I(IN2)}$, $V_{I(ISENSE2)}$, $V_{I(ISET2)}$, $V_{I(VREG)}$ | –0.3 to 7 | V |
| Output voltage range | $V_{O(GATE1)}$ | –0.3 to 30 | V |
| | $V_{O(GATE2)}$ | –0.3 to 22 | V |
| | $V_{O(DISCH1)}$, $V_{O(FAULT)}$, $V_{O(DISCH2)}$, $V_{O(TIMER)}$ | –0.3 to 15 | V |
| Sink current range | $I_{(GATE1)}$, $I_{(GATE2)}$, $I_{(DISCH1)}$, $I_{(DISCH2)}$ | 0 to 100 | mA |
| | $I_{(TIMER)}$, $I_{(FAULT)}$ | 0 to 10 | mA |
| Operating virtual junction temperature range, T_J | | –40 to 100 | °C |
| Storage temperature range, T_{stg} | | –55 to 150 | °C |
| Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds | | 260 | °C |

- (1) Stresses beyond those listed under *absolute maximum ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *recommended operating conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltages are respect to DGND.

DISSIPATION RATING TABLE

| PACKAGE | $T_A \leq 25^\circ\text{C}$ POWER RATING | DERATING FACTOR ABOVE $T_A = 25^\circ\text{C}$ | $T_A = 70^\circ\text{C}$ POWER RATING | $T_A = 85^\circ\text{C}$ POWER RATING |
|---------|---|---|--|--|
| PW-16 | 823 mW | 10.98 mW/°C | 329 mW | 165 mW |
| D-16 | 674 mW | 8.98 mW/°C | 270 mW | 135 mW |

RECOMMENDED OPERATING CONDITIONS

| | | MIN | NOM | MAX | UNIT |
|--|--|-----|-----|--------------|------|
| V_I Input voltage | $V_{I(IN1)}$, $V_{I(ISENSE1)}$, $V_{I(ISET1)}$ | 3 | | 13 | V |
| | $V_{I(IN2)}$, $V_{I(ISENSE2)}$, $V_{I(ISET2)}$, $V_{I(VREG)}$ | 3 | | 5.5 | |
| | $V_{I(ISENSE1)}$, $V_{I(ISET1)}$ | | | $V_{I(IN1)}$ | |
| | $V_{I(ISENSE2)}$, $V_{I(ISET2)}$ | | | $V_{I(IN2)}$ | |
| T_J Operating virtual junction temperature | | –40 | | 100 | °C |

ELECTRICAL CHARACTERISTICS

over recommended operating temperature range ($-40^{\circ}\text{C} < T_A < 85^{\circ}\text{C}$), $3\text{V} \leq V_{I(IN1)} \leq 13\text{V}$, $3\text{V} \leq V_{I(IN2)} \leq 5.5\text{V}$ (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | MIN | TYP | MAX | UNIT |
|-----------------------------|---|--|------------------------------|----------------------------|------|-----|------|
| GENERAL | | | | | | | |
| I _{I(IN1)} | Input current, IN1 | V _{I(ENABLE)} = 5 V (TPS2321), V _{I(ENABLE)} = 0 V (TPS2320) | | 0.5 | | 1 | mA |
| I _{I(IN2)} | Input current, IN2 | | | 75 | | 200 | μA |
| I _{I(stby)} | Standby current (sum of currents into IN1, IN2, ISENSE1, ISENSE2, ISET1, and ISET2) | V _{I(ENABLE)} = 0 V (TPS2321), V _{I(ENABLE)} = 5 V (TPS2320) | | | | 5 | μA |
| GATE1 | | | | | | | |
| V _{G(GATE1_3V)} | Gate voltage | I _{I(GATE1)} = 500 nA, DISCH1 open | V _{I(IN1)} = 3 V | 9 | 11.5 | V | |
| V _{G(GATE1_4.5V)} | | | V _{I(IN1)} = 4.5 V | 10.5 | 14.5 | | |
| V _{G(GATE1_10.8V)} | | | V _{I(IN1)} = 10.8 V | 16.8 | 21 | | |
| V _{C(GATE1)} | Clamping voltage, GATE1 to DISCH1 | | | 9 | 10 | 12 | V |
| I _{S(GATE1)} | Source current, GATE1 | 3 V ≤ V _{I(IN1)} ≤ 13.2 V, 3 V ≤ V _{O(VREG)} ≤ 5.5 V, V _{I(GATE1)} = V _{I(IN1)} + 6 V | | 10 | 14 | 20 | μA |
| | Sink current, GATE1 | 3 V ≤ V _{I(IN1)} ≤ 13.2 V, 3 V ≤ V _{O(VREG)} ≤ 5.5 V, V _{I(GATE1)} = V _{I(IN1)} | | 50 | 75 | 100 | μA |
| t _{r(GATE1)} | Rise time, GATE1 | C _g to GND = 1 nF ⁽¹⁾ | V _{I(IN1)} = 3 V | 0.5 | | ms | |
| | | | V _{I(IN1)} = 4.5 V | 0.6 | | | |
| | | | V _{I(IN1)} = 10.8 V | 1 | | | |
| t _{f(GATE1)} | Fall time, GATE1 | C _g to GND = 1 nF ⁽¹⁾ | V _{I(IN1)} = 3 V | 0.1 | | ms | |
| | | | V _{I(IN1)} = 4.5 V | 0.12 | | | |
| | | | V _{I(IN1)} = 10.8 V | 0.2 | | | |
| GATE2 | | | | | | | |
| V _{G(GATE2_3V)} | Gate voltage | I _{I(GATE2)} = 500 nA, DISCH2 open | V _{I(IN2)} = 3 V | 9 | 11.7 | V | |
| V _{G(GATE2_4.5V)} | | | V _{I(IN2)} = 4.5 V | 10.5 | 14.7 | | |
| V _{C(GATE2)} | Clamping voltage, GATE2 to DISCH2 | | | 9 | 10 | 12 | V |
| I _{S(GATE2)} | Source current, GATE2 | 3 V ≤ V _{I(IN2)} ≤ 5.5 V, 3 V ≤ V _{O(VREG)} ≤ 5.5 V, V _{I(GATE2)} = V _{I(IN2)} + 6 V | | 10 | 14 | 20 | μA |
| | Sink current, GATE2 | 3 V ≤ V _{I(IN2)} ≤ 5.5 V, 3 V ≤ V _{O(VREG)} ≤ 5.5 V, V _{I(GATE2)} = V _{I(IN2)} | | 50 | 75 | 100 | μA |
| t _{r(GATE2)} | Rise time, GATE2 | C _g to GND = 1 nF ⁽¹⁾ | V _{I(IN2)} = 3 V | V _{O(VREG)} = 3 V | 0.5 | ms | |
| | | | V _{I(IN2)} = 4.5 V | | 0.6 | | |
| t _{f(GATE2)} | Fall time, GATE2 | C _g to GND = 1 nF ⁽¹⁾ | V _{I(IN2)} = 3 V | | 0.1 | ms | |
| | | | V _{I(IN2)} = 4.5 V | | 0.12 | | |

(1) Specified, but not production tested.

ELECTRICAL CHARACTERISTICS (Continued)

over recommended operating temperature range ($-40^{\circ}\text{C} < T_A < 85^{\circ}\text{C}$), $3\text{V} \leq V_{I(IN1)} \leq 13\text{V}$, $3\text{V} \leq V_{I(IN2)} \leq 5.5\text{V}$ (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--------------------------------------|--|--|-----|-----|-----|---------------|
| TIMER | | | | | | |
| $V_{(TO_TIMER)}$ | Threshold voltage, TIMER | | 0.4 | 0.5 | 0.6 | V |
| | Charge current, TIMER | $V_{I(TIMER)} = 0\text{ V}$ | 35 | 50 | 65 | μA |
| | Discharge current, TIMER | $V_{I(TIMER)} = 1\text{ V}$ | 1 | 2.5 | | mA |
| CIRCUIT BREAKER | | | | | | |
| $V_{IT(CB)}$ | Threshold voltage, circuit breaker | $R_{ISETx} = 1\text{ k}\Omega$ | 40 | 50 | 60 | mV |
| | | $R_{ISETx} = 400\text{ }\Omega$, $T_A = 25^{\circ}\text{C}$ | 14 | 19 | 24 | |
| | | $R_{ISETx} = 1\text{ k}\Omega$, $T_A = 25^{\circ}\text{C}$ | 44 | 50 | 53 | |
| | | $R_{ISETx} = 1.5\text{ k}\Omega$, $T_A = 25^{\circ}\text{C}$ | 68 | 73 | 78 | |
| $I_{(IB_ISENSEx)}$ | Input bias current, I_{SENSEx} | | | 0.1 | 5 | μA |
| | Discharge current, $GATEx$ | $V_{O(GATEx)} = 4\text{ V}$ | 400 | 800 | | mA |
| | | $V_{O(GATEx)} = 1\text{ V}$ | 25 | 150 | | |
| $t_{pd(CB)}$ | Propagation (delay) time, comparator inputs to gate output | $C_g = 50\text{ pF}$, 10 mV overdrive, $C_{TIMER} = 50\text{ pF}$ (50% to 10%), | | 1.3 | | μs |
| ENABLE, ACTIVE LOW (TPS2320) | | | | | | |
| $V_{IH(ENABLE)}$ | High-level input voltage, \overline{ENABLE} | | 2 | | | V |
| $V_{IL(ENABLE)}$ | Low-level input voltage, \overline{ENABLE} | | | | 0.8 | V |
| $R_{I(ENABLE)}$ | Input pullup resistance, \overline{ENABLE} | See ⁽¹⁾ | 100 | 200 | 300 | k Ω |
| $t_{d(off_ENABLE)}$ | Turnoff delay time, \overline{ENABLE} | $V_{I(\overline{ENABLE})}$ increasing above stop threshold; 100 ns rise time, 20 mV overdrive ⁽²⁾ | | 60 | | μs |
| $t_{d(on_ENABLE)}$ | Turnon delay time, \overline{ENABLE} | $V_{I(ENABLE)}$ decreasing below start threshold; 100 ns fall time, 20 mV overdrive ⁽²⁾ | | 125 | | μs |
| ENABLE, ACTIVE HIGH (TPS2321) | | | | | | |
| $V_{IH(ENABLE)}$ | High-level input voltage, ENABLE | | 2 | | | V |
| $V_{IL(ENABLE)}$ | Low-level input voltage, ENABLE | | | | 0.7 | V |
| $R_{I(ENABLE)}$ | Input pulldown resistance, ENABLE | | 100 | 150 | 300 | k Ω |
| $t_{d(on_ENABLE)}$ | Turnon delay time, ENABLE | $V_{I(ENABLE)}$ increasing above start threshold; 100 ns rise time, 20 mV overdrive ⁽²⁾ | | 85 | | μs |
| $t_{d(off_ENABLE)}$ | Turnoff delay time, ENABLE | $V_{I(ENABLE)}$ decreasing below stop threshold; 100 ns fall time, 20 mV overdrive ⁽²⁾ | | 100 | | μs |
| PREREG | | | | | | |
| $V_{(VREG)}$ | PREREG output voltage | $4.5 \leq V_{I(IN1)} \leq 13\text{ V}$ | 3.5 | 4.1 | 5.5 | V |
| $V_{(drop_PREREG)}$ | PREREG dropout voltage | $V_{I(IN1)} = 3\text{ V}$ | | | 0.1 | V |

- (1) Test I_O of \overline{ENABLE} at $V_{I(ENABLE)} = 1\text{ V}$ and 0 V , then $R_{I(ENABLE)} = \frac{1\text{ V}}{I_{O_0V} - I_{O_1V}}$
(2) Specified, but not production tested.

ELECTRICAL CHARACTERISTICS (Continued)

over recommended operating temperature range ($-40^{\circ}\text{C} < T_A < 85^{\circ}\text{C}$), $3\text{V} \leq V_{I(IN1)} \leq 13\text{V}$, $3\text{V} \leq V_{I(IN2)} \leq 5.5\text{V}$ (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--------------------------|---|---|------|------|------|---------------|
| VREG UVLO | | | | | | |
| $V_{(TO_UVLOstart)}$ | Output threshold voltage, start | | 2.75 | 2.85 | 2.95 | V |
| $V_{(TO_UVLOstop)}$ | Output threshold voltage, stop | | 2.65 | 2.78 | | V |
| $V_{hys(UVLO)}$ | Hysteresis | | 50 | 75 | | mV |
| | UVLO sink current, GATEx | $V_{I(GATEx)} = 2\text{ V}$ | 10 | | | mA |
| FAULT OUTPUT | | | | | | |
| $V_{O(sat_FAULT)}$ | Output saturation voltage, \overline{FAULT} | $I_O = 2\text{ mA}$ | | | 0.4 | V |
| $I_{lkg(FAULT)}$ | Leakage current, \overline{FAULT} | $V_{O(FAULT)} = 13\text{ V}$ | | | 1 | μA |
| DISCH1 AND DISCH2 | | | | | | |
| $I_{(DISCH)}$ | Discharge current, DISCHx | $V_{I(DISCHx)} = 1.5\text{ V}$, $V_{I(VIN1)} = 5\text{ V}$ | 5 | 10 | | mA |
| $V_{IH(DISCH)}$ | Discharge on high-level input voltage | | 2 | | | V |
| $V_{IL(DISCH)}$ | Discharge on low-level input voltage | | | | 1 | V |

PARAMETER MEASUREMENT INFORMATION




Figure 1. Turnon Voltage Transition of Channel 1




Figure 2. Turnoff Voltage Transition of Channel 1




Figure 3. Turnon Voltage Transition of Channel 2




Figure 4. Turnoff Voltage Transition of Channel 2

PARAMETER MEASUREMENT INFORMATION (continued)




Figure 5. Channel 1 Overcurrent Response: Enabled Into Overcurrent Load




Figure 6. Channel 1 Overcurrent Response: an Overcurrent Load Plugged Into the Enabled Board




Figure 7. Channel 2 Overcurrent Response: Enabled Into Overcurrent Load




Figure 8. Channel 2 Overcurrent Response: an Overcurrent Load Plugged Into the Enabled Board

PARAMETER MEASUREMENT INFORMATION (continued)




Figure 9. Channel 1 – Enabled Into Short Circuit




Figure 10. Channel 2 – Enabled Into Short Circuit




Figure 11. Channel 1 – Hot Plug




Figure 12. Channel 1 – Hot Removal

PARAMETER MEASUREMENT INFORMATION (continued)




Figure 13. Channel 2 - Hot Plug








Figure 14. Channel 2 - Hot Removal

TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS (continued)




Figure 19.




Figure 20.




Figure 21.




Figure 22.

TYPICAL CHARACTERISTICS (continued)




Figure 23.




Figure 24.




Figure 25.

APPLICATION INFORMATION

Figure 26 shows a typical dual hot-swap application. The pullup resistor at $\overline{\text{FAULT}}$ should be relatively large (e.g., 100 k Ω) to reduce power loss, unless it is required to drive a large load.




Figure 26. Typical Dual Hot-Swap Application

INPUT CAPACITOR

A 0.1- μF ceramic capacitor in parallel with a 1- μF ceramic capacitor should be placed on the input power terminals near the connector on the hot-plug board to help stabilize the voltage rails on the cards. The TPS2320/01 does not need to be mounted near the connector or to these input capacitors. For applications with more severe power environments, a 2.2- μF , or higher, ceramic capacitor is recommended near the input terminals of the hot-plug board. A bypass capacitor for IN1 and for IN2 should be placed close to the device.

OUTPUT CAPACITOR

A 0.1- μF ceramic capacitor is recommended per load on the TPS2320/21; these capacitors should be placed close to the external FETs and to TPS2320/21. A larger bulk capacitor is also recommended on the load. The value of the bulk capacitor should be selected based on the power requirements and the transients generated by the application.

EXTERNAL FET

To deliver power from the input sources to the loads, each channel needs an external N-channel MOSFET. A few widely used MOSFETs are shown in Table 3. But many other MOSFETs on the market can also be used with TPS23xx in hot-swap systems.

Table 3. Some Available N-Channel MOSFETs

| CURRENT RANGE (A) | PART NUMBER | DESCRIPTION | MANUFACTURER |
|-------------------|--------------|--|-------------------------|
| 0 to 2 | IRF7601 | N-channel, $r_{\text{DS(on)}}$ = 0.035 Ω , 4.6 A, Micro-8 | International Rectifier |
| | MTSF3N03H2R2 | N-channel, $r_{\text{DS(on)}}$ = 0.040 Ω , 4.6 A, Micro-8 | ON Semiconductor |
| | MMSF5N02H2R2 | Dual N-channel, $r_{\text{DS(on)}}$ = 0.04 Ω , 5 A, SO-8 | ON Semiconductor |

Table 3. Some Available N-Channel MOSFETs (continued)

| CURRENT RANGE (A) | PART NUMBER | DESCRIPTION | MANUFACTURER |
|----------------------|--------------|---|-------------------------|
| 2 to 5 | IRF7401 | N-channel, $r_{DS(on)} = 0.022 \Omega$, 7 A, SO-8 | International Rectifier |
| | MMSF5N02HDR2 | N-channel, $r_{DS(on)} = 0.025 \Omega$, 5 A, SO-8 | ON Semiconductor |
| | IRF7313 | Dual N-channel, $r_{DS(on)} = 0.029 \Omega$, 5.2 A, SO-8 | International Rectifier |
| | SI4410 | N-channel, $r_{DS(on)} = 0.020 \Omega$, 8 A, SO-8 | Vishay Dale |
| 5 to 10 | IRLR3103 | N-channel, $r_{DS(on)} = 0.019 \Omega$, 29 A, d-Pak | International Rectifier |
| | IRLR2703 | N-channel, $r_{DS(on)} = 0.045 \Omega$, 14 A, d-Pak | International Rectifier |

TIMER

For most applications, a minimum capacitance of 50 pF is recommended to prevent false triggering. A capacitor should be connected between TIMER and ground. The presence of an overcurrent condition on either channel of the TPS2320/TPS2321 causes a 50- μ A current source to begin charging this capacitor. If the over-current condition persists until the capacitor has been charged to approximately 0.5 V, the TPS2320/TPS2321 latches off the offending channels and pulls the $\overline{\text{FAULT}}$ pin low. The timer capacitor can be made as large as desired to provide additional time delay before registering a fault condition. PWRGDx will not correctly report power conditions when the device is disabled. The time delay is approximately:

$$dt(\text{sec}) = C_{\text{TIMER}}(F) \times 10,000(\Omega).$$

OUTPUT-VOLTAGE SLEW-RATE CONTROL

When enabled, the TPS2320/TPS2321 controllers supply the gates of each external MOSFET transistor with a current of approximately 15 μ A. The slew rate of the MOSFET source voltage is thus limited by the gate-to-drain capacitance C_{gd} of the external MOSFET capacitor to a value approximating:

$$\frac{dV_s}{dt} = \frac{15 \mu\text{A}}{C_{gd}} \quad (1)$$

If a slower slew rate is desired, an additional capacitance can be connected between the gate of the external MOSFET and ground.

VREG CAPACITOR

The internal voltage regulator connected to VREG requires an external capacitor to ensure stability. A 0.1- μ F or 0.22- μ F ceramic capacitor is recommended.

GATE-DRIVE CIRCUITRY

The TPS2320/TPS2321 includes four separate features associated with each gate-drive terminal:

- A charging current of approximately 15 μ A is applied to enable the external MOSFET transistor. This current is generated by an internal charge pump that can develop a gate-to-source potential (referenced to DISCH1 or DISCH2) of 9 V–12 V. DISCH1 and DISCH2 must be connected to the respective external MOSFET source terminals to ensure proper operation of this circuitry.
- A discharge current of approximately 75 μ A is applied to disable the external MOSFET transistor. Once the transistor gate voltage has dropped below approximately 1.5 V, this current is disabled and the UVLO discharge driver is enabled instead. This feature allows the part to enter a low-current shutdown mode while ensuring that the gates of the external MOSFET transistors remain at a low voltage.
- During a UVLO condition, the gates of both MOSFET transistors are pulled down by internal PMOS transistors. These transistors continue to operate even if IN1 and IN2 are both at 0 V. This circuitry also helps hold the external MOSFET transistors off when power is suddenly applied to the system.
- During an overcurrent fault condition, the external MOSFET transistor that exhibited an overcurrent condition will be rapidly turned off by an internal pulldown circuit capable of pulling in excess of 400 mA (at 4 V) from the pin. Once the gate has been pulled below approximately 1.5 V, this driver is disengaged and the UVLO driver is enabled instead. If one channel experiences an overcurrent condition and the other does not, then only the channel that is conducting excessive current will be turned off rapidly. The other channel will continue to operate normally.

SETTING THE CURRENT-LIMIT CIRCUIT-BREAKER THRESHOLD

Using channel 1 as an example, the current sensing resistor $R_{ISENSE1}$ and the current-limit-setting resistor R_{ISET1} determine the current limit of the channel, and can be calculated by the following equation:

$$I_{LMT1} = \frac{R_{ISET1} \times 50 \times 10^{-6}}{R_{ISENSE1}} \quad (2)$$

Typically $R_{ISENSE1}$ is very small (0.001 Ω to 0.1 Ω). If the trace and solder-junction resistances between the junction of $R_{ISENSE1}$ and ISENSE1 and the junction of $R_{ISENSE1}$ and R_{ISET1} are greater than 10% of the $R_{ISENSE1}$ value, then these resistance values should be added to the $R_{ISENSE1}$ value used in the calculation above.

The above information and calculation also apply to channel 2. Table 4 shows some of the current sense resistors available in the market.

Table 4. Some Current Sense Resistors

| CURRENT RANGE (A) | PART NUMBER | DESCRIPTION | MANUFACTURER |
|-------------------|--------------------|--------------------------------------|--------------|
| 0 to 1 | WSL-1206, 0.05 1% | 0.05 Ω , 0.25 W, 1% resistor | Vishay Dale |
| 1 to 2 | WSL-1206, 0.025 1% | 0.025 Ω , 0.25 W, 1% resistor | |
| 2 to 4 | WSL-1206, 0.015 1% | 0.015 Ω , 0.25 W, 1% resistor | |
| 4 to 6 | WSL-2010, 0.010 1% | 0.010 Ω , 0.5 W, 1% resistor | |
| 6 to 8 | WSL-2010, 0.007 1% | 0.007 Ω , 0.5 W, 1% resistor | |
| 8 to 10 | WSR-2, 0.005 1% | 0.005 Ω , 0.5 W, 1% resistor | |

UNDERVOLTAGE LOCKOUT (UVLO)

The TPS2320/TPS2321 includes an undervoltage lockout (UVLO) feature that monitors the voltage present on the VREG pin. This feature will disable both external MOSFETs if the voltage on VREG drops below 2.78 V (nominal) and will re-enable normal operation when it rises above 2.85 V (nominal). Since VREG is fed from IN1 through a low-dropout voltage regulator, the voltage on VREG will track the voltage on IN1 within 50 mV. While the undervoltage lockout is engaged, both GATE1 and GATE2 are held low by internal PMOS pulldown transistors, ensuring that the external MOSFET transistors remain off at all times, even if all power supplies have fallen to 0 V.

SINGLE-CHANNEL OPERATION

Some applications may require only a single external MOS transistor. Such applications should use GATE1 and the associated circuitry (IN1, ISENSE1, ISET1, DISCH1). The IN2 pin should be grounded to disable the circuitry associated with the GATE2 pin.

POWER-UP CONTROL

The TPS2320/TPS2321 includes a 500 μ s (nominal) startup delay that ensures that internal circuitry has sufficient time to start before the device begins turning on the external MOSFETs. This delay is triggered only upon the rapid application of power to the circuit. If the power supply ramps up slowly, the undervoltage lockout circuitry will provide adequate protection against undervoltage operation.

3-CHANNEL HOT-SWAP APPLICATION

Some applications require hot-swap control of up to three voltage rails, but may not explicitly require the sensing of the status of the output power on all three of the voltage rails. One such application is device bay, where dv/dt control of 3.3 V, 5 V, and 12 V is required. By using Channel 2 to drive both the 3.3-V and 5-V power rails and Channel 1 to drive the 12-V power rail, as is shown below, TPS2320/01 can deliver three different voltages to three loads while monitoring the status of two of the loads.




Figure 27. Three-Channel Application

Figure 28 shows ramp-up waveforms of the three output voltages.




Figure 28.

REVISION HISTORY

Note: Revision history for previous versions is not available. Page numbers of previous versions may differ.

| Changes from Revision E (November 2006) to Revision F | Page |
|--|------|
| • Added text to ISENSE1, ISENSE2, ISET1, ISET2 pin description paragraph for clarification. | 3 |
| • Added additional V_I specs to ROC table for clarification | 4 |
| • Added minus sign to 40°C MIN T_J temperature | 4 |

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| TPS2320ID | ACTIVE | SOIC | D | 16 | 40 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | TPS2320I | Samples |
| TPS2320IDG4 | ACTIVE | SOIC | D | 16 | 40 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | TPS2320I | Samples |
| TPS2320IDR | ACTIVE | SOIC | D | 16 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | TPS2320I | Samples |
| TPS2320IDRG4 | ACTIVE | SOIC | D | 16 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | TPS2320I | Samples |
| TPS2320IPW | ACTIVE | TSSOP | PW | 16 | 90 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | PD2320I | Samples |
| TPS2320IPWG4 | ACTIVE | TSSOP | PW | 16 | 90 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | PD2320I | Samples |
| TPS2320IPWR | ACTIVE | TSSOP | PW | 16 | 2000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | PD2320I | Samples |
| TPS2320IPWRG4 | ACTIVE | TSSOP | PW | 16 | 2000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | PD2320I | Samples |
| TPS2321ID | ACTIVE | SOIC | D | 16 | 40 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | TPS2321I | Samples |
| TPS2321IPW | ACTIVE | TSSOP | PW | 16 | 90 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | PD2321I | Samples |
| TPS2321IPWR | ACTIVE | TSSOP | PW | 16 | 2000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | PD2321I | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBsolete: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

⁽⁴⁾ There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

⁽⁵⁾ Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

⁽⁶⁾ Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

D (R-PDSO-G16)

PLASTIC SMALL OUTLINE



4040047-6/M 06/11

- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
 - D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
 - E. Reference JEDEC MS-012 variation AC.

D (R-PDSO-G16)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate designs.
 - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
 - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PW (R-PDSO-G16)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - B. This drawing is subject to change without notice.
 - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
 - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
 - E. Falls within JEDEC MO-153

PW (R-PDSO-G16)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate designs.
 - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
 - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

| | |
|------------------------------|--|
| Audio | www.ti.com/audio |
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DLP® Products | www.dlp.com |
| DSP | dsp.ti.com |
| Clocks and Timers | www.ti.com/clocks |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| RFID | www.ti-rfid.com |
| OMAP Applications Processors | www.ti.com/omap |
| Wireless Connectivity | www.ti.com/wirelessconnectivity |

Applications

| | |
|-------------------------------|--|
| Automotive and Transportation | www.ti.com/automotive |
| Communications and Telecom | www.ti.com/communications |
| Computers and Peripherals | www.ti.com/computers |
| Consumer Electronics | www.ti.com/consumer-apps |
| Energy and Lighting | www.ti.com/energy |
| Industrial | www.ti.com/industrial |
| Medical | www.ti.com/medical |
| Security | www.ti.com/security |
| Space, Avionics and Defense | www.ti.com/space-avionics-defense |
| Video and Imaging | www.ti.com/video |

TI E2E Community

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2016, Texas Instruments Incorporated