

ConnectPort® X2

ZigBee Smart Energy Certified IP Gateway

Gateways with the ZigBee Smart Energy public profile provide interoperable IP-to-application connectivity.



Overview

The ConnectPort X2 for Smart Energy provides a low-cost connection between a Home Area Network (HAN) and an energy service provider's software application over an IP connection. The gateway incorporates the ZigBee Smart Energy wireless standard (or "Public Application Profile"), making it interoperable with non-Digi devices. The ZigBee Smart Energy standard also allows the ConnectPort X2 to define what information the device will send over the network and how to behave with other devices on the network.

ConnectPort X2 can be combined with Device Cloud by Etherios™ service to create a platform for serving data to a software application layer. This allows energy service providers to develop their own unique, customizable Smart Energy solutions without designing customized hardware.

Built on the XBee-PRO® ZB ZigBee module, the gateways feature firmware supporting the implementation of each of the eight devices defined in the ZigBee Smart Energy Public Application Profile. The module also handles networking, joining, authentication and key establishment functions.

Related Products



Device Cloud Solutions



SE Gateways




SE Range Extenders



Dev Kits




Cellular Gateways



SE Ready Modules

Application Highlight



Features/Benefits

- Full certification as a ZigBee Alliance SE 1.0 Energy Service Portal enables the Home Area Network to operate independent from any Smart Meter network if needed
- Python® open scripting support enables the device to function as a secondary gateway alongside an installed Smart Energy certified meter
- Device Cloud service manages connectivity, configuration and software upgrades, and provides a web-services interface to any current or future energy service application
- Digi's hardware design expertise speeds time-to-market and software development



www.digi.com

Specifications		ConnectPort® X2 for Smart Energy	
General			
Management	HTTP/HTTPS web interface, Password access control, IP service port control, Optional secure enterprise management via Device Cloud		
Protocols	UDP/TCP, DHCP, SNMPv1		
LEDs	Ethernet status, Power, ZigBee link/activity		
Security	SSL tunnels		
ZigBee	XBee-PRO® 80 mW (+19.1 dBm, including 2.1 dBi antenna) / Int'l 10 mW (+10 dBm)		
Dimensions (L x W x H)	2.81 in x 2.74 in x 1.30 in (7.14 cm x 6.96 cm x 3.30 cm)		
Weight	0.20 lb (0.09 kg)		
Development			
ZigBee Public Application Profile	Smart Energy		
Python Version	2.4.3		
Memory (User-available memory varies by firmware and OS version)	8 MB RAM, 4 MB Flash		
Ethernet			
Ports	1 RJ-45 port		
Physical Layer	10/100Base-T		
Data Rate	10/100 Mbps (auto-sensing)		
Mode	Full or half duplex (auto-sensing)		
Power Requirements			
Power Input	5 VDC		
Power Supply	5 VDC power supply with barrel connector included		
Power Consumption	Idle: 1.2 W, Max: 3.4 W		
Surge Protection (with included power supply)	4 kV burst (EFT) per-4-4, 2 kV surge per EN61000-4		
Environmental			
Operating Temperature	-30° C to +70° C (-22° F to +158° F)		
Relative Humidity	5% to 95% (non-condensing)		
Ethernet Isolation	1500VAC min per IEEE802.3/ANSI X3.263		
Regulatory Approvals			
Safety	EN60950		
Emissions/Immunity	CE, FCC Part 15 (Class B), IC, ETSI, C-TICK, Telec		



Visit www.digi.com for part numbers.

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support

91001588
A7/513

**Digi International
Worldwide HQ**

877-912-3444
952-912-3444

**Digi International
France**

+33-1-55-61-98-98
www.digi.fr

**Digi International
Japan**

+81-3-5428-0261
www.digi-intl.co.jp

**Digi International
India**

+91-80-4287-9887

**Digi International
Singapore**

+65-6213-5380

**Digi International
China**

+86-21-5150-6898
www.digi.cn

BUY ONLINE • www.digi.com

2009-2013 Digi International Inc.

All rights reserved. Digi, Digi International, Etherios, the Digi logo, the Device Cloud by Etherios logo, ConnectPort, Device Cloud Device Cloud, XBee and XBee-PRO are trademarks or registered trademarks of Digi International Inc. in the United States and other countries worldwide. All other trademarks are the property of their respective owners. All information provided is subject to change without notice.

info@digi.com

