

ON Semiconductor

Is Now



To learn more about onsemi™, please visit our website at
www.onsemi.com

onsemi and **onsemi** and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries. onsemi owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of onsemi product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. onsemi reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and onsemi makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using onsemi products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by onsemi. "Typical" parameters which may be provided in onsemi data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. onsemi does not convey any license under any of its intellectual property rights nor the rights of others. onsemi products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use onsemi products for any such unintended or unauthorized application, Buyer shall indemnify and hold onsemi and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that onsemi was negligent regarding the design or manufacture of the part. onsemi is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.





ON Semiconductor®

FQB22P10TM-F085

100V P-Channel MOSFET

General Description

These P-Channel enhancement mode power field effect transistors are produced using ON Semiconductor proprietary, planar stripe, DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for low voltage applications such as audio amplifier, high efficiency switching DC/DC converters, and DC motor control.



Absolute Maximum Ratings

 $T_C = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	FQB22P10TM_F085	Units
V_{DSS}	Drain-Source Voltage	-100	V
I_D	Drain Current - Continuous ($T_C = 25^\circ\text{C}$)	-22	A
	- Continuous ($T_C = 100^\circ\text{C}$)	-15.6	A
I_{DM}	Drain Current - Pulsed	(Note 1)	A
V_{GSS}	Gate-Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy	(Note 2)	mJ
I_{AR}	Avalanche Current	(Note 1)	A
E_{AR}	Repetitive Avalanche Energy	(Note 1)	mJ
dv/dt	Peak Diode Recovery dv/dt	(Note 3)	V/ns
P_D	Power Dissipation ($T_A = 25^\circ\text{C}$) *	3.75	W
	Power Dissipation ($T_C = 25^\circ\text{C}$)	125	W
	- Derate above 25°C	0.83	W/ $^\circ\text{C}$
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to +175	$^\circ\text{C}$
T_L	Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	300	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typ	Max	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	--	1.2	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient *	--	40	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	--	62.5	$^\circ\text{C}/\text{W}$

* When mounted on the minimum pad size recommended (PCB Mount)

Electrical Characteristics		$T_C = 25^\circ\text{C}$ unless otherwise noted					
Symbol	Parameter	Test Conditions		Min	Typ	Max	Units
Off Characteristics							
BV_{DSS}	Drain-Source Breakdown Voltage	$\text{V}_{\text{GS}} = 0 \text{ V}$, $\text{I}_D = -250 \mu\text{A}$		-100	--	--	V
$\Delta \text{BV}_{\text{DSS}} / \Delta T_J$	Breakdown Voltage Temperature Coefficient	$\text{I}_D = -250 \mu\text{A}$, Referenced to 25°C		--	-0.1	--	$\text{V}/^\circ\text{C}$
I_{DSS}	Zero Gate Voltage Drain Current	$\text{V}_{\text{DS}} = -100 \text{ V}$, $\text{V}_{\text{GS}} = 0 \text{ V}$		--	--	-1	μA
		$\text{V}_{\text{DS}} = -80 \text{ V}$, $T_C = 125^\circ\text{C}$		--	--	-10	μA
I_{GSSF}	Gate-Body Leakage Current, Forward	$\text{V}_{\text{GS}} = -30 \text{ V}$, $\text{V}_{\text{DS}} = 0 \text{ V}$		--	--	-100	nA
I_{GSSR}	Gate-Body Leakage Current, Reverse	$\text{V}_{\text{GS}} = 30 \text{ V}$, $\text{V}_{\text{DS}} = 0 \text{ V}$		--	--	100	nA
On Characteristics							
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	$\text{V}_{\text{DS}} = \text{V}_{\text{GS}}$, $\text{I}_D = -250 \mu\text{A}$		-2.0	--	-4.0	V
$\text{R}_{\text{DS(on)}}$	Static Drain-Source On-Resistance	$\text{V}_{\text{GS}} = -10 \text{ V}$, $\text{I}_D = -11 \text{ A}$		--	0.096	0.125	Ω
g_{FS}	Forward Transconductance	$\text{V}_{\text{DS}} = -40 \text{ V}$, $\text{I}_D = -11 \text{ A}$	(Note 4)	--	13.5	--	S
Dynamic Characteristics							
C_{iss}	Input Capacitance	$\text{V}_{\text{DS}} = -25 \text{ V}$, $\text{V}_{\text{GS}} = 0 \text{ V}$, $f = 1.0 \text{ MHz}$		--	1170	1500	pF
C_{oss}	Output Capacitance			--	460	600	pF
C_{rss}	Reverse Transfer Capacitance			--	160	200	pF
Switching Characteristics							
$t_{\text{d(on)}}$	Turn-On Delay Time	$\text{V}_{\text{DD}} = -50 \text{ V}$, $\text{I}_D = -22 \text{ A}$, $\text{R}_G = 25 \Omega$		--	17	45	ns
t_r	Turn-On Rise Time			--	170	350	ns
$t_{\text{d(off)}}$	Turn-Off Delay Time			--	60	130	ns
t_f	Turn-Off Fall Time			--	110	230	ns
Q_g	Total Gate Charge			--	40	50	nC
Q_{gs}	Gate-Source Charge	$\text{V}_{\text{DS}} = -80 \text{ V}$, $\text{I}_D = -22 \text{ A}$, $\text{V}_{\text{GS}} = -10 \text{ V}$		--	7.0	--	nC
Q_{gd}	Gate-Drain Charge			--	21	--	nC
Drain-Source Diode Characteristics and Maximum Ratings							
I_S	Maximum Continuous Drain-Source Diode Forward Current			--	--	-22	A
I_{SM}	Maximum Pulsed Drain-Source Diode Forward Current			--	--	-88	A
V_{SD}	Drain-Source Diode Forward Voltage	$\text{V}_{\text{GS}} = 0 \text{ V}$, $\text{I}_S = -22 \text{ A}$		--	--	-4.0	V
t_{rr}	Reverse Recovery Time	$\text{V}_{\text{GS}} = 0 \text{ V}$, $\text{I}_S = -22 \text{ A}$, $d\text{I}_F / dt = 100 \text{ A}/\mu\text{s}$		--	110	--	ns
Q_{rr}	Reverse Recovery Charge			--	0.6	--	μC

Notes:

1. Repetitive Rating : Pulse width limited by maximum junction temperature
2. $L = 2.2\text{mH}$, $\text{I}_{AS} = -22\text{A}$, $\text{V}_{DD} = -25\text{V}$, $\text{R}_G = 25 \Omega$, Starting $T_J = 25^\circ\text{C}$
3. $\text{I}_{SD} \leq -22\text{A}$, $d\text{I}/dt \leq 300\text{A}/\mu\text{s}$, $\text{V}_{DD} \leq \text{BV}_{\text{DSS}}$, Starting $T_J = 25^\circ\text{C}$
4. Pulse Test : Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$
5. Essentially independent of operating temperature

Typical Characteristics




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance Variation vs. Drain Current and Gate Voltage




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics

Typical Characteristics (Continued)




Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 8. On-Resistance Variation vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature






Figure 11. Transient Thermal Response Curve


Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching Test Circuit & Waveforms




Peak Diode Recovery dv/dt Test Circuit & Waveforms



Package Dimensions

D²-PAK



ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative