

Description: 2520 Triplexer

PART NUMBER: TPX2520LKTBR0914A

# **Features:**

## Compact Size

# **Applications:**

• For LTE/NR application

- Low loss
- High Soldering Heat Resistance

# **ELECTRICAL SPECIFICATIONS**

Low-Band				
Item	Frequency Range (MHz)	Min.	Тур.	Max.
Insertion loss (dB)	698~960	-	0.62	0.8
Return loss (dB)	698~960	10	16.4	-
	1452~1496	12	14.8	-
	1565~1606	15	23.0	-
	1710~2170	17	20.3	-
Attenuation(dB)	2496~2690	30	46.7	-
	3300~4200	30	45.7	-
	4400~5000	30	48.4	-
	4900~5850	30	47.7	-

#### **Middle-band**

Item	Frequency Range (MHz)	Min.	Тур.	Max.
Incortion loss (dP)	1452~1496	-	1.85	2.3
Insertion loss (dB)	1710~2170	-	1.49	1.6
Return loss (dB)	1452~2170	10	11.9	-
	698~960	21	24.6	-
	2496~2690	17	23.6	-
Attonuction(dP)	3300~3800	15	21.6	-
Attenuation(dB)	3800~4200	20	27.4	-
	4400~5000	20	35.3	-
	4900~5850	20	32.5	-

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100

Downloaded from Arrow.com.

Pulse/Larsen Antennas 18110 SE 34<sup>th</sup> St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4<sup>th</sup> Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998





# Description: 2520 Triplexer

## PART NUMBER: TPX2520LKTBR0914A

# ELECTRICAL SPECIFICATIONS

ign-Band				
Item	Frequency Range (MHz)	Min.	Тур.	Max.
	2496~2690	-	1.22	1.55
Incortion loss (dP)	3300~4200	-	0.59	1.0
Insertion loss (dB)	4400~5000	-	0.65	1.0
	4900~5850	-	0.58	1.0
Return loss (dB)	2496~5850	10	12.2	-
	698~960	23	34.9	-
Attenuation(dB)	1452~1496	30	35.7	-
	1710~2170	16	23.9	-

#### Common

Ilah Dand

Item	Frequency Range (MHz)	Min.	Тур.	Max.
	698~960	10	16.3	-
Return loss (dB)	1452~2170	10	12.8	-
	2496~5850	10	12.0	-

#### **Isolation**

ltem	Frequency Range (MHz)	Min.	Тур.	Max.
	698~960	21	24.2	-
Low to Middle band (dB)	1452~1496	12	18.4	-
	1710~2170	17	21.1	-
	1452~1496	30	33.1	-
Middle to High band (dB)	1710~2170	16	26.4	-
	2496~2690	17	21.6	-
Low to High bond (dP)	698~960	28	34.2	-
Low to High band (dB)	2496~2690	35	50	-

Operating Temperature Range : -40~85°C

Power Capacity : 3W max.

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION



2



# Description: 2520 Triplexer

## PART NUMBER: TPX2520LKTBR0914A

#### **MECHANICAL DIMENSION** Outline Dimension L W Т а 2.50±0.15 0.40±0.10 2.00±0.15 0.65max. b d С е (7) (6) (5) $0.55 \pm 0.10$ $0.30 \pm 0.10$ $0.40 \pm 0.10$ $0.90 \pm 0.15$ (9) (4) w i(8) NOTE : Dimensions in mm. (2) (1) (3) **Termination Terminal name** Dimension Т L 1 High band 2 GND **Top View** 3 Middle band (7)(6) (5) 4 GND 5 Low band 1(8 (9) (4) 6 GND с 7 Common (2) (3) 8 GND b 9 GND **Reference design of EVB**



Unit : mm

Line width should be designed to match 50 characteristic impedance, depending on PCB material and thickness.

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



3



# Description: 2520 Triplexer

## PART NUMBER: TPX2520LKTBR0914A

# **MEASURING DIAGRAM**



Test Instrument : Agilent E5071C Network Analyzer or equivalent.

## **ELECTRICAL PERFORMANCES**



In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



4



# Description: 2520 Triplexer

## PART NUMBER: TPX2520LKTBR0914A

# **PACKING SPECIFICATION**

#### Peel-off force





The force for peeling of cover tape is 10 grams in the arrow direction.

### **Dimension (Unit: mm)**



ТҮРЕ	A	В	С	D	E	F
8 mm	178±1	60+0.5 -0	-	13±0.2	9±0.5	12±0.5
12 mm	178±0.3	60±0.2	19.3±0.1	13.5±0.1	13.6±0.1	-

5

RóHS

### **Taping quantity**

SERIES	5824 5724	5320 5220	4532	4516	3225	3216 2520	2012 1608	1005 0605
PCS/Reel	5000	3000	1000	2000	2500	3000	4000	10000



P= 4 mm

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

Е



Description: 2520 Triplexer

## PART NUMBER: TPX2520LKTBR0914A

		<b>REVISION HISTORY</b>	
Revision	Date	Description	
Version 1	Apr. 13, 2022	- New issue	

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



6