

Part Number: <u>1202550002</u>

**Product Description :** Contrinex Reflector for Photoelectric Sensors, 46.5mm Diameter, Self-

adhesive, Standard Type **Series Number:** 120255

Status: Not Recommended For New Design Product Category: Sensor Accessories Engineering Number: LXR-0000-046



### **Documents & Resources**

## **Specifications**

1202550001-000.pdf

1202550002-000.pdf

# **Product Environment Compliance**

# Compliance

| GADSL/IMDS         | Not Relevant                                    |
|--------------------|---|
| China RoHS         | ⊚<br>per SJ/T 11365-2006                        |
| EU ELV             | Not Relevant                                    |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                 |
| REACH SVHC         | Not Contained per D(2022)4187-DC (10 June 2022) |
| EU RoHS            | Compliant per EU 2015/863                       |

### **Compliance Statements**

- EU RoHS
- REACH SVHC
- Low-Halogen

## **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## **Substances of Interest**

PFAS

**EU RoHS Certificate of Compliance** 

**Additional Product Compliance Information** 

**UKCA - Declaration of Conformity** 

CE - Declaration of Conformity

## **Part Details**

### General

| Status       | Not Recommended For New Design  |
|--------------|---|
| Category     | Accessories   |
| Series       | 120255  |
| Description  | Contrinex Reflector for<br>Photoelectric Sensors, 46.5mm<br>Diameter, Self-adhesive, Standard<br>Type |
| IP Rating    | IP67  |
| Product Name | Contrinex   |
| Туре         | Photoelectric, Standard   |
| UPC          | 191130069361  |

# **Physical**

| Accessory Type                | Reflector     |
|-------------------------------|---------------|
| Material - Reflector          | PMMA          |
| Net Weight                    | 444.000/g     |
| Reflector Size                | 46.5mm dia.   |
| Self-Adhesive                 | Yes           |
| Temperature Range - Operating | -40° to +70°C |

This document was generated on Sep 16, 2025