

microSD/TF Card Connector

FCN-560 Series

RoHS compliant

microSD is currently the world's smallest memory card storage system, specifically designed for use with ultra-small mobile phones and other devices. Like the miniSD, the microSD/TransFlash is ideal for use in storing media-rich files such as music, videos, and photographs in compatible mobile phones.

Fujitsu's microSD connector offers the lowest profile height (1.65mm) currently available in the market.

Featuring Fujitsu's precise and insert molding technology, the FCN-560 series micro SD connector measures 15mm (D) x 14mm (W) x 1.6mm (H) and has a life cycle of ten thousand insertions/withdrawals.

Fujitsu's connector uses a proprietary push-push structure that provides positive tactile feedback during card insertion and withdrawal.

A card drop protection mechanism prevents the card from falling out during pre-insertion and forced card extraction after it's locked in. When ejected, the card travels 3.5mm from its locked position.

	The state of	4	10	THE REAL PROPERTY.
	a contract		5	Contract of the Contract of th
l FEA	TURES		Marie Constitution of the	

- Reduction in seize and weight (15 (D) x 14 (W) x 1.65 (H)mm) with unique push-push structure
- Half-lock to prevent forced card extraction, good operability with sense of click for insertion
- Smooth card inserion/withdrawl with unique drop-protection mechanism
- With card detections switch
- Card ejection distance 3.5mm
- FCN-568Z008-G/0M


Item	Specification	
Operating temperature	-20°C to +70°C	
range		
Current rating	AC 0.5A	
Voltage rating	AC/DC 5V	
Contact resistance	100mΩ maximum	
Dielectric withstanding	AC 500V for 1 minute	
voltage		
Insertion/Withdrawl life	10,000 cycles	

Tape and	reel:	1, 500	pcs/reel
----------	-------	--------	----------

Item	Specification	
Insulating material	LCP, UL94 V-0	
Contact	Copper Alloy Plating NiPdAu	
Pin / Spring	SWPA	
Metal Cover	Stainless steel	


microSD/TF Card Connector

SPECIFICATIONS



microSD/TF Card Connector

SPECIFICATIONS



Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited Gotanda-Chuo Building

3-5, Higashigotanda 2-chome, Shinagawa-ku

Tokyo 141 8630, Japan Tel: (81-3) 5449-7010 Fax: (81-3) 5449-2626 Email: promothq@fcl.fujitsu.com Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc. 250 E. Caribbean Drive Sunnyvale, CA 94089 U.S.A. Tel: (1-408) 745-4900

Fax: (1-408) 745-4970 Email: components@us.fujitsu.com Web: http://us.fujitsu.com/components/

Europe

Fujitsu Components Europe B.V. Diamantlaan 25

2132 WV Hoofddorp Netherlands Tel: (31-23) 5560910 Fax: (31-23) 5560950 Email: info@fceu.fujitsu.com Web: emea.fujitsu.com/components/

Asia Pacific

Fujitsu Components Asia Ltd. 102E Pasir Panjang Road #01-01 Citilink Warehouse Complex Singapore 118529

Tel: (65) 6375-8560 Fax: (65) 6273-3021 Email: fcal@fcal.fujitsu.com

Web: http://www.fujitsu.com/sg/services/micro/components/

©2010 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice. Rev. August 11, 2010.