

MLG0402Q3N5ST000



Applications	Commercial Grade
Feature	MultilayerMultilayer Non-Mag CoreNon-Magnetic Core (Dielectric Ceramic) High QHigh Q
Series Type	MLG-Q
Status	Production
Brand	TDK



Size	
Length(L)	0.40mm ±0.02mm
Width(W)	0.20mm ±0.02mm
Thickness Height	0.20mm ±0.02mm
Recommended Land Pattern (A)	0.15mm to 0.20mm
Recommended Land Pattern (B)	0.20mm Nom.
Recommended Land Pattern (C)	0.18mm to 0.20mm

Electrical Characteristics	
Inductance	3.5nH ±0.3nH at 100MHz
Rated Current	180mA
DC Resistance [Typ.]	740mΩ
DC Resistance [Max.]	1.1Ω
Self Resonant Frequency [Min.]	6GHz
Self Resonant Frequency [Typ.]	9GHz
Q [Min.]	2 at 100MHz
Q [Typ.]	3 at 100MHz





Other	
Operating Temp. Range	-55 to 125°C
Soldering Method	Reflow
AEC-Q200	NO
Packing	Punched (Paper)Taping [180mm Reel, Tape width 8mm]
Package Quantity	20000pcs
Weight	0.00007g

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

MLG0402Q3N5ST000



Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)





Associated Images

