

## Features

- Peak pulse power:
  - 600 W (10/1000  $\mu$ s)
  - 4 kW (8/20  $\mu$ s)
- Stand-off voltage 213 V
- Bidirectional type
- Low leakage current:
  - 200 nA at 25 °C
  - 1  $\mu$ A at 85 °C
- Operating  $T_j$  max: 175 °C
- High power capability at  $T_j$  max
- JEDEC registered package outline
- Resin meets UL 94, V0
- AEC-Q101 qualified

## Complies with the following standards

- IEC 61000-4-2 exceeds level 4:
  - 30 kV (air discharge)
  - 30 kV (contact discharge)
- ISO 10605, C = 330 pF, R = 330  $\Omega$  exceeds level 4:
  - 30 kV (air discharge)
  - 30 kV (contact discharge)
- ISO 7637-2

## Description

The SM6T250CAY Transil series has been designed to protect sensitive automotive circuits against surges defined in ISO 7637-2 and against electrostatic discharges according to IEC 61000-4-2 and ISO 10605.

The planar technology makes this device compatible with high-end circuits where low leakage current and high junction temperature are required to provide reliability and stability over time. SM6T250CAY is packaged in SMB (SMB footprint in accordance with IPC 7531 standard).

**TM:** Transil is a trademark of STMicroelectronics

# 1 Characteristics

Table 1. Absolute maximum ratings ( $T_{amb} = 25^\circ C$ )

Symbol	Parameter		Value	Unit
$V_{PP}$	Peak pulse voltage	ISO 10605 ( $C = 330 \text{ pF}$ , $R = 330 \Omega$ ): Contact discharge Air discharge IEC61000-4-2: Contact discharge Air discharge	30 30 30 30	kV
$P_{PP}$	Peak pulse power dissipation <sup>(1)</sup>	$T_j$ initial = $T_{amb}$	600	W
$T_j$	Operating junction temperature range		-55 to 175	°C
$T_{stg}$	Storage temperature range		-65 to 175	°C
$T_L$	Maximum lead temperature for soldering during 10 s.		260	°C

1. For a surge greater than the maximum values, the diode will fail in short-circuit.

Figure 1. Electrical characteristics - definitions




Figure 2. Pulse definition for electrical characteristics




Table 2. Electrical characteristics, parameter values ( $T_{amb} = 25^{\circ}C$ )

Order code	I <sub>RM</sub> max at V <sub>RM</sub>			V <sub>BR</sub> at I <sub>R</sub> <sup>(1)</sup>			V <sub>CL</sub> at I <sub>PP</sub> 10/1000 $\mu$ s		R <sub>D</sub> <sup>(2)</sup> 10/100 $\mu$ s		V <sub>CL</sub> at I <sub>PP</sub> 8/20 $\mu$ s		R <sub>D</sub> <sup>(2)</sup> 8/20 $\mu$ s		$\alpha T$
	25	85		min.	typ.	max.		max.			max.				max.
	°C														
	nA	$\mu$ A	V	V			mA	V <sup>(3)</sup>	A	$\Omega$	V <sup>(3)</sup>	A	$\Omega$	10-4/ $^{\circ}$ C	
SM6T250CAY	200	1	213	237	250	263	1	344	1.75	53.7	400	10	15	11	

1. Pulse test:  $t_p < 50$  ms

2. To calculate maximum clamping voltage at another surge level, use the following formula:



$$V_{CLmax} = V_{CL} - R_D \times (I_{PP} - I_{PPapp}) \text{ where } I_{PPapp} \text{ is the surge current in the application.}$$



3. To calculate V<sub>BR</sub> or V<sub>CL</sub> versus junction temperature, use the following formulas:

$$V_{BR} @ T_J = V_{BR} @ 25^{\circ}C \times (1 + \alpha T \times (T_J - 25))$$


$$V_{CL} @ T_J = V_{CL} @ 25^{\circ}C \times (1 + \alpha T \times (T_J - 25))$$

Figure 3. Peak power dissipation versus initial junction temperature


Figure 4. Peak pulse power versus exponential pulse duration ( $T_j$  initial = 25 °C)

**Figure 5. Clamping voltage versus peak pulse current exponential waveform (maximum values)****Figure 6. Junction capacitance versus reverse applied (typical values)**


**Figure 7. Relative variation of thermal impedance, junction to ambient, versus pulse duration**



**Figure 8. Thermal resistance junction to ambient versus copper surface under each lead**



**Figure 9. Leakage current versus junction temperature (typical values)**



## 2 Application and design guidelines

More information is available in the ST Application note AN2689 "Protection of automotive electronics from electrical hazards, guidelines for design and component selection".

## 3 Packaging information

- Case: JEDEC DO-214AA molded plastic over planar junction
- Terminals: solder plated, solderable as per MIL-STD-750, Method 2026
- Polarity: for unidirectional types the band indicates cathode
- Epoxy meets UL94, V0
- Lead-free package

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

Figure 10. SMB outline (definitions)






Table 3. SMB dimensions (values)

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.40	0.006	0.016
D	3.30	3.95	0.130	0.156
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
L	0.75	1.50	0.030	0.059

Figure 11. SMB footprint dimensions in mm (inches)

Figure 12. Marking layout<sup>(1)</sup>

1. Marking layout can vary according to assembly location.

## 4 Ordering information

Figure 13. Ordering information scheme




Table 4. Ordering information

Order code	Marking	Weight	Base qty.	Delivery mode
SM6T250CAY	PRY	0.11 g	2500	Tape and reel

## 5 Revision history

Table 5. Document revision history

Date	Revision	Changes
19-Mar-2015	1	Initial release.
09-Apr-2015	2	Updated <a href="#">Figure 7</a> .

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2015 STMicroelectronics – All rights reserved

