
SPECIFICATION CONTROL DRAWING



MATERIALS

1. INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
2. SOLDER PREFORM WITH FLUX:
   SOLDER: TYPE Sn63 per ANSI J-STD-006.
   FLUX: TYPE ROL1 per ANSI-J-STD-004.

APPLICATION

1. This part is designed for use in terminating the shield of a miniature coaxial cable having tin or silver plated shields.
2. Sleeve will recover to 0.76 (0.30) max. I.D.

Raychem Interconnect a division of tyco ELECTRONICS 300 Constitution Drive Menlo Park, CA 94025, USA		THERMOFIT DEVICES	TITLE: **SOLDERSLEEVE SHIELD TERMINATOR**				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.			DOCUMENT NO.: **D-110-0074**				
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	Raychem reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.	DCR NUMBER: D990726		REPLACES: N/A		
DRAWN BY: M. FORONDA	DATE: 06-July-00	PROD. REV. B	DOC. ISSUE: 1	SCALE: None	SIZE: A	SHEET: 1 of 1	

If this document is printed it becomes uncontrolled. Check for the latest revision

Downloaded from Arrow.com.