

Part Number: 836119006

Product Description: 1.27mm Pitch Commercial Micro-D, PCB Mount, Right-Angle

Plug, 9 Circuits

Series Number: 83611

**Status:** Active

**Product Category: I/O Connectors** 



#### **Documents & Resources**

### **Drawings**

836119006\_sd.pdf PK-83098-636-001.pdf

#### 3D Models and Design Files

836119006\_stp.zip

### **Specifications**

PS-83421-001-001.pdf

# **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	•
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

# Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

# **Part Details**

#### General

Status	Active
Category	I/O Connectors
Series	83611
Description	1.27mm Pitch Commercial Micro-D, PCB Mount, Right-Angle Plug, 9 Circuits
Application	Wire-to-Board
Comments	Pin Contact
Component Type	Plug
Product Name	Commercial Micro-D
Type	N/A
UPC	800754026239

# Agency

UL	E152602
----	---------

## Electrical

Current - Maximum per Contact	1.0A
Shielded	Yes
Voltage - Maximum	350V AC

# Physical

Circuits (Loaded)	9
Circuits (maximum)	9
Durability (mating cycles max)	500
Lock to Mating Part	Yes
Material - Plating Mating	Gold
Net Weight	4.479/g
Orientation	Right Angle

Packaging Type	Tube
Panel Mount	Yes
PC Tail Length	2.79mm
PCB Retention	Yes
PCB Thickness - Recommended	1.52mm
Pitch - Mating Interface	1.27mm
Plating min - Mating	0.381µm
Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +125°C
Termination Interface Style	Through Hole
Wire Size (AWG)	N/A

#### **Solder Process Data**

Max-Duration	30
Lead-Free Process Capability	WAVE

## Mates With / Use With

# Mates with Part(s)

Description	Part Number
Commercial Micro-D Cable Receptacle Kits and Cable Assemblies	<u>83421</u>

This document was generated on Mar 14, 2025