ON Semiconductor

Is Now

To learn more about onsemi™, please visit our website at
www.onsemi.com

onsemi and onsemi and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.

Downloaded from Arrow.com.

ON Semiconductor®

FGA25S125P
1250 V, 25 A Shorted-anode IGBT

Features

- High Speed Switching
- Low Saturation Voltage: $V_{CE(sat)}$ = 1.8 V @ I_C = 25 A
- High Input Impedance
- RoHS Compliant

Applications

- Induction Heating, Microwave Oven

General Description

Using advanced field stop trench and shorted-anode technology, ON Semiconductor's shorted-anode trench IGBTs offer superior con-duction and switching performances for soft switching applications. The device can operate in parallel configuration with exceptional avalanche capability . This device is designed for induction heating and microwave oven.



TO-3PN



Absolute Maximum Ratings

Symbol	Description		FGA25S125P-SN00337	Unit
V_{CES}	Collector to Emitter Voltage		1250	V
V_{GES}	Gate to Emitter Voltage		± 25	V
I_C	Collector Current	@ T_C = 25°C	50	A
	Collector Current	@ T_C = 100°C	25	A
$I_{CM\ (1)}$	Pulsed Collector Current		75	A
I_F	Diode Continuous Forward Current	@ T_C = 25°C	50	A
	Diode Continuous Forward Current	@ T_C = 100°C	25	A
P_D	Maximum Power Dissipation	@ T_C = 25°C	250	W
	Maximum Power Dissipation	@ T_C = 100°C	125	W
T_J	Operating Junction Temperature		-55 to +175	°C
T_{stg}	Storage Temperature Range		-55 to +175	°C
T_L	Maximum Lead Temp. for soldering Purposes, 1/8” from case for 5 seconds		300	°C

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JC}$(IGBT)	Thermal Resistance, Junction to Case, Max	-	0.6	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient, Max	-	40	°C/W

Notes:

1: Limited by Tjmax

©2012 Semiconductor Components Industries, LLC.
October-2017,Rev. 2

Publication Order Number:
FGA25S125P/D

Downloaded from Arrow.com.

Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
FGA25S125P	FGA25S125P -SN00337	TO-3PN	-	-	30

Electrical Characteristics of the IGBT T_C = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
BV_{CES}	Collector to Emitter Breakdown Voltage	V_{GE} = 0 V, I_C = 1 mA	1250	-	-	V
$\frac{\Delta BV_{CES}}{\Delta T_J}$	Temperature Coefficient of Breakdown Voltage	V_{GE} = 0 V, I_C = 1 mA	-	1.2	-	V/^{o}C
I_{CES}	Collector Cut-Off Current	V_{CE} = 1250V, V_{GE} = 0V	-	-	1	mA
I_{GES}	G-E Leakage Current	V_{GE} = V_{GES}, V_{CE} = 0V	-	-	±500	nA
On Characteristics						
$V_{GE(th)}$	G-E Threshold Voltage	I_C = 25mA, V_{CE} = V_{GE}	4.5	6.0	7.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	I_C = 25A, V_{GE} = 15V T_C = 25°C	-	1.8	2.35	V
		I_C = 25A, V_{GE} = 15V T_C = 125°C	-	2.05	-	V
		I_C = 25A, V_{GE} = 15V, T_C = 175°C	-	2.16	-	V
V_{FM}	Diode Forward Voltage	I_F = 25A, T_C = 25°C	-	1.7	2.4	V
		I_F = 25A, T_C = 175°C	-	2.1	-	V
Dynamic Characteristics						
C_{ies}	Input Capacitance	V_{CE} = 30V, V_{GE} = 0V, f = 1MHz	-	2150	-	pF
C_{oes}	Output Capacitance		-	48	-	pF
C_{res}	Reverse Transfer Capacitance		-	36	-	pF
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 600V, I_C = 25A, R_G = 10Ω, V_{GE} = 15V, Resistive Load, T_C = 25°C	-	24	-	ns
t_r	Rise Time		-	250	-	ns
$t_{d(off)}$	Turn-Off Delay Time		-	502	-	ns
t_f	Fall Time		-	138	-	ns
E_{on}	Turn-On Switching Loss		-	1085	-	uJ
E_{off}	Turn-Off Switching Loss		-	580	-	uJ
E_{ts}	Total Switching Loss		-	1665	-	uJ
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 600V, I_C = 25A, R_G = 10Ω, V_{GE} = 15V, Resistive Load,, T_C = 175°C	-	21.2	-	ns
t_r	Rise Time		-	304	-	ns
$t_{d(off)}$	Turn-Off Delay Time		-	490	-	ns
t_f	Fall Time		-	232	-	ns
E_{on}	Turn-On Switching Loss		-	1310	-	uJ
E_{off}	Turn-Off Switching Loss		-	952	-	uJ
E_{ts}	Total Switching Loss		-	2262	-	uJ
Q_g	Total Gate Charge	V_{CE} = 600V, I_C = 25A, V_{GE} = 15V	-	204	-	nC
Q_{ge}	Gate to Emitter Charge		-	15	-	nC
Q_{gc}	Gate to Collector Charge		-	103	-	nC

Downloaded from Arrow.com.

Typical Performance Characteristics

Figure 1. Typical Output Characteristics



Figure 2. Typical Output Characteristics



Figure 3. Typical Saturation Voltage Characteristics



Figure 4. Transfer Characteristics



Figure 5. Saturation Voltage vs. Case Temperature at Variant Current Level



Figure 6. Saturation Voltage vs. V_{GE}



Downloaded from Arrow.com.

Typical Performance Characteristics

Figure 7. Saturation Voltage vs. V_{GE}



Figure 8. Capacitance Characteristics



Figure 9. Gate charge Characteristics



Figure 10. SOA Characteristics



Figure 11. Turn-on Characteristics vs. Gate Resistance



Figure 12. Turn-off Characteristics vs. Gate Resistance



Downloaded from Arrow.com.

Typical Performance Characteristics

Figure 13. Turn-on Characteristics vs. Collector Current



Figure 14. Turn-off Characteristics vs. Collector Current



Figure 15. Switching Loss vs. Gate Resistance



Figure 16. Switching Loss vs. Collector Current



Figure 17. Turn off Switching SOA Characteristics



Figure 18. Forward Characteristics



Downloaded from Arrow.com.

Typical Performance Characteristics

Figure 19. Transient Thermal Impedance of IGBT



Downloaded from Arrow.com.

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

Downloaded from Arrow.com.