SURFACE MOUNT SILICON ULTRA LOW CAPACITANCE TRANSIENT VOLTAGE SUPPRESSORS



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CSL05 (Single) and CSL05D (Dual) types are ultra low capacitance transient voltage suppressors packaged in the SOT-23 surface mount package. These devices provide excellent protection from spurious voltage transients. The very low capacitance reduces insertion loss to minimizes the affect on the data line through-put. Typical applications include: mobile phones, digital cameras, USB ports, MP3 players, and Ethernet port protection.



SOT-23 CASE

MARKING CODES: CSL05 (Single):CL05 CSL05D (Dual): CL5D

| MAXIMUM RATINGS: (T _A =25°C) | SYMBOL | | UNITS |
|--|------------------|-------------|-------|
| Peak Power Dissipation (8x20µs) | P_{PK} | 400 | W |
| Peak Pulse Current (8x20µs) | I_{PP} | 17 | Α |
| Electrical Fast Transient (IEC 61000-4-4) (5x50ns) | EFT | 40 | Α |
| ESD Voltage (IEC 61000-4-2, Air) | V_{ESD} | 25 | kV |
| ESD Voltage (IEC 61000-4-2, Contact) | V_{ESD} | 25 | kV |
| Operating Junction Temperature | T_J | -50 to +125 | °C |
| Storage Temperature | T _{stg} | -50 to +150 | °C |

ELECTRICAL CHARACTERISTICS PER TVS: (T_A=25°C unless otherwise noted)

| Maximum Reverse Stand-off Voltage VRWM | Minimum Breakdown Voltage VBR @ IT | Test Current | Maximum Reverse Leakage Current I _R @ V _{RWM} | Clam Voli (8x2 | mum nping tage 0µs) ② Ipp | TLP Cla Volt (Not | ical amping tage te 1) | Typical Dynamic Resistance (Note 1) RDYN | Maximum Junction Capacitance @ 0V Bias CJ |
|--|---|-----------------|---|----------------------|---------------------------------------|-------------------------|---------------------------------|--|---|
| V | v | mA | μΑ | V | Α | v | Α | Ω | pF |
| 5.0 | 6.0 | 1.0 | 5.0 | 9.5 | 1.0 | 10 | 4.5 | 0.57 | 1.2 |
| 5.0 0.0 1.0 5.0 | 5.0 | 12 | 5.0 | 15 | 13.3 | 0.57 | 1.2 | | |


Note 1: Transmission Line Pulse (TLP) conditions: Z_0 =50 Ω , tp=100ns


R3 (15-October 2015)

SURFACE MOUNT SILICON ULTRA LOW CAPACITANCE TRANSIENT VOLTAGE SUPPRESSORS



SOT-23 CASE - MECHANICAL OUTLINE







| DIMENSIONS | | | | | |
|------------|-------|-------|-------------|------|--|
| | INC | HES | MILLIMETERS | | |
| SYMBOL | MIN | MAX | MIN | MAX | |
| Α | 0.003 | 0.007 | 0.08 | 0.18 | |
| В | 0.006 | - | 0.15 | - | |
| С | - | 0.005 | - | 0.13 | |
| D | 0.035 | 0.043 | 0.89 | 1.09 | |
| Е | 0.110 | 0.120 | 2.80 | 3.05 | |
| F | 0.075 | | 1.90 | | |
| G | 0.037 | | 0.95 | | |
| Н | 0.047 | 0.055 | 1.19 | 1.40 | |
| İ | 0.083 | 0.098 | 2.10 | 2.49 | |
| J | 0.014 | 0.020 | 0.35 | 0.50 | |

SOT-23 (REV: R3)

PIN CONFIGURATIONS





CSL05

LEAD CODE:

- 1) Cathode D2
- 2) Cathode D1
- 3) No Connection

MARKING CODE: CL05

CSL05D

LEAD CODE:

- 1) Cathode D2
- 2) Cathode D1
- 3) Cathode D3, D4

MARKING CODE: CL5D


R3 (15-October 2015)


www.centralsemi.com


SURFACE MOUNT SILICON ULTRA LOW CAPACITANCE TRANSIENT VOLTAGE SUPPRESSORS




TYPICAL ELECTRICAL CHARACTERISTICS










R3 (15-October 2015)


www.centralsemi.com


SURFACE MOUNT SILICON ULTRA LOW CAPACITANCE TRANSIENT VOLTAGE SUPPRESSORS



TYPICAL ELECTRICAL CHARACTERISTICS







R3 (15-October 2015)

www.centralsemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms



Product End of Life Notification

| PDN ID: | PDN01065 |
|--------------------|----------|
| Notification Date: | 6/02/17 |
| Last Buy Date: | N/A |
| Last Shipment Date | N/A |

Please be advised that Central Semiconductor must immediately discontinue the product(s) listed in the attached PDN notice. We are unable to accept any further orders for these products <u>unless</u> we have available inventory on hand.

You may have purchased one or more of the products listed. Please do not hesitate to contact your local Central Semiconductor sales representative with any questions or needs you may have. Central regrets any inconvenience this may cause.

Sincerely,

Central Semiconductor Corp.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



Product End of Life Notification

| PDN ID: | PDN01065 |
|--------------------|----------|
| Notification Date: | 6/02/17 |
| Last Buy Date: | N/A |
| Last Shipment Date | N/A |

Summary: The CSL05 and CSL05D low capacitance Transient Voltage Suppressors have been discontinued and are now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

| Central Part Number | Replacement |
|---------------------|-------------|
| CSL05 BK | N/A |
| CSL05 TR | N/A |
| CSL05D BK | N/A |
| CSL05D TR | N/A |

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002