

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: 8329TFS-B

- **Other Means of Identification:** Thermally Conductive Epoxy Adhesive (Part B)
- **Related Part Number:** 8329TFS-Part B, 8329TFS-25ML (B), 8329TFS-50ML (B), MC002977 (B)
- **UFI:** AKF0-W0YN-A007-U5HD

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

- **Application of the substance / the mixture** Thermally conductive adhesive hardener
- **Uses advised against** Not for use as a spray coating

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

MG Chemicals Ltd. (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 905-331-1396
info@mgchemicals.com

MG Chemicals
Heame House, 23 Bliston Street
Sedgely Dudley DY3 1JA.
United Kingdom
+(44) 1663 362888

MG Chemicalst Ltd.
18-20, Msida Road,
Gzira, GZR 1401
MALTA

- **Further information obtainable from:** sds@mgchemicals.com

· 1.4 Emergency telephone number:

3E (Access code: 335388)
+(44) 20 3514787
+(1) 760 476 3961
UK Toll free: +(0) 800 680 0425

Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

- | | |
|-------------------|--|
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Eye Dam. 1 | H318 Causes serious eye damage. |
| Skin Sens. 1 | H317 May cause an allergic skin reaction. |
| Aquatic Chronic 1 | H410 Very toxic to aquatic life with long lasting effects. |

(Contd. on page 2)

— GB —

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07 GHS09

Signal word Danger

Hazard-determining components of labelling:

fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines
3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine
triethylenetetramine

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor.
P333+P313 If skin irritation or rash occurs: Get medical advice.
P501 Dispose of contents and container in accordance with local, regional, and national regulations.

2.3 Other hazards

Long term exposure to silver powder or compounds can lead to an irreversible blue-grey discoloration of the skin.

Results of PBT and vPvB assessment

- **PBT:** Not applicable
- **vPvB:** Not applicable


• **Determination of endocrine-disrupting properties** Endocrine Disruptor substance $\geq 0.1\%$ = none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1344-28-1 EINECS: 215-691-6	aluminium oxide substance with a Community workplace exposure limit	39.0%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7	zinc oxide  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	25.0%

(Contd. on page 3)

—GB—

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 2)

CAS: 68541-13-9	fatty acids, c18-unsat, dimer, polymers, w/3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine ⚠ Eye Irrit. 2, H319	18.0%
CAS: 68410-23-1	fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	10.0%
CAS: 4246-51-9	3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine ⚠ Skin Corr. 1B, H314; ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317	3.0%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	0.9%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black ⚠ Carc. 2, H351	0.9%
CAS: 8052-41-3 EINECS: 232-489-3 Index number: 649-345-00-4	Stoddard solvent ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; ⚠ Asp. Tox. 1, H304	0.5%
CAS: 112-24-3 EINECS: 203-950-6 Index number: 612-059-00-5	triethylenetetramine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H312; ⚠ Skin Sens. 1, H317; ⚠ Aquatic Chronic 3, H412	0.1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Remove person to fresh air and keep comfortable for breathing.
If feeling unwell: Call a POISON CENTRE or doctor.

· After skin contact:

Wash with plenty water.
If skin irritation or rash occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.

· After eye contact:

Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a POISON CENTER or doctor.

· After swallowing:

Rinse mouth.
Do NOT induce vomiting.
If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

If exposed to metal fumes, chills and fever-like symptoms may occur 4-12 hours after exposure.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Trade name: 8329TFS-B

(Contd. of page 3)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure.

Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.

Prevent fire-fighting wash from entering waterway or sewer system.

Inhalation of metal fumes may cause metal fever and irritate the respiratory tract.

- **Hazardous combustion products:**

- Carbon Oxides (COx)
- toxic metal fumes
- Nitrogen Oxides (NOx)
- Boron oxides
- Zinc oxides

· 5.3 Advice for firefighters

- **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove or keep away all sources of extreme heat or open flames.

Avoid breathing mist, spray, or vapors.

· 6.2 Environmental precautions:

Avoid release to the environment.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect liquid in a sealable, chemical-resistant container.

Wash residue with a paper towel and place dirty towels in container.

Use soap and water to remove the last traces of residue.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Wear protective gloves and eye protection.

Wash hands and exposed skin thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Collect spillage.

Contaminated work clothing should not be allowed out of the workplace.

Avoid breathing fumes or vapours.

- **Information about fire - and explosion protection:** No special measures required.

(Contd. on page 5)

— GB —

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 4)

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

- **Requirements to be met by storerooms and receptacles:**
Keep in a dry and clean area, away from incompatible substances
- **Information about storage in one common storage facility:** Not required
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 10

· **7.3 Specific end use(s)** See section 1.2

* SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1344-28-1 aluminium oxide	
WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
1333-86-4 Carbon black	
WEL	Short-term value: 7 mg/m ³ Long-term value: 3.5 mg/m ³

· **Additional information:**

The lists valid during the making were used as basis.
Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· **8.2 Exposure controls**

- **Appropriate engineering controls** Keep airborne concentrations below exposure limits.
- **Individual protection measures, such as personal protective equipment**
 - **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
 - **Respiratory protection:**
If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.
Advice should be sought from respiratory protection specialists.
 - **Hand protection**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses or tightly sealed goggles: EN 166

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· Physical state	Liquid
· Form:	Viscous
· Colour:	Grey
· Odour:	Amine-like
· Odour threshold:	Not determined
· Melting point/freezing point:	Undetermined
	Not available
· Boiling point or initial boiling point and boiling range	>145 °C
· Flammability	Non flammable
· Lower and upper explosion limit	
· Lower:	Not applicable
· Upper:	Not applicable
· Flash point:	110 °C
· Auto-ignition temperature:	Not determined
· Decomposition temperature:	Not determined
· pH	Not determined
· Viscosity:	
· Kinematic viscosity at 20 °C	>20.5 mm ² /s
· Dynamic:	Not determined
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined
· Vapour pressure:	Not determined
· Density at 20 °C:	1.96 g/cm ³
· Relative density at 25 °C:	2.83
· Vapour density (air=1):	Not determined
· Particle characteristics	Not applicable.

· **9.2 Other information**

· **9.2.1 Information with regard to physical hazard classes**

Not applicable

· **9.2.2 Other safety characteristics**

· Evaporation rate	Not determined
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.

(Contd. on page 7)

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 6)

· Solvent content:	
· Organic solvents:	0.90 %
· VOC (EC)	0.9 %
	0.90 %
· Solids content:	>68.0 %

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
Reacts exothermically with amines.
Reacts exothermically with ketones, halogenated hydrocarbons, cyanides, nitriles, and epoxides.
- **10.2 Chemical stability** Chemically stable at normal temperatures and pressures.
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Halogenated compounds
Strong oxidizing agents
Strong acids
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products known.
Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
1344-28-1 aluminium oxide		
Oral	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>2 mg/L (mouse)
1314-13-2 zinc oxide		
Oral	LD50	7,950 mg/kg (rat)
4246-51-9 3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine		
Oral	LD50	4,310 mg/kg (rat)
Dermal	LD50	2,510 mg/kg (rabbit)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
Dermal	LD/50	5 g/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/L (rat)
1333-86-4 Carbon black		
Oral	LD50	>15,400 mg/kg (rat)

(Contd. on page 8)

GB

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 7)

Dermal	LD50	>3,000 mg/kg (rabbit)
112-24-3 triethylenetetramine		
Oral	LD50	2,500 mg/kg (rat)
Dermal	LD50	805 mg/kg (rabbit)

- **Primary irritant effect:**
 - **Skin corrosion/irritation** Causes skin irritation.
 - **Serious eye damage/irritation** Causes serious eye damage.
 - **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Summary of Effects and Symptoms by Routes of Exposure**
 - **Eyes:**
redness, serious irritation
eye damage, pain
 - **Skin:**
rash, allergic contact dermatitis
redness, irritation
 - **Inhalation:**
Inhalation of fumes may cause metal fever and irritate the respiratory tract.
The flu-like symptoms of metal fume fever may be delayed, occurring 4–12 hours after exposure.
 - **Swallowed:**
allergic reactions
irritation to the mouth, throat, esophagus, and stomach
see inhalation symptoms
- **Subacute to chronic toxicity:**
 - **Delayed and immediate effects as well as chronic effects from short and long-term exposure**
Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

· 11.2 Information on other hazards

· Endocrine disrupting properties
None of the ingredients is listed.

* SECTION 12: Ecological information

· 12.1 Toxicity

- **Aquatic toxicity:**
Very toxic to aquatic life with long lasting effect.
Avoid release to the environment.
Collect spillage.

1314-13-2 zinc oxide	
LC50	0.042 mg/L (fish)
4246-51-9 3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine	
LC50 96h	>1,000 mg/L (fish)

(Contd. on page 9)

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 8)

1333-86-4 Carbon black	
EC50/ 24 h	>5,600 mg/L (aquatic invertebrates)
EC50/ 72 h	>10,000 mg/L (aquatic algae and cyanobacteria)
EC0/ 3 h	>800 mg/L (microorganisms)
LC50	>1,000 mg/L (fish)
112-24-3 triethylenetetramine	
EC50/ 48 h	24 mg/L (daphnia)
LC50 96h	420 mg/L (guppy)
IC50 72h	2 mg/L (algae)

- **12.2 Persistence and degradability** Not readily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable
 - **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
 - **Additional ecological information:**
 - **General notes:**
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Also poisonous for fish and plankton in water bodies.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation** This material and its container must be disposed of as hazardous waste.

· European waste catalogue	
HP4	Irritant - skin irritation and eye damage
HP13	Sensitising
HP14	Ecotoxic

- **Uncleaned packaging:**
 - **Recommendation:**
Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.
Where possible retain label warnings and SDS and observe all notices pertaining to the product.



— GB —

(Contd. on page 10)

Trade name: 8329TFS-B

(Contd. of page 9)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA 	UN3082
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	<p>NOT REGULATED by Road ADR Special Provision 375 for sizes 5L or less. ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)</p> <p>NOT REGULATED by Sea IMDG according to 2.10.2.7 for sizes of 5L or less. ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)</p> <p>NOT REGULATED by Air IATA Special Provision A197 for sizes 5L or less. Environmentally hazardous substance, liquid, n.o.s. (zinc oxide)</p>
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG 	 <ul style="list-style-type: none"> · Class · Label
	<p>9 Miscellaneous dangerous substances and articles.</p> <p>9</p>
<ul style="list-style-type: none"> · IATA 	 <ul style="list-style-type: none"> · Class · Label
	<p>9 Miscellaneous dangerous substances and articles.</p> <p>9</p>
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA): 	<p>MARINE POLLUTANT</p> <p>ENVIRONMENTALLY HAZARDOUS</p> <p>ENVIRONMENTALLY HAZARDOUS</p> <p>Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	<p>Not applicable</p> <p>90</p> <p>F-A,S-F</p> <p>A</p>
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable

(Contd. on page 11)

GB

Safety data sheet

according to UK REACH

Trade name: 8329TFS-B

(Contd. of page 10)

· Transport/Additional information:	Not Regulated
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ZINC OXIDE), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors (Part 1)
None of the ingredients is listed.
· Regulated poisons (Part 2)
None of the ingredients is listed.
· Reportable explosives precursors (Part 3)
None of the ingredients is listed.
· Reportable poisons (Part 4)
None of the ingredients is listed.

· Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** E1 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.
· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.

(Contd. on page 12)

Safety data sheet

according to UK REACH

Page 12/13

Printing date 26.03.2026

Version number 6.02 (replaces version 6.01)

Revision: 22.04.2025

Trade name: 8329TFS-B

(Contd. of page 11)

<ul style="list-style-type: none"> · Annex II - REPORTABLE EXPLOSIVES PRECURSORS <p>None of the ingredients is listed.</p>
<ul style="list-style-type: none"> · Regulation (EC) No 273/2004 on drug precursors <p>None of the ingredients is listed.</p>
<ul style="list-style-type: none"> · Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors <p>None of the ingredients is listed.</p>

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

<ul style="list-style-type: none"> · Classification according to Regulation (EC) No 1272/2008 	
Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** Regulatory department
- **Contact:** sds@mgchemicals.com
- **Date of previous version:** 22.04.2025
- **Version number of previous version:** 6.01
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 13)

GB

Safety data sheet according to UK REACH

Page 13/13

Printing date 26.03.2026

Version number 6.02 (replaces version 6.01)

Revision: 22.04.2025

Trade name: 8329TFS-B

(Contd. of page 12)

ATE: Acute toxicity estimate values
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**

— GB —