



- ?

[Circuit Board Indicators](#)

?

[Panel Mount Indicators](#)

?

[Solid State Lighting](#)

?

[Traffic Signals](#)

?

[Vehicle Lighting](#)

?

[Rail](#)

?

[Obstruction Lighting](#)

?

[Hazardous Area Lighting](#)

?

[Heliport Lighting](#)

Region:

Product Line:

Circuit Board Indicators

Check stock with our distributors now.

5973225307F

Please note that the stock check**is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Please select a Product Line to search.

Circuit Board Indicators

Part No.:

Text Search:

[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp.
[View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)

menu rendered

Circuit Board Indicators - Surface Mount Indicators	
P/N#	PLCC-2 Single Color
5973225307F	
Description	

Forward Current Continuous	30 mA
Forward Current Pulse	100 mA
Derating	from 40° @ .42mA/°C
Solder Temp	240° for 20 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C
Peak Wave Length	594

RoHS Compliant Product

Operating Characteristics	
LED Position	
Color	
Lamp Type	
LED Type	
Intensity Min (mcd)	
Intensity Typ (mcd)	
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Copyright 2006 Dialight. All rights reserved | [Privacy Policy](#)