

Small Signal Product

Surface Mount Schottky Barrier

FEATURES

- Designed for mounting on small surface
- Extremely thin/leadless package
- Low capacitance
- Low forward voltage drop
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21


0603


MECHANICAL DATA

- Case: 0603
- Terminal: Gold plated, solderable per MIL-STD-750, method 2026
- Polarity : Indicated by cathode band
- Weight : 3 mg (approximately)
- Marking code: B2

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Repetitive Peak Reverse Voltage	V_{RRM}	45	V
DC Reverse Voltage	V_R	40	V
Average Forward Current	I_O	30	mA
Peak Forward Surge Current 8.3 ms Single Half Sine-Wave Superimposed on Rate Load	I_{FSM}	500	mA
Power Dissipation	P_d	150	mW
Forward Voltage @ $I_F=1\text{ mA}$	V_F	0.37	V
Reverse Leakage Current $V_R=30\text{V}$ $V_R=40\text{V}$	I_R	0.5	μA
		1.0	
Typical Capacitance Between Terminals $V_R=1\text{V}$, $f=1.0\text{MHz}$ Reverse Voltage	C_J	1.5	pF
Junction Temperature	T_J	-40 to +125	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-40 to +125	$^{\circ}\text{C}$

Small Signal Product

RATINGS AND CHARACTERISTICS CURVES

($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig.1 Maximum Forward Current Derating Curve




Fig. 2 Typical Reverse Characteristics




Fig. 3 Maximum Non-Repetitive Forward Surge Current




Fig. 4 Typical Junction Capacitance





Fig. 5 Forward Characteristics Curve



Small Signal Product

ORDERING INFORMATION

PART NO.	PACKING CODE	PACKING CODE SUFFIX	PACKAGE	PACKING
TSS0340U	RG	G	0603	4K / 7" Reel


Note: Whole series with green compound

EXAMPLE

EXAMPLE PART NO.	PART NO.	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
TSS0340U RGG	TSS0340U	RG	G	Green compound

PACKAGE OUTLINE DIMENSION

0603



DIM.	Unit (mm)			Unit (inch)		
	Min	Typ.	Max	Min	Typ.	Max
L	1.60	-	1.80	0.063	-	0.071
W	0.80	-	1.00	0.031	-	0.039
T	0.70	-	0.85	0.028	-	0.033
C	-	0.45	-	-	0.018	-
D	-	0.70	-	-	0.028	-

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.