

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of MYRGP120060B21RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=MYRGP120060B21RC

MYRGP120060B21RC

2V to 6V input voltage, 1.2V output voltage up to 0.6A, Buck Converter with 85degC Ta











Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Consumer equipment,Industrial	
	Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
Applications	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	
	Processor [ASIC / FPGA / xPU],Optical	
Recommended	Backbone network,Optical Module,	
Applications	Server,Storage,Switch,Industrial	
	Equipment	



Features

The MYRGP-W/B series is a synchronous step-down mini DC/DC converter which integrates an inductor and a control IC in one tiny package (2.5mm×2.0mm, H=1.0mm).



Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ MYRGP120060B21RC\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=MYRGP120060B21RC

MYRGP120060B21RC



Specifications

Local ANA	0.6A
lout(A)Max	0.6A
Vin(V)	2V to 6V
Vin(V)typ	5V
Vout(V)	1.2V
Vout(V)typ	1.2V
Outputs (#)	1
Efficiency (%)	90%
Switching frequency (kHz)	3000kHz
Size(mm)W	2.0mm
Size(mm)L	2.5mm
Size(mm)T	1.0mm
Operatingtemperature(degC)	-40°C to 85°C
Circuit topology	Buck(Step-down)
Package	SMD
Туре	Modules (integrated components)
Productseries	MYRGP
Product Series Features	Inductor Built-in Step-Down "mini DC/DC" Converters
Brand	Murata

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

