

24V DRIVE, FTP-609 SERIES

ULTRA HIGH SPEED (200mm/s)

3" TYPE MECHANISM (with cutter)

FTP-639MCL064/113/364/393-R

■ OVERVIEW

The FTP-609MCL Series thermal printer (driven by 24VDC) provides ultra-high speed printing (200mm/s) for 3-inch wide paper.

This series is suitable for a variety of applications, such as POS/ ECR, kiosk terminals, ticket machines, label printers, banking machines, measuring devices, medical equipment, etc.

■ HIGHLIGHTS

- **Ultra high speed printing**
It can print at 250 mm/s (2000 dotlines/s) maximum by using Fujitsu Components' unique head drive control.
- **2-D Barcode printing**
QR, Maxi, PDF417
- **ELM (Easy Loading Mechanism) with lock type**
Fujitsu Components' unique platen release mechanism allows easy paper setting and easy head maintenance.
- **Auto Cutter**
Printer with auto cutter (full cut/ partial cut) is available. It can be mounted on top of the mechanism.
- **Multi-featuring diecast frame**
By application of multi-featuring diecast frame, continuous print by function of heat-sink, high ESD stand by function of earth frame and shock/vibration stand by function of solid frame are valid.
- **Compact size**
Depth: 63-70mm, width: 110-113mm, height: 37-38mm.
- **High resolution**
8 dots/mm head provides clear print out.
- **RoHS compliant**



FTP-6x9MCL364R

FTP-639MCL064/113/364/393-R

■ PART NUMBERS

Name		Part Number		
Printer mechanism	Bottom insertion	FTP-639MCL064R	FTP-629MCL105R	FTP-639MCL064R
	Detachable platen	FTP-639MCL113R	FTP-639MCL115R	FTP-639MCL113R
Mechanism with cutter	Bottom insertion	FTP-639MCL364R		FTP-639MCL364R
	Detachable platen	FTP-639MCL393R	FTP-639MCL395R	FTP-639MCL393R
LSI		FTP-629CU151R	FTP-629SR201R	FTP-629CU301R
Interface board	Parallel	FTP-629DSL283R*	FTP-629DSL281R*	---
	Serial (RS232C)	FTP-629DSL283R*	FTP-629DSL281R*	FTP-629DSL301R
	USB	FTP-629DSL232R*	FTP-629DSL212R	FTP-629DSL301R
Thermal head cable extension		---	FTP-629Y001	---
Interface cable (board to mechanism)	Parallel	FTP-628Y202		---
	Serial	FTP-628Y302	FTP-629Y302	
	USB	---	FTP-629Y301	
Power supply cable	Logic	FTP-629Y401	---	FTP-629Y602
	Head, motor	FTP-629Y601		

*1: #01 is for full cut, #02 is for partial cut

*2: Interface is selectable by DIP switch

FTP-639MCL064/113/364/393-R

■ GENERAL SPECIFICATIONS

Item		Specifications	
Part number		FTP-639MCL064/364-R	FTP-639MCL113/393#01/#02-R
Printing method		Thermal sensitive line dot method	
Dot structure		640 dots/line	
Dot pitch (horizontal)		0.125mm (8dots/mm) - Dot density	
Dot pitch (vertical)		0.125mm (8dots/mm) - Line feed pitch	
Effective printing area		80 mm	
Number of columns		ANK 53 columns/line (12 x 24 dot font) OCR 26 columns (24x40)	
Paper width		82.5mm +0/-1	
Paper thickness		60 to 150μm (there may be exceptions)	60 to 100μm
Cutting type		Standard full or partial cut	ELM full or partial
Printing speed	FTP-629DSL200 series	125mm/sec. (1000 dot lines/sec.) line mode	
	FTP-629DSL300 series	250mm/sec. (2000 dot lines/sec.) page mode	
Interface types		FTP-629DCL/DSL200 series	FTP-629DSL300 series
Character types	Alphanumeric, Kana:	159 types	159 types
	International:	195 types	195 types
	JIS Kanji (Kanji CG loaded board):	about 6800 types	about 6,800 types
	OCRI 103 types		103 types
	OCRII 23 types		23 types
	OCRIII 103 types		103 types
	Extended numeric		11 types
Character, dimensions (WxH), number of columns		8x16 dots, 80 columns: ANK 12x24 dots, 53 columns: ANK 16x16 dots, 40 columns: ANK 24x24 dots, 26 columns: ANK	24x40 dots, 26 columns, OCRI 24x48 dots, 26 columns, OCRIII 36x60 dots, 17 columns, OCRIV 24x48 dots, 26 columns, extended numeric
Interface standard		Centronics / RS232C /USB	Serial/USB

FTP-639MCL064/113/364/393-R

Item		Specifications	
Part number		FTP-639MCL064/364-R	FTP-639MCL113/393-R
Power supply	For head	24 VDC $\pm 5\%$, 3.0A (5.3A) (24V, 25% printing ratio)	
	For printer motor	24 VDC $\pm 5\%$ 1A maximum	
	For cutter motor	24 VDC $\pm 5\%$ 1A maximum	
	For logic	5 VDC $\pm 5\%$ 0.2A maximum	
Dimension W x D x H	Printer mechanism	104.2 x 40.5 x 20.5mm	104.2 x 40.5 x 20.5mm
	Printer mechanism with cutter	110.4 x 62.5 x 37.2mm	112.5 x 70.3 x 37.4mm
	Interface board (DSL200)	95 x 73.5 x 11.6mm	
	Interface board (DSL300)	77 x 50 x 21.5mm	
Weight	Printer mechanism	Approximately 125g	Approximately 125g
	Printer mechanism with cutter	Approximately 320g	Approximately 350g
	Interface board (std)	Approximately 25g	
	Interface board (medium speed)	Approximately 45 g	
	Interface board (high speed)	Approximately 20g	
Life	Head	Pulse durability: 100 million pulse/dot (using Fujitsu's standard driving method) Wear resistance: 100km (at 12.5% print ratio)	
	Cutter	500,000	1,000,000 cuts minimum
	Platen	5,000 times (open/close)	
Environmental conditions	Operating temperature	-10°C to +60°C (guarantee)	0°C to +50°C (guarantee)
	Operating humidity	20 to 85% RH (no condensation)	
	Storage temperature	-40°C to +70°C	-20°C to +60°C
	Storage humidity	5 to 95% RH (no condensation)	
Detection	Head temperature	By thermistor	
	Paper out/Mark detect	By photointerruptor	
	Head release	By slide switch	
Recommended thermal sensitive paper	High sensitive paper	TF50KS-E4 (Nippon paper)	
	Standard paper	TF60KS-E2 (Nippon paper), FTP-030P0104 (80mm) PD150R (Oji paper), FTP-030P0701 (80mm)	
	Medium life storage paper	TF60KS-F1 (Nippon paper), FTP-030P0102 (80mm) PD170R (Oji paper) P220VBB-1 (Mitsubishi paper) PD160R-N (Oji paper)	
	Long life storage paper	AFP-235 (Mitsubishi paper) TP50KJ-R (Nippon paper) HA220AA (Nippon paper)	


■ FUNCTION

ITEM		ITEM	
1.	Test printing	8.	Cutter trouble detection
2.	Paper-out detection	9.	Motor power save
3.	Paper near end detection	10.	Mark detection
4.	Head-up detection	11.	MCU trouble detection
5.	Abnormal temp. of thermal head detection	12.	Power on/off sequence protection
6.	Blown fuse detection	13.	Motor protection
7.	Abnormal voltage detection of head	14.	Hardware timer

■ DIMENSIONS

1. Printer mechanism / cutter


FTP-639MCL364R



Notes: 1. Nominal value (Tolerance +0.5, -0.5)

Unit: mm

2. Printer mechanism / cutter



■ CONNECTOR PIN ASSIGNMENT OF PRINTER MECHANISM (FPC)

1. Thermal head control circuit side

Part number : 52610-3071 (Molex) or equivalent

No	Signal	I/O	Contents	No	Signal	I/O	Contents
1	SW	O	Platen open switch	2	SW	-	Platen open switch
3	VH	I	Power for thermal head	4	V-	I	Power for thermal head
5	VH	I	Power for thermal head	6	V-	I	Power for thermal head
7	DI	I	Data in	8	STB2	I	Print enable 2
9	NC	-	Not connected	10	VDD	-	Power for logic
11	TM	-	Head Thermistor	12	GND	-	Head GND
13	GND	-	Head GND	14	GND	-	Head GND
15	GND	-	Head GND	16	GND	-	Head GND
17	GND	-	Head GND	18	GND	-	Head GND
19	GND	-	Head GND	20	GND	-	Head GND
21	TH	O	Thermistor	22	STB1	I	Print enable 1
23	NC	-	Not connected	24	$\overline{\text{LAT}}$	I	Print data latch
25	CLK	I	Clock	26	DO	O	Data out
27	VH	I	Power for thermal head	28	VH	I	Power for thermal head
29	VH	I	Power for thermal head	30	VH	I	Power for thermal head

2. Motor, Sensor (CN4)

Connector on circuit side : 52610-1071 (Molex) or equivalent

No.	Signal	I/O	Contents	No.	Signal	I/O	Contents
1	NC	-	Not connected	2	TM	O	Motor temperature sensor
3	TM	-	Motor temperature sensor	4	$\text{MT } \overline{\text{A}}$	I	Motor coil excitation /A
5	MT A	I	Motor coil excitation A	6	$\text{MT } \overline{\text{B}}$	I	Motor coil excitation /B
7	MT B	I	Motor coil excitation B	8	PHK	-	Paper out sensor cathode
9	VSEN	-	Power for paper sensor	10	$\overline{\text{PHE}}$	O	Paper out sensor emitter

3. Cutter (CN5)

Connector type: B4B-PH (J.S.T.) or equivalent

No.	Signal	I/O	Contents	No.	Signal	I/O	Contents
1	SW1	O	Cutter home position switch	2	SW2	O	Cutter home position switch
3	M+	I/O	Cutter motor drive	4	M-	I/O	Cutter motor drive

■ INTERFACE COMMAND OPTIONS

Please refer to the FTP-629DCL/DSL200 or FTP-629DSL300 series datasheet

Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141 8630, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626
Email: promothq@fcl.fujitsu.com
Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970
Email: components@us.fujitsu.com
Web: <http://us.fujitsu.com/components/>

Europe

Fujitsu Components Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950
Email: info@fceu.fujitsu.com
Web: emea.fujitsu.com/components/

Asia Pacific

Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#01-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 6375-8560
Fax: (65) 6273-3021
Email: fcal@fcal.fujitsu.com
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2013 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.
Rev. September 18, 2013.