

USB UART 2 Click



PID: MIKROE-2674

USB UART 2 click provides USB isolation and carries the ADUM4160BRWZ USB port isolator.

The click is designed to run on either 3.3V or 5V power supply. It communicates with the target microcontroller over UART interface, with additional functionality provided the following pins on the mikroBUS™ line: RST, CS, PWM, INT.

USB UART 2 click provides USB isolation and carries the [ADUM4160](#) USB port isolator, from [Analog Devices](#). The click is designed to run on either 3.3V or 5V power supply. It communicates with the target microcontroller over UART interface, with additional functionality provided the following pins on the mikroBUS™ line: RST, CS, PWM, INT.

Use the USB UART 2 click for isolating USB communication, and preventing voltage spikes from destroying sensitive equipment.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

ADUM4160BRWZ features

ADUM4160BRWZ is a USB port isolator, based on Analog Devices, Inc., iCoupler® technology. Combining high-speed CMOS and monolithic air core transformer technology, these isolation components provide outstanding performance characteristics and are easily integrated with low and full speed USB-compatible peripheral devices.

The ADUM4160BRWZ uses the edge detection based iCoupler technology in conjunction with internal logic to implement a transparent, easily configured, upstream facing port isolator. Isolating an upstream facing port provides several advantages in simplicity, power management, and robust operation.

How the click works

The click takes power both from the development system and from the USB, so both sides of the isolator can function.

The FT232RL chip on board to act as a USB-UART converter.

Specifications

Type	Isolators,USB
Applications	USB peripheral isolation, isolated USB hub, etc.
On-board modules	ADUM4160BRWZ USB port isolator, FT232 IC
Key Features	iCoupler technology in conjunction with internal logic to implement a transparent, easily configured, upstream facing port isolator
Interface	GPIO,UART,USB
Feature	No ClickID
Compatibility	mikroBUS™
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V or 5V

Pinout diagram

This table shows how the pinout on **USB UART 2 click** corresponds to the pinout on the mikroBUS™ socket (the latter shown in the two middle columns).

Notes	Pin					Pin	Notes
	NC	1	AN	PWM	16	CBUS	Factory PWR EN

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

						3	
Clear to send	CTS	2	RST	INT	15	RTS	Request to send
Factory Sleep	CBUS 4	3	CS	TX	14	TXD	UART transmit data
	NC	4	SCK	RX	13	RXD	UART receive data
	NC	5	MISO	SCL	12	NC	
	NC	6	MOSI	SDA	11	NC	
Power supply	+3.3V	7	3.3V	5V	10	+5V	Power supply
Ground	GND	8	GND	GND	9	GND	Ground

Jumpers and settings

Designator	Name	Default Position	Default Option	Description
JP1	PWR.SEL.	Left	3V3	Power Supply Voltage Selection 3V3/5V, left position 3V3, right position 5V

LEDs and buttons

Designator	Name	Type	Description
TX		LED	Shows UART TX activity
RX		LED	Shows UART RX activity

Specifications

Type	Isolators,USB
Applications	USB peripheral isolation, isolated USB hub, etc.
On-board modules	ADUM4160BRWZ USB port isolator, FT232 IC
Key Features	iCoupler technology in conjunction with internal logic to implement a transparent, easily configured, upstream facing port isolator
Interface	GPIO,UART,USB
Feature	No ClickID
Compatibility	mikroBUS™
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V or 5V

Resources

[mikroBUS™](#)

[Click board™ Catalog](#)

[Click Boards™](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

Downloads

[USB UART 2 click schematic](#)

[ADUM4160BRWZ datasheet](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).