


# Product Data Sheet

Colibri Plug 220, 5 mm,  
Part No. 401-51101-51



**COM**   
**Express**®

Illustration similar



Parallel



SMT



High Density



High Speed

- for 5 mm PCB spacing
- Overlap tolerance up to +0.6 mm
- Number of poles: 220
- SMT Connectivity
- Grid: 0.5 mm
- Data transfer rate: 10+ Gbps



» to product on [www.ept.de](http://www.ept.de)



» to product group Colibri - 0.5 mm SMT

# Product Data Sheet

Colibri Plug 220, 5 mm,  
Part No. 401-51101-51



## Technical Specifications

### Basics

Specification	PICMG® COM.0 Rev. 3.1
No. of Contacts	220
Termination Technology	SMT
Board-to-Board Distance	5 mm
Operating Temperature Range	-40°F to +125°F

### Material

Insulator Material	LCP, UL 94 V-0
CTI value <i>IEC 60112</i>	175
Contact Material	copper alloy
Plating	Above Ni
Termination area	Au flash over Ni

### Mechanical

Pitch	0.5 mm
Mating Force per Pin	max. 0.9 N
Separating Force per Pin	at least 0.1 N
Durability	30 insertion cycles
Coplanarity	max. 0.1 mm
Overmating Distance	0.6 mm
Center offset in the x direction	± 0.4 mm
Center offset in the y direction	± 0.19 mm
Axial offset when mated (x/y)	± 0.1 mm (8 mm height) / ± 0.115 mm (5 mm height)
Angular offset in the x direction	± 2°

### Electrical

Operational Current	max. 0.5 A
Operational Voltage	50 VAC
Contact Resistance	max. 75 mΩ
Clearance and Creepage	≥ 0.15 mm
Insulation Resistance	> 100 MΩ
Test Voltage	200 VAC
Data Transfer Rate	10 Gbit/s

# Product Data Sheet

Colibri Plug 220, 5 mm,  
Part No. 401-51101-51



---

## Technical Specifications

### Processing

---

Soldering Temperature 260°C according to J-STD-020

MSL 1

Assembly Pick and Place

### Approval / Compliance

---

UL file E130314

Environment RoHS compliant

# Product Data Sheet

Colibri Plug 220, 5 mm,  
Part No. 401-51101-51

---



## Derating Diagram

# Product Data Sheet

Colibri Plug 220, 5 mm,  
Part No. 401-51101-51

---



## Options

for the connector with pick & place cap use part number 401-51151-51

## Modifications

Available on request

- other pole counts
- other stack heights
- alternative contact coatings

## Drawings

Component data in 2D and 3D format you can download here:

» [PDF](#)

» [3D IGES](#)

» [3D STEP](#)

» [3D PDF](#)