



STOCK CHECK

M83513/26-G02NP

- DESCRIPTION
- SUPPORT
- REQUEST QUOTE
- DOCUMENTS

MIL-DTL-83513 PCB Mounted Connector, Socket, 51 Positions, Shell Finish - Nickel, Female, PCB Solder Pins, 0.140" (3.56 mm) Pin Length, Jackpost Attached

Connector Type	Socket
Number of Positions	51
Shell Material	Aluminum alloy
Shell Finish	Nickel
Insulation Material	Polyester, glass filled
Contact Gender	Female
Contact Material	Copper alloy
Contact Finish	Gold
Termination Type	PCB Solder Pins
Solder Pin Length in. (mm)	0.140 in (3.56 mm)
Mounting Hardware	Jackpost Attached
Min Operating Temp. °F (°C)	-65°F (-55°C)
Max Operating Temp. °F (°C)	255°F (125°C)
Current Rating	3 Amps
Dielectric Withstanding Voltage	600 VAC RMS @ sea level
Contact Resistance	8 mΩ
Max Mating Cycles	500
Contact Insertion Force	6 oz (170 gm)
Contact Withdrawal Force	0.5 oz (14 gm)

RECOMMENDED PRODUCTS



M83513/23-G03NP
[Dura-Con™ MIL-DTL-83513 PCB Mount Connectors](#)

See Details



M83513/19-E01NP
[Dura-Con™ MIL-DTL-83513 PCB Mount Connectors](#)

See Details



M83513/13-B02NP
[Dura-Con™ MIL-DTL-83513 PCB Mount Connectors](#)

See Details

Products

- Cable Assemblies
- Circuit Protection
- Connectors
- Linear Transformers

Bel Groups

- Bel Fuse-Circuit Protection
- Bel Magnetic Solutions
- Bel Power Solutions
- Cinch Connectivity Solutions

Information

- Contact Us
- Privacy Statement

Connect with Us

Explore Bel

- About Us
- Bel Extranet
- Careers
- Investors

Magnetic Solutions
Power Solutions
See All

Signal Transformer
Stewart Connector
TRP Connector



News Room

Copyright © 2018, Bel Fuse Inc. All Rights Reserved.

