




PRODUCT NUMBER: 0712-0-33-15-08-27-10-0

www.mill-max.com
DATA SHEET



0712-0-33-15-08-27-10-0 SPECIFICATIONS

General Info	
Description ¹ :	Wire Termination
	Receptacle - Crimp Type
Mounting Feature:	Wire Mount
Pin Diameter .084"-.102" (2,134-2,591mm)	
Packaging: Packaged in Bulk	
RoHS ² : Yes	
Product Lifecycle ³ : Active	


Materials	
Shell Material ⁴ : Brass Alloy	
Shell Plating ⁵ : 10 µ" Gold over Nickel	
Contact Plating ⁶ : 30 µ" Gold over Nickel	

Technical Specs	
Durability ⁷ : 1,000 Cycles Minimum	
Operating Temperature Range ⁸ : -55/+125° C	
Current Rating ⁹ : 18A @ 10°C Temperature Rise	
Contact Resistance ¹⁰ : 10 mΩ Max	
Shock ¹¹ : No Elect. Discontinuity > 1µs @ 50g	
Vibration ¹² : No Elect. Discontinuity > 1µs @ 10-2000HZ, 20 G	

NOTES:

- 1. Standard Tolerances:
Lengths +/- .005" (0,13)
Diameters: +/- .002" (0,051)
Angles: +/- 2°
- 2. Mill-Max products labeled with the RoHS symbol are compliant with all three ROHS Directives. All of our products previously described as RoHS (2002/95/EC) and RoHS-2 (2011/65/EC) are also compliant with RoHS-3 (2015/863/EU).
- 3. Part is Active and in Production, No Scheduled Obsolescence
- 4. Brass Alloy 360 per ASTM B 16, or 385 per ASTM B455
- 5. GOLD per ASTM B 488, Type 1 (99.7% min. gold), Code C (130-200 HK {Knoop hardness}); NICKEL per ASTM B 689, Type 2 (Bright),
- 6. GOLD per ASTM B 488, Type 1 (99.7% min. gold), Code C (130-200 HK {Knoop hardness}), NICKEL per ASTM B 689, Type 2 (Bright)
- 7. Receptacles are capable of 1,000 Minimum insertion/extraction cycles for a broad range of applications. Mating pin size, shape and finish, along with application specific variables, will affect the life of a receptacle contact.
- 8. Per IEC 60512-11-(4,-9,-10,-12)
- 9. Per IEC 60512-5-1, Current Carrying Capacity (evaluated at 10° C Temp. Rise)
- 10. Per EIA-364-23C, Low Level Contact Resistance
- 11. Per IEC 60512-6-3: Test 6c: Shock
- 12. Per IEC 60512-6-4: Test 6d: Vibration (sinusoidal)

CONTACT:



ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance , Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

RELATED LINKS AND DOCUMENTS

Engineering Notebook: (<https://www.mill-max.com/engineering-notebooks/precision-machined-crimp-pins-and-receptacles>)

Environmental Compliance: (<https://www.mill-max.com/rohs>)