Complementary Silicon Power Transistors

2N3055(NPN), MJ2955(PNP)

Complementary silicon power transistors are designed for general−purpose switching and amplifier applications.

15 AMPERE POWER TRANSISTORS COMPLEMENTARY SILICON 60 VOLTS, 115 WATTS

Features

- DC Current Gain − h_{FE} = 20−70 @ I_C = 4 Adc
- Collector−Emitter Saturation Voltage − $V_{CE(sat)}$ = 1.1 Vdc (Max) @ I_C = 4 Adc
- Excellent Safe Operating Area
- Pb−Free Packages are Available*



TO−204AA (TO−3)
CASE 1−07
STYLE 1

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	60	Vdc
Collector−Emitter Voltage	V_{CER}	70	Vdc
Collector−Base Voltage	V_{CB}	100	Vdc
Emitter−Base Voltage	V_{EB}	7	Vdc
Collector Current − Continuous	I_C	15	Adc
Base Current	I_B	7	Adc
Total Power Dissipation @ T_C = 25°C Derate Above 25°C	P_D	115 0.657	W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +200	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



Figure 1. Power Derating

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

MARKING DIAGRAM

xxxx55	=	Device Code xxxx = 2N30 or MJ20
G	=	Pb−Free Package
A	=	Location Code
YY	=	Year
WW	=	Work Week
MEX	=	Country of Orgin

ORDERING INFORMATION

Device	Package	Shipping
2N3055	TO−204AA	100 Units / Tray
2N3055G	TO−204AA (Pb−Free)	100 Units / Tray
MJ2955	TO−204AA	100 Units / Tray
MJ2955G	TO−204AA (Pb−Free)	100 Units / Tray

Preferred devices are recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2005

Downloaded from Arrow.com.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	1.52	°C/W

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS*				
Collector−Emitter Sustaining Voltage (Note 1) (I_C = 200 mAdc, I_B = 0)	$V_{CEO(sus)}$	60	–	Vdc
Collector−Emitter Sustaining Voltage (Note 1) (I_C = 200 mAdc, R_{BE} = 100 Ω)	$V_{CER(sus)}$	70	–	Vdc
Collector Cutoff Current (V_{CE} = 30 Vdc, I_B = 0)	I_{CEO}	–	0.7	mAdc
Collector Cutoff Current (V_{CE} = 100 Vdc, $V_{BE(off)}$ = 1.5 Vdc) (V_{CE} = 100 Vdc, $V_{BE(off)}$ = 1.5 Vdc, T_C = 150°C)	I_{CEX}	 – –	 1.0 5.0	mAdc
Emitter Cutoff Current (V_{BE} = 7.0 Vdc, I_C = 0)	I_{EBO}	–	5.0	mAdc
ON CHARACTERISTICS* (Note 1)				
DC Current Gain (I_C = 4.0 Adc, V_{CE} = 4.0 Vdc) (I_C = 10 Adc, V_{CE} = 4.0 Vdc)	h_{FE}	 20 5.0	 70 –	–
Collector−Emitter Saturation Voltage (I_C = 4.0 Adc, I_B = 400 mAdc) (I_C = 10 Adc, I_B = 3.3 Adc)	$V_{CE(sat)}$	 –	 1.1 3.0	Vdc
Base−Emitter On Voltage (I_C = 4.0 Adc, V_{CE} = 4.0 Vdc)	$V_{BE(on)}$	–	1.5	Vdc
SECOND BREAKDOWN				
Second Breakdown Collector Current with Base Forward Biased (V_{CE} = 40 Vdc, t = 1.0 s, Nonrepetitive)	$I_{s/b}$	2.87	–	Adc
DYNAMIC CHARACTERISTICS				
Current Gain − Bandwidth Product (I_C = 0.5 Adc, V_{CE} = 10 Vdc, f = 1.0 MHz)	f_T	2.5	–	MHz
*Small−Signal Current Gain (I_C = 1.0 Adc, V_{CE} = 4.0 Vdc, f = 1.0 kHz)	h_{fe}	15	120	–
*Small−Signal Current Gain Cutoff Frequency (V_{CE} = 4.0 Vdc, I_C = 1.0 Adc, f = 1.0 kHz)	f_{hfe}	10	–	kHz

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

*Indicates Within JEDEC Registration. (2N3055)

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.



Figure 2. Active Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 2 is based on T_C = 25°C; $T_{J(pk)}$ is variable depending on power level. Second breakdown pulse limits are valid for duty cycles to 10% but must be derated for temperature according to Figure 1.

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.



Figure 3. DC Current Gain, 2N3055 (NPN)



Figure 4. DC Current Gain, MJ2955 (PNP)



Figure 5. Collector Saturation Region, 2N3055 (NPN)



Figure 6. Collector Saturation Region, MJ2955 (PNP)



Figure 7. “On” Voltages, 2N3055 (NPN)



Figure 8. “On” Voltages, MJ2955 (PNP)

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.



SCALE 1:1

TO−204 (TO−3)
CASE 1−07
ISSUE Z

DATE 10 MAR 2000



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. ALL RULES AND NOTES ASSOCIATED WITH REFERENCED TO−204AA OUTLINE SHALL APPLY.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	1.550 REF		39.37 REF	
B	---	1.050	---	26.67
C	0.250	0.335	6.35	8.51
D	0.038	0.043	0.97	1.09
E	0.055	0.070	1.40	1.77
G	0.430 BSC		10.92 BSC	
H	0.215 BSC		5.46 BSC	
K	0.440	0.480	11.18	12.19
L	0.665 BSC		16.89 BSC	
N	---	0.830	---	21.08
Q	0.151	0.165	3.84	4.19
U	1.187 BSC		30.15 BSC	
V	0.131	0.188	3.33	4.77

STYLE 1:
PIN 1. BASE
2. EMITTER
CASE: COLLECTOR

STYLE 2:
PIN 1. BASE
2. COLLECTOR
CASE: EMITTER

STYLE 3:
PIN 1. GATE
2. SOURCE
CASE: DRAIN

STYLE 4:
PIN 1. GROUND
2. INPUT
CASE: OUTPUT

STYLE 5:
PIN 1. CATHODE
2. EXTERNAL TRIP/DELAY
CASE: ANODE

STYLE 6:
PIN 1. GATE
2. EMITTER
CASE: COLLECTOR

STYLE 7:
PIN 1. ANODE
2. OPEN
CASE: CATHODE

STYLE 8:
PIN 1. CATHODE #1
2. CATHODE #2
CASE: ANODE

STYLE 9:
PIN 1. ANODE #1
2. ANODE #2
CASE: CATHODE

DOCUMENT NUMBER:	**98ASB42001B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TO−204 (TO−3)**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

Downloaded from Arrow.com.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Downloaded from Arrow.com.