


4G/LTE Flexible Printed Antenna



AFAC110020-S698

110.0 x 20.0 x 0.2 mm
RoHS/RoHS II Compliant
MSL - 1

FEATURES

- Operates in 698-2700 MHz
- Linear polarization
- Low VSWR
- Low profile
- Omni-directional pattern
- IPEX connector with cable

APPLICATIONS

- Cellular
- Transportation
- Industrial wearable
- Smart city
- Smart agriculture
- Home automation

Electrical Specifications

Parameters	Min.	Typ.	Max.	Units	Note
Frequency Range		698~960/1710~2690		MHz	
VSWR			2.0		
Polarization Model	Linear				
Impedance		50		Ω	
Gain		3.0		dBi	

Mechanical Characteristics

Parameters	Description
Connector	IPEX
Cable Type	100mm/RF1.13
Mounting	Embedded
FPC Dimensions	110 x 20 x 0.2 mm

Environmental Characteristics

Parameters	Note
Operating Temperature	-40°C to +85°C
Vibration	10 to 55Hz with 1.5mm amplitude 2 hours
ROHS Compliant	Yes
MSL Level	1




5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 01.25.2019

ABRACON IS
ISO9001-2015
CERTIFIED


4G/LTE Flexible Printed Antenna



AFAC110020-S698

110.0 x 20.0 x 0.2 mm
RoHS/RoHS II Compliant
MSL - 1

Dimensions




Product Image



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 01.25.2019


ABRACON IS
ISO9001-2015
CERTIFIED



AFAC110020-S698

110.0 x 20.0 x 0.2 mm
RoHS/RoHS II Compliant
MSL - 1




VSWR




AFAC110020-S698

110.0 x 20.0 x 0.2 mm
RoHS/RoHS II Compliant
MSL - 1

Radiation Patterns






AFAC110020-S698

110.0 x 20.0 x 0.2 mm
RoHS/RoHS II Compliant
MSL - 1


Radiation Patterns

3D-Pattern


698 MHZ




824 MHZ




868 MHZ




960 MHZ




1710 MHZ




1850 MHZ




1990 MHZ




2170 MHZ



2690 MHZ



4G/LTE Flexible Printed Antenna



AFAC110020-S698

110.0 x 20.0 x 0.2 mm
RoHS/RoHS II Compliant
MSL - 1

Gain and Efficiency

Frequency (MHz)	Efficiency	Gain (dBi)
698	0.43	0.53
824	0.58	3.02
868	0.59	3.04
960	0.46	2.82
1710	0.39	-6.96
1850	0.42	-0.69
1990	0.47	1.51
2170	0.56	2.46
2690	0.56	2.53

Packaging

Each 37 x 36 x 17 cm size carton includes 1000 pcs antenna, weighs 8 kg



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 01.25.2019

ABRACON IS
ISO9001-2015
CERTIFIED