

SIGNAL RELAYS



Active

See All Documentation

TE CONNECTIVITY
V23054D1021F104

Axicom | Cradle Relay S

9-1393812-4
TE Internal Number: 9-1393812-4
Alias ID: V23054D1021F104

- Converted to EU RoHS/ELV Compliant
- Contact Voltage Rating **250VAC[260VDC]**
- Coil Power Rating (DC)(mW) **736**
- Insulation Initial Resistance(MΩ) **1000**
- Mounting Type **Screw Mount, Socket**
- Terminal Type **Plug-In, Solder**
- See All Features

North America

Contact us to request pricing, availability and customization options.

REQUEST ADDITIONAL INFORMATION



GET SAMPLE



SAVE TO LIST



CHECK FOR TOOLING



FIND SIMILAR PRODUCTS



DOCUMENTATIONFEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Relay Style	Cradle S Relay
Product Type	Relay
Relay Type	Cradle S Relay V23054/V23062

Electrical Characteristics

Contact Voltage Rating	250VAC[260VDC]
Coil Power Rating (DC)(mW)	736
Insulation Initial Resistance(MΩ)	1000
Contact Switching Voltage (Max)	250VAC[260VDC]
Coil Magnetic System	Monostable, DC
Insulation Initial Dielectric Between Coil/Contact Class	500 – 1000 V
Insulation Initial Dielectric Between Adjacent Contacts(Vrms)	100
Insulation Initial Dielectric Between Contacts and Coil(Vrms)	1000
Contact Limiting Making Current(A)	5
Insulation Initial Dielectric Between Open Contacts(Vrms)	500
Actuating System	DC
Contact Limiting Short-Time Current(A)	5
Contact Limiting Continuous Current(A)	5
Coil Resistance(Ω)	1050
Contact Limiting Breaking Current(A)	5
Power Consumption(mW)	800
Coil Power Rating Class	800 – 1000 mW
Coil Type	Monostable

Body Features

Weight	25g[.881oz]
--------	-------------

Contact Features

Terminal Type	Plug-In, Solder
Contact Current Rating(A)	2
Contact Arrangement	4 Form C (CO)
Contact Material	Ag
Contact Number of Poles	2
Contact Current Class	2 – 5 A
Contact Plating Material	Gold Flash

Termination Features

Termination Type	Solder Terminals
------------------	------------------

Mechanical Attachment

Mounting Type	Screw Mount, Socket
---------------	---------------------

Dimensions

Length Class (Mechanical)	25 – 30 mm
Width Class (Mechanical)	16 – 20 mm
Length	30mm[1.181in]
Width	19mm[.748in]
Height Class (Mechanical)	25 – 30 mm
Height	30mm[1.181in]

Usage Conditions

Environmental Category of Protection	RTI
Operating Temperature Range(°C)	-40 – 70
Environmental Ambient Temperature (Max)	70°C[158°F]
Environmental Ambient Temperature Class	50 – 70°C

Operation/Application

Performance Type	Standard
------------------	----------

Packaging Features

Packaging Method	Box/Carton
------------------	------------

Product Compliance

Statement of Compliance
PDF
VIEW ALL PRODUCT COMPLIANCE

COMPATIBLE

No compatible products found for 9-1393812-4